




NATIONAL AERONAUTICS AND SPACE ADMINISTRATION

NASA CR-

134421



(NASA-CR-134421) EFFECTS OF WING/ELEVON
GAP SEALING FLAPPER DOORS ON ORBITER
ELEVON EFFECTIVENESS OF MODEL 16-0 IN
THE NAAL 7.75 BY 11 FOOT (Chrysler
Corp.) 288 p HC \$8.75


N75-12035

Unclas
GJ/18 03605

CSCL 22B

SPACE SHUTTLE

AEROTHERMODYNAMIC DATA REPORT



JOHNSON SPACE CENTER

HOUSTON, TEXAS

DATA Management services



October, 1974

DMS-DR-2187
NASA CR-134,421

EFFECTS OF WING/ELEVON GAP SEALING
FLAPPER DOORS ON ORBITER ELEVON
EFFECTIVENESS OF MODEL 16-0 IN THE NAAL
7.75 X 11-FOOT CONTINUOUS FLOW WIND TUNNEL
(OA119A)

By

R. Menell
Shuttle Aero Sciences
Rockwell International Space Division

Prepared under NASA Contract Number NAS9-13247

by

Data Management Services
Chrysler Corporation Space Division
New Orleans, La. 70189

for

Engineering Analysis Division
Johnson Space Center
National Aeronautics and Space Administration
Houston, Texas

WIND TUNNEL TEST SPECIFICS:

Test Number: NAAL 726
NASA Series Number: OA119A
Model Number: 16-0
Test Dates: 18 through 24 June 1974
Occupancy Hours: 45

FACILITY COORDINATOR:

R. B. Russell
Mail Code BD02
Rockwell International B-1 Division
Los Angeles, California 90009

Phone: (213) 670-9151 x3343

PROJECT ENGINEER:

R. Mennell
Mail Code BD02
Rockwell International
B-1 Division
Los Angeles, California 90009

Phone: (213) 670-9151 x3343

AERODYNAMICS ANALYSIS ENGINEER:

F. F. Fitzgerald
Mail Code AC07
Rockwell International
Space Division
Downey, California 90241

Phone: (213) 922-4430

DATA MANAGEMENT SERVICES:

Prepared by: Liaison--D. A. Sarver, M. J. Lanfranco
Operations--R. B. Lowe

Reviewed by: D. E. Poucher, J. L. Glynn

Approved: *N. D. Kemp*
N. D. Kemp, Manager
Data Management Services

Concurrence: *R. D. Taylor*
ru J. G. Swider, Manager
Flight Technology Branch

Chrysler Corporation Space Division assumes no responsibility for the data presented other than display characteristics.

EFFECTS OF WING/ELEVON GAP SEALING
FLAPPER DOORS ON ORBITER ELEVON
EFFECTIVENESS OF MODEL 16-0 IN THE NAAL
7.75 X 11-FOOT CONTINUOUS FLOW WIND TUNNEL (OA119A)

By

R. Mennell, Rockwell International Space Division

ABSTRACT

Experimental aerodynamic investigations were conducted on a sting-mounted 0.0405-scale representation of the 140A/B inner mold line Space Shuttle Orbiter in the Rockwell International 7.75 x 11.00 Foot Low Speed Wind Tunnel during the time period from June 18, 1974 to June 24, 1974. The NASA designation for this test period was OA119A.

The primary test objective was to define IML Orbiter elevon effectiveness with the 6" elevon/elevon and elevon/fuselage gaps and various configurations of wing/elevon upper hingeline gap sealing "flapper" doors. The elevon configuration parametric variations consisted of sealing the lower hingeline to prevent flow-through and testing a long chord flapper door, a short chord flapper door, no flapper door (elevon/wing gap upper hingeline completely open), and a completely sealed elevon at elevon deflections from +20° to -40° ($\delta_a = 0$).

Preliminary data analysis indicates loss of elevon effectiveness at deflections more negative than -20° (consistent with previous results) and little or no effect of flapper door configuration on elevon effectiveness. Flow visualization photographs taken at $\alpha = 15^\circ$ for two flapper door configurations substantiated the force data results.

For this test period aerodynamic force and moment data were measured in the body axis by a 2.5-inch Task type internal strain gage balance. The model was sting supported through the base region with a nominal angle-of-attack range of $-10^\circ \leq \alpha \leq 24^\circ$ at a model angle of sideslip of $\beta = 0^\circ$.

TABLE OF CONTENTS

	Page
ABSTRACT	iii
INDEX OF MODEL FIGURES	2
INDEX OF DATA FIGURES	3
NOMENCLATURE	5
CONFIGURATIONS INVESTIGATED	8
TEST FACILITY DESCRIPTION	10
DATA REDUCTION	11
TABLES	
I. TEST CONDITIONS	13
II. DATA SET/RUN NUMBER COLLATION SUMMARY	14
III. MODEL DIMENSIONAL DATA	17
FIGURES	
MODEL	31
DATA	39
APPENDIX	
TABULATED SOURCE DATA	

INDEX OF MODEL FIGURES

<u>Figure</u>	<u>Title</u>	<u>Page</u>
1.	Axis systems.	
	a. General	31
	b. Sign Convention for Control Surfaces	32
2.	Model sketches.	
	a. General Arrangement -140 Orbiter	33
	b. Long Flapper Door Configuration E46	34
	c. Short Flapper Door Configuration E47	35
3.	Model photographs.	
	a. Rear View, NAAL Installation Configuration B61 C11 M51 F12 W124 E46 V19 R15 X29	36
	b. Side View, Left Wing, Short Flapper Door Configuration E47	36
	c. Side View, Left Wing, Elevon/Wing Gap Open Configuration E49	37
	d. Side View, Left Wing, Long Flapper Door Configuration E46	37
	e. Rear View, Right Wing, Flow Visualization of Elevon/Wing Gap Open Configuration E51	38
	f. Rear View, Right Wing, Flow Visualization of Completely Sealed Elevon Configuration E48	38

INDEX OF DATA FIGURES

FIGURE NUMBER	TITLE	SCHEDULE OF COEFFICIENTS PLOTTED	CONDITIONS VARYING	PAGES
Fig. 4	Elevon Effectiveness - Elevon E46 (Positive Elevon Deflections)	A	ELEVON	1-10
Fig. 5	Elevon Effectiveness - Elevon E46 (Negative Elevon Deflections)	A	ELEVON	11-20
Fig. 6	Elevon Effectiveness - Elevon E47 (Positive Elevon Deflections)	A	ELEVON	21-30
Fig. 7	Elevon Effectiveness - Elevon E47 (Negative Elevon Deflections)	A	ELEVON	31-40
Fig. 8	Elevon Effectiveness - Elevon E48 (Positive Elevon Deflections)	A	ELEVON	41-50
Fig. 9	Elevon Effectiveness - Elevon E48 (Negative Elevon Deflections)	A	ELEVON	51-60
Fig. 10	Elevon Effectiveness - Elevons E49 and E51 (Positive Elevon Deflections)	A	ELEVON & CONFIG.	61-70
Fig. 11	Elevon Effectiveness - Elevons E49 and E51 (Negative Elevon Deflections)	A	ELEVON & CONFIG.	71-80
Fig. 12	Effect of Flapper Door on Elevon Effectiveness, Elevon = 0 and 5 Deg	A	ELEVON & CONFIG.	81-90
Fig. 13	Effect of Flapper Door on Elevon Effectiveness, Elevon = 10 and 15 Deg	A	ELEVON & CONFIG.	91-100
Fig. 14	Effect of Flapper Door on Elevon Effectiveness, Elevon = 20 Deg	A	CONFIG.	101-110

INDEX OF DATA FIGURES (Continued)

FIGURE NUMBER	TITLE	SCHEDULE OF COEFFICIENTS PLOTTED	CONDITIONS VARYING	PAGES
Fig. 15	Effect of Flapper Door on Elevation Effectiveness, Elevation = -10 and -15 Deg	A	ELEVON & CONFIG.	111-120
Fig. 16	Effect of Flapper Door on Elevation Effectiveness, Elevation = -20 and -30 Deg	A	ELEVON & CONFIG.	121-130
Fig. 17	Effect of Flapper Door on Elevation Effectiveness, Elevation = -40 Deg	A	CONFIG.	131-140
Fig. 18	Effect of Wing/Elevation Gap on Elevation Effectiveness, Elevation = 0, 10, 15	A	ELEVON & CONFIG.	141-150
Fig. 19	Effect of Wing/Elevation Gap on Elevation Effectiveness, Elevation = 20 Deg	A	CONFIG.	151-160
Fig. 20	Effect of Wing/Elevation Gap on Elevation Effectiveness, Elevation = 0, -10, -20	A	ELEVON & CONFIG.	161-170
Fig. 21	Effect of Wing/Elevation Gap on Elevation Effectiveness, Elevation = -30, -40	A	ELEVON & CONFIG.	171-180
Fig. 22	Effect of Elevation Hingeline Roughness	A	CONFIG.	181-190
Fig. 23	Body Flap Effectiveness	A	ELEVON & BDFLAP	191-200

SCHEDULE OF COEFFICIENTS PLOTTED:

(A) CLF, CN, CAF, CAB, CDF, CLM, L/DF and XCP/L versus ALPHA

CLF versus CLM

CLF versus CDF

NOMENCLATURE
General

<u>SYMBOL</u>	<u>PLOT SYMBOL</u>	<u>DEFINITION</u>
a		speed of sound; m/sec, ft/sec
C _p	CP	pressure coefficient; $(p_1 - p_\infty)/q$
M	MACH	Mach number; V/a
p		pressure; N/m ² , psf
q	Q(NSM) Q(PSF)	dynamic pressure; $1/2\rho V^2$, N/m ² , psf
RN/L	RE/L	unit Reynolds number; per m, per ft
V		velocity; m/sec, ft/sec
α	ALPHA	angle of attack, degrees
β	BETA	angle of sideslip, degrees
ψ	PSI	angle of yaw, degrees
ϕ	PHI	angle of roll, degrees
ρ		mass density; kg/m ³ , slugs/ft ³

Reference & C.G. Definitions

A _b		base area; m ² , ft ²
b	BREF	wing span or reference span; m, ft
c.g.		center of gravity
$\frac{l}{c}$ _{REF}	LREF	reference length or wing mean aerodynamic chord; m, ft
S	SREF	wing area or reference area; m ² , ft ²
	MRP	moment reference point
	XMRP	moment reference point on X axis
	YMRP	moment reference point on Y axis
	ZMRP	moment reference point on Z axis

SUBSCRIPTS

b	base
l	local
t	total conditions
∞	free stream
0	free stream

NOMENCLATURE (Continued)

Body-Axis System

<u>SYMBOL</u>	<u>PLOT SYMBOL</u>	<u>DEFINITION</u>
C_N	CN	normal-force coefficient; $\frac{\text{normal force}}{qS}$
C_A	CA	axial-force coefficient; $\frac{\text{axial force}}{qS}$
C_Y	CY	side-force coefficient; $\frac{\text{side force}}{qS}$
C_{A_b}	CAB	base-force coefficient; $\frac{\text{base force}}{qS}$ $-A_b(p_b - p_o)/qS$
C_{A_f}	CAF	forebody axial force coefficient, $C_A - C_{A_b}$
C_m	CLM	pitching-moment coefficient; $\frac{\text{pitching moment}}{qS l_{REF}}$
C_n	CYN	yawing-moment coefficient; $\frac{\text{yawing moment}}{qS b}$
C_l	CBL	rolling-moment coefficient; $\frac{\text{rolling moment}}{qS b}$

Stability-Axis System

C_L	CL	lift coefficient; $\frac{\text{lift}}{qS}$
C_D	CD	drag coefficient; $\frac{\text{drag}}{qS}$
C_{D_b}	CDB	base-drag coefficient; $\frac{\text{base drag}}{qS}$
C_{D_f}	CDF	forebody drag coefficient; $C_D - C_{D_b}$
C_Y	CY	side-force coefficient; $\frac{\text{side force}}{qS}$
C_q	CLM	pitching-moment coefficient; $\frac{\text{pitching moment}}{qS l_{REF}}$
C_n	CLN	yawing-moment coefficient; $\frac{\text{yawing moment}}{qS b}$
C_l	CCL	rolling-moment coefficient; $\frac{\text{rolling moment}}{qS b}$
L/D	L/D	lift-to-drag ratio; C_L/C_D
L/D_f	L/D _f	lift to forebody drag ratio; C_L/C_{D_f}

NOMENCLATURE (Concluded)
Additions to Standard List

<u>Symbol</u>	<u>Plot Symbol</u>	<u>Definition</u>
A_B		fuselage base area, ft ²
A_{BC}		balance cavity area, ft ²
C_{A_B}		fuselage base axial-force coefficient adjustment
$C_{A_{BC}}$		balance cavity axial-force coefficient adjustment
C_{A_T}		model weight tare axial-force coefficient
P_{BC}		balance cavity pressure, psia
$P_{B1}, P_{B2}, \dots, P_{B8}$		base pressure at stations 1 through 8, respectively, psia
L_B		reference body length, in.
δ_a	AILRON	aileron deflection angle, deg.
δ_{BF}	BDFLAP	bodyflap deflection angle, deg.
δ_e	ELEVON	elevon deflection angle, deg.
δ_R	RUDDER	rudder deflection angle, deg.
δ_{SB}	SPDBRK	speedbrake deflection angle, deg.
X_{cp}/L_B	XCP/L	longitudinal center of pressure location/body length
C_{L_f}	CLF	forebody lift coefficient

CONFIGURATIONS INVESTIGATED

The model provided for test period 0A119A was an 0.0405-scale representation of the 140A/B Space Shuttle Orbiter Inner Mold Line Configuration. The basic model was of the blended wing-body design utilizing a double delta wing ($75^\circ/45^\circ_{LE}$), full span, split elevons (unswept hingeline), a centerline vertical tail with rudder and/or speedbrake deflection capability, a canopy, a bodyflap, and an orbital maneuvering system (OMS) mounted on the aft fuselage sidewalls adjacent to the vertical tail.

This inner mold line configuration represents the Orbiter inner structural lines with all thermal protection systems (TPS) removed. All vehicle lines were per SD drawing VL70-000233 except as indicated (see dimensional data).

During this test period several configurations of wing/elevon upper hingeline gap sealing "flapper" doors were evaluated. The various configurations consisted of a long chord flapper door, a short chord flapper door, and no flapper door. All testing was with the lower elevon hingeline sealed to prevent flow through from the lower wing surface to the upper wing surface.

For this test period the following nomenclature was used to designate the various model components:

<u>Component</u>	<u>Description</u>
B ₆₁	140A/B Inner Mold Line Orbiter Fuselage
C ₁₁	140A/3 Canopy used on Fuselage B ₆₁

CONFIGURATIONS INVESTIGATED (Concluded)

E₄₆ 140A/B Elevon used on Wing W₁₂₄, 6" elevon gaps, long chord flapper door

E₄₇ 140A/B Elevon used on Wing W₁₂₄, 6" elevon gaps, short chord flapper door

E₄₈ 140A/B Elevon used on Wing W₁₂₄, 6" elevon gaps, no flapper door, upper hingeline sealed

E₄₉ Same as E₄₈ except upper hingeline unsealed

E₅₀ Same as E₄₆ except elevon lower surface leading edge has been "smoothed"

E₅₁ Same as E₄₉ except elevon lower surface leading edge has been "smoothed"

F₁₂ 140A/B Bodyflap used on Fuselage B₆₁

M₅₁ 140A/B Orbital Maneuvering System used on Fuselage B₆₁

R₁₅ 140A/B Rudder used on Vertical Tail V₁₉

V₁₉ 140A/B Inner Mold Line Centerline Vertical Tail

W₁₂₄ 140A/B Inner Mold Line Double Delta Wing

X₂₉ Transition grit located on Fuselage nose and all swept surfaces

TEST FACILITY DESCRIPTION

North American Aerodynamics Laboratory (NAAL) 7.75 x 11-foot Wind Tunnel is a continuous flow, closed circuit, single return tunnel capable of speeds up to 200 miles per hour.

The test section is vented to atmospheric pressure and is 7.75 x 11 feet wide and 12 feet long. Power is supplied by a 1250-horsepower nacelle-mounted synchronous motor driving a 19-foot, seven-blade, laminated birch propeller. Airspeed is controlled by using a magnetic clutch to vary the degree of coupling between the motor and propeller. Turbulence is minimized by a damping screen and a honeycomb section in the settling chamber upstream from the contraction cone (ratio 7.53 to 1).

Tests may be conducted using a variety of mounting systems: single strut, double strut, sting strut, reflection plane, cable suspension, or two-dimensional wall. Aerodynamic data may be measured by a planar type external balance system or sting-mounted internal balances. An Astrodata Automatic Data Acquisition System collects, multiplexes, digitizes, and records on magnetic tape 50 channels of force or pressure data or both. Data are then reduced and plotted using automatic data processing equipment and an automatic digital plotter.

The NAAL Wind Tunnel has been operating since June 1943. Calibrations are available over a wide range of test conditions.

DATA REDUCTION

The aerodynamic force and moment data presented were measured by the Task Corporation 2.5-inch MK IX Internal Strain Gage Balance. The data have been corrected for model base and balance chamber pressure effects, model blockage influence on tunnel dynamic pressure, wall interference effects, sting and balance deflections, and model weight tare.

The corrections made to the axial-force coefficient were accomplished in the following manner:

$$C_{A_f} = C_A - C_{A_{BC}} - C_{A_B} - C_{A_T}$$

where C_A = balance axial force coefficient

$$C_{A_{BC}} = - \left(\frac{P_{BC} - P_0}{q} \right) \left(\frac{A_{BC}}{S} \right)$$

$$C_{A_B} = - \left(\frac{P_B - P_\infty}{q} \right) \left(\frac{A_B}{S} \right), \quad P_B = 1/8 (P_{B1} + P_{B2} + \dots + P_{B8})$$

C_{A_T} = model axial force coefficient weight tare

The following reference dimensions and model constants were used for reducing all aerodynamic data to coefficient form:

<u>Symbol</u>		Full Scale	Model Scale
A_B	Area of model base, ft ² (not including A_{BC})		0.5885
A_{BC}	Area of balance cavity, ft ²		0.0985
b	Wing span, in.	936.68	37.9356

DATA REDUCTION (Concluded)

\bar{c}	Wing M.A.C., in.	474.81	19.2300
X_{MRP}	Reference MRP, in. aft of nose ($X_0 = 235$)	841.48	34.0799
	Reference MRP, fus. sta., in.	1076.48	43.5974
Z_{MRP}	Reference C.G., waterplane, in.	375.00	15.1875
L_B	Length Orbiter body, in.	1290.30	52.2572
S	Wing area, ft ²	2690.00	4.4123

TABLE I.

TEST : 0A119A NAAL 726		DATE : 6-28-74	
TEST CONDITIONS			
MACH NUMBER	REYNOLDS NUMBER (per foot)	DYNAMIC PRESSURE (pounds/sq. inch)	STAGNATION TEMPERATURE (degrees Fahrenheit)
0.26	$1.85 \times 10^6/\text{ft.}$	100 lbs/ft^2	$90 \rightarrow 120^\circ\text{F}$
BALANCE UTILIZED: <u>Task Corporation 2.5" MK IX</u>			
	CAPACITY:	ACCURACY:	COEFFICIENT TOLERANCE:
NF	<u>1500 lbs</u>	<u>±.25%</u>	_____
SF	<u>750 lbs</u>	<u>±.25%</u>	_____
AF	<u>200 lbs</u>	<u>±.25%</u>	_____
PM	_____	_____	_____
RM	_____	_____	_____
YM	<u>4000 in-lbs</u>	<u>±.25%</u>	_____
COMMENTS:			

TEST: 0619A NAAL 726

DATE: 6/20/74

DATA SET/RUN NUMBER COLLATION SUMMARY

DATA SET IDENTIFIER	CONFIGURATION	SCHD.		PARAMETERS/VALUES							NO. OF RUNS	MACH NUMBERS	
		α	β	εC	δa	δb	δK	δSK	NO.	MACH			
RF 2001	① + E46	A	0	0	0	0	0	0	0	1	1	26	
004	E46												
005	E47			-40									
006	E45												
009	E46												
010	Y			-30									
011	E41												
012	E46												
013	E46			-20									
016	E45												
017	E47												
018	Y			-15									
017	E45												
018	E46												
021	Y			10									
024	E45												
025	E41												
026	Y			-10									

7 13 19 25 31 37 43 49 55 61 67 73 79

CL CDE CLM CN CAF CYN CBL CY XCP/L CAB MACH ALPHA 1.0

① B61C/M51 Fix w/124Vig K15 X29 α(A) = -10° → 24° ΔX = 2

α ON P SCHEDULES

REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR

TABLE II. - Continued.

TEST: ALPHA NPA. 2.6		DATA SET/RUN NUMBER COLLATION SUMMARY											DATE: 6/25/74	
DATA SET IDENTIFIER	CONFIGURATION	SCHD.		PARAMETERS/VALUES							NO. OF RUNS	MACH NUMBERS		
		A	B	Se	Ca	St	JK	USE						
RFB021	① + EAS	A	0	-10	0	0	0	0	0	25	1	26		
030	E4c			↑								27		
031	↑			-5								30		
032	E41			↑								31		
033	E43			↑								32		
034	E47			5								33		
035	E45			↑								34		
036	E46			↑								35		
037	E47			10								36		
038	E4c			↑								38		
041	E41			0								41		
042	E49			↑								42		
043	↑			-10								43		
044	E30			-10								44		
045	E31			↑								45		
046	↑			-30								46		
047	↑			-20								47		
048	↑			15								48		

TEST RUN NUMBERS

7 13 19 25 31 37 43 49 55 61 67 73 79

CH... CDE... CLA... CN... CAF... CYN... CAL... CY... XSP/L... CAB... MACH... ALPHA... 1.0
 ① Bui C III MSIF12 W24 V19 R15 X29 α(A) = -10° - 24° ΔX = 2

α OR β SCHEDULES

TEST: PA NAME: 726

DATA SET/RUN NUMBER COLLATION SUMMARY

DATE: 6/25/14

DATA SET IDENTIFIER	CONFIGURATION	SCHD.		PARAMETERS/VALUES						NO. OF RUNS	MACH NUMBERS	
		A	B	de	sa	sof	sr	usb				
R0049	0 + E47			15	0	0	0		58		26	
	E48										49	
	E47			20							50	
	E48										51	
	E51										52	
	E49			0		11.7					54	
	E49			15							55	
	E46			20		0					56	
				15							59	
											61	

TEST RUN NUMBERS

13 19 25 31 37 43 49 55 61 67 73 79

C...C...D...E...F...G...H...I...J...K...L...M...N...O...P...Q...R...S...T...U...V...W...X...Y...Z...AA...AB...AC...AD...AE...AF...AG...AH...AI...AJ...AK...AL...AM...AN...AO...AP...AQ...AR...AS...AT...AU...AV...AW...AX...AY...AZ...BA...BB...BC...BD...BE...BF...BG...BH...BI...BJ...BK...BL...BM...BN...BO...BP...BQ...BR...BS...BT...BU...BV...BW...BX...BY...BZ...CA...CB...CC...CD...CE...CF...CG...CH...CI...CJ...CK...CL...CM...CN...CO...CP...CQ...CR...CS...CT...CU...CV...CW...CX...CY...CZ...DA...DB...DC...DD...DE...DF...DG...DH...DI...DJ...DK...DL...DM...DN...DO...DP...DQ...DR...DS...DT...DU...DV...DW...DX...DY...DZ...EA...EB...EC...ED...EE...EF...EG...EH...EI...EJ...EK...EL...EM...EN...EO...EP...EQ...ER...ES...ET...EU...EV...EW...EX...EY...EZ...FA...FB...FC...FD...FE...FF...FG...FH...FI...FJ...FK...FL...FM...FN...FO...FP...FQ...FR...FS...FT...FU...FV...FW...FX...FY...FZ...GA...GB...GC...GD...GE...GF...GG...GH...GI...GJ...GK...GL...GM...GN...GO...GP...GQ...GR...GS...GT...GU...GV...GW...GX...GY...GZ...HA...HB...HC...HD...HE...HF...HG...HH...HI...HJ...HK...HL...HM...HN...HO...HP...HQ...HR...HS...HT...HU...HV...HW...HX...HY...HZ...IA...IB...IC...ID...IE...IF...IG...IH...II...IJ...IK...IL...IM...IN...IO...IP...IQ...IR...IS...IT...IU...IV...IW...IX...IY...IZ...JA...JB...JC...JD...JE...JF...JG...JH...JI...JJ...JK...JL...JM...JN...JO...JP...JQ...JR...JS...JT...JU...JV...JW...JX...JY...JZ...KA...KB...KC...KD...KE...KF...KG...KH...KI...KJ...KK...KL...KM...KN...KO...KP...KQ...KR...KS...KT...KU...KV...KW...KX...KY...KZ...LA...LB...LC...LD...LE...LF...LG...LH...LI...LJ...LK...LL...LM...LN...LO...LP...LQ...LR...LS...LT...LU...LV...LW...LX...LY...LZ...MA...MB...MC...MD...ME...MF...MG...MH...MI...MJ...MK...ML...MN...MO...MP...MQ...MR...MS...MT...MU...MV...MW...MX...MY...MZ...NA...NB...NC...ND...NE...NF...NG...NH...NI...NJ...NK...NL...NM...NO...NP...NQ...NR...NS...NT...NU...NV...NW...NX...NY...NZ...OA...OB...OC...OD...OE...OF...OG...OH...OI...OJ...OK...OL...OM...ON...OO...OP...OQ...OR...OS...OT...OU...OV...OW...OX...OY...OZ...PA...PB...PC...PD...PE...PF...PG...PH...PI...PJ...PK...PL...PM...PN...PO...PP...PQ...PR...PS...PT...PU...PV...PW...PX...PY...PZ...QA...QB...QC...QD...QE...QF...QG...QH...QI...QJ...QK...QL...QM...QN...QO...QP...QQ...QR...QS...QT...QU...QV...QW...QX...QY...QZ...RA...RB...RC...RD...RE...RF...RG...RH...RI...RJ...RK...RL...RM...RN...RO...RP...RQ...RR...RS...RT...RU...RV...RW...RX...RY...RZ...SA...SB...SC...SD...SE...SF...SG...SH...SI...SJ...SK...SL...SM...SN...SO...SP...SQ...SR...SS...ST...SU...SV...SW...SX...SY...SZ...TA...TB...TC...TD...TE...TF...TG...TH...TI...TJ...TK...TL...TM...TN...TO...TP...TQ...TR...TS...TT...TU...TV...TW...TX...TY...TZ...UA...UB...UC...UD...UE...UF...UG...UH...UI...UJ...UK...UL...UM...UN...UO...UP...UQ...UR...US...UT...UU...UV...UW...UX...UY...UZ...VA...VB...VC...VD...VE...VF...VG...VH...VI...VJ...VK...VL...VM...VN...VO...VP...VQ...VR...VS...VT...VU...VV...VW...VX...VY...VZ...WA...WB...WC...WD...WE...WF...WG...WH...WI...WJ...WK...WL...WM...WN...WO...WP...WQ...WR...WS...WT...WU...WV...WW...WX...WY...WZ...XA...XB...XC...XD...XE...XF...XG...XH...XI...XJ...XK...XL...XM...XN...XO...XP...XQ...XR...XS...XT...XU...XV...XW...XX...XY...XZ...YA...YB...YC...YD...YE...YF...YG...YH...YI...YJ...YK...YL...YM...YN...YO...YP...YQ...YR...YS...YT...YU...YV...YW...YX...YY...YZ...ZA...ZB...ZC...ZD...ZE...ZF...ZG...ZH...ZI...ZJ...ZK...ZL...ZM...ZN...ZO...ZP...ZQ...ZR...ZS...ZT...ZU...ZV...ZW...ZX...ZY...ZZ

α OR β SCHEDULES

α(A) = -10 → + 24, EX-28

MACH... MACH... MACH... ALPHA... 710

MODEL DIMENSIONAL DATA

MODEL COMPONENT : BODY - B61

GENERAL DESCRIPTION : 140 A/B inner mold line orbiter fuselage.

Represents structural lines with all thermal protection systems removed.

Model Scale: 0.0405

Model Drawing: SS-A01185

DRAWING NUMBER : VL70-000233

DIMENSIONS : (Inner mold line dimensions) FULL SCALE MODEL SCALE

Length, In.	<u>1290.30</u>	<u>52.257</u>
Max Width ($X_0 = 1528.3$), In.	<u>260.69</u>	<u>10.558</u>
Max Depth ($X_0 = 1464.0$), In.	<u>246.91</u>	<u>10.000</u>
Fineness Ratio	<u>4.95</u>	<u>4.95</u>
Area - Ft ²		
Max. Cross-Sectional	<u>338.67</u>	<u>0.556</u>
Planform		
Wetted		
Base		

TABLE III. - Continued.

MODEL COMPONENT: CANOPY - C₁₁

GENERAL DESCRIPTION: 140A/B inner mold line orbiter canopy used on fuselage B₆₁. Represents structural lines with all thermal protection systems removed.

MODEL SCALE: 0.0405 MODEL DRAWING: SS-A01185

DRAWING NUMBER VL70-000233

<u>DIMENSION: (Inner mold line dimensions)</u>	<u>FULL SCALE</u>	<u>MODEL SCALE</u>
Length ($X_0=434.64$ to 578.00)(Fwd Blkhd)	<u>206.67</u>	<u>8.37</u>
Max Width ($X_0 = 513.13$ (Fwd Blkhd)), In.	<u>210.86</u>	<u>8.54</u>
Max Depth ($X_0 = 485.00$), In.	<u>25.00</u>	<u>1.013</u>
Fineness Ratio	<u> </u>	<u> </u>
Area		
Max Cross-Sectional	<u> </u>	<u> </u>
Planform	<u> </u>	<u> </u>
Wetted	<u> </u>	<u> </u>
Base	<u> </u>	<u> </u>

TABLE III. - Continued.

MODEL COMPONENT: ELEVON - E₁₆

GENERAL DESCRIPTION: 140 A/B inner mold line orbiter elevon. Unswept hingeline, dual panel, 6" elevon/elevon and elevon/wing gaps, and long chord flapper door. Represents structural lines with all thermal protection systems removed.

MODEL SCALE: 0.0405 MODEL DRAWING: SS-A01186

DRAWING NUMBER: VL70-000233

<u>DIMENSIONS:</u> (Data for 1 of 2 sides)	<u>FULL-SCALE</u>	<u>MODEL SCALE</u>
Area - Ft ²	<u>210.00</u>	<u>0.344</u>
Span (equivalent), In.	<u>349.20</u>	<u>14.143</u>
Inb'd equivalent chord, In.	<u>118.00</u>	<u>4.779</u>
Outb'd equivalent chord, In.	<u>55.19</u>	<u>2.235</u>
Ratio movable surface chord/ total surface chord		
At Inb'd equiv. chord	<u>0.210</u>	<u>0.210</u>
At Outb'd equiv. chord	<u>0.400</u>	<u>0.400</u>
Sweep Back Angles, degrees		
Leading Edge	<u>0.00</u>	<u>0.00</u>
Tailing Edge	<u>- 10.056</u>	<u>- 10.056</u>
Hingeline	<u>0.00</u>	<u>0.00</u>
Area Moment (Normal to hinge line), Ft ³	<u>1587.25</u>	<u>0.1054</u>

TABLE III. - Continued.

MODEL COMPONENT: ELEVON E47

GENERAL DESCRIPTION: 140A/B inner mold line orbiter elevon. Unswept hingeline, dual panel, 6" elevon/elevon and elevon/wing gaps, and short chord flapper door used to seal wing/elevon gap. Represents structural lines with all thermal protection systems removed.

MODEL SCALE: 0.0405 MODEL DRAWING: SS-A01185

DRAWING NUMBER: VL70-000233

<u>DIMENSIONS: (Data for 1 of 2 sides)</u>	<u>FULL-SCALE</u>	<u>MODEL SCALE</u>
Area - Ft ²	<u>210.00</u>	<u>0.344</u>
Span (equivalent), In.	<u>349.20</u>	<u>14.143</u>
Inb'd equivalent chord, In.	<u>118.00</u>	<u>4.779</u>
Outb'd equivalent chord, In.	<u>55.19</u>	<u>2.235</u>
Ratio movable surface chord/ total surface chord		
At Inb'd equiv. chord	<u>0.210</u>	<u>0.210</u>
At Outb'd equiv. chord	<u>0.400</u>	<u>0.400</u>
Sweep Back Angles, degrees		
Leading Edge	<u>0.00</u>	<u>0.00</u>
Tailing Edge	<u>- 10.056</u>	<u>- 10.056</u>
Hingeline	<u>0.00</u>	<u>0.00</u>
Area Moment (Normal to hinge line), Ft ³	<u>1587.25</u>	<u>0.1054</u>

REPRODUCIBILITY OF THE
ORIGINAL PAGE IS POOR

TABLE III. - Continued.

MODEL COMPONENT: ELEVON - E18

GENERAL DESCRIPTION: 140A/B inner mold line orbiter elevon. Unswept hingeline, dual panel, 6" elevon/elevon and elevon/ving gaps with no flapper door. Upper elevon hingeline is sealed flush to ving surface. Represents structural lines with all thermal protection systems removed.

MODEL SCALE: 0.0405 MODEL DRAWING: SS-A01185

DRAWING NUMBER: VL7G-000233

<u>DIMENSIONS:</u>	<u>FULL-SCALE</u>	<u>MODEL SCALE</u>
Area - Ft ²	<u>210.00</u>	<u>0.344</u>
Span (equivalent) , In.	<u>349.20</u>	<u>14.143</u>
Inb'd equivalent chord , In.	<u>118.00</u>	<u>4.779</u>
Outb'd equivalent chord , In.	<u>55.19</u>	<u>2.235</u>
Ratio movable surface chord/ total surface chord		
At Inb'd equiv. chord	<u>0.210</u>	<u>0.210</u>
At Outb'd equiv. chord	<u>0.400</u>	<u>0.400</u>
Sweep Back Angles, degrees		
Leading Edge	<u>0.00</u>	<u>0.00</u>
Tailing Edge	<u>- 10.056</u>	<u>- 10.056</u>
Hingeline	<u>0.00</u>	<u>0.00</u>
Area Moment (Normal to hinge line) Ft ³	<u>1587.25</u>	<u>0.1054</u>

TABLE III. - Continued.

MODEL COMPONENT: ELEVON E₄₉

GENERAL DESCRIPTION: 140A/B inner mold line orbiter elevon. Unswept hingeline, dual panel, and 6" elevon/elevon and elevon/wing gaps. Upper elevon hingeline is unsealed and no flapper door is used. Represents structural lines with all thermal protection systems removed.

MODEL SCALE: 0.0405

MODEL DRAWING: SS-A01185

DRAWING NUMBER: VL70-000233

<u>DIMENSIONS:</u> (Data for 1 of 2 sides)	<u>FULL-SCALE</u>	<u>MODEL SCALE</u>
Area - Ft ²	<u>210.00</u>	<u>0.344</u>
Span (equivalent), In.	<u>349.20</u>	<u>14.143</u>
Inb'd equivalent chord, In.	<u>118.00</u>	<u>4.779</u>
Outb'd equivalent chord, In.	<u>55.19</u>	<u>2.235</u>
Ratio movable surface chord/ total surface chord		
At Inb'd equiv. chord	<u>0.210</u>	<u>0.210</u>
At Outb'd equiv. chord	<u>0.400</u>	<u>0.400</u>
Sweep Back Angles, degrees		
Leading Edge	<u>0.00</u>	<u>0.00</u>
Tailing Edge	<u>-10.056</u>	<u>-10.056</u>
Hingeline	<u>0.00</u>	<u>0.00</u>
Area Moment (Normal to hinge line), Ft ³	<u>1587.25</u>	<u>0.1054</u>

TABLE III. - Continued.

MODEL COMPONENT: ELEVON - E50

GENERAL DESCRIPTION: 140A/B inner mold line orbiter elevon. Unswept hingeline, dual panel, 6" elevon/elevon and elevon/wing gaps and long chord flapper door, and lower elevon hingeline has been smoothed to prevent any discontinuity in the lower wing contour at large negative elevon deflections. Represents structural lines with all thermal protection systems removed.

MODEL SCALE: 0.0405 MODEL DRAWING: SS-A01185

DRAWING NUMBER: VL70-000233

<u>DIMENSIONS:</u>	<u>FULL-SCALE</u>	<u>MODEL SCALE</u>
Area - Ft ²	<u>210.00</u>	<u>0.344</u>
Span (equivalent), In.	<u>349.20</u>	<u>14.143</u>
Inb'd equivalent chord, In.	<u>118.00</u>	<u>4.779</u>
Outb'd equivalent chord, In.	<u>55.19</u>	<u>2.235</u>
Ratio movable surface chord/ total surface chord		
At Inb'd equiv. chord	<u>0.210</u>	<u>0.210</u>
At Outb'd equiv. chord	<u>0.400</u>	<u>0.400</u>
Sweep Back Angles, degrees		
Leading Edge	<u>0.00</u>	<u>0.00</u>
Tailing Edge	<u>- 10.056</u>	<u>-10.056</u>
Hingeline	<u>0.00</u>	<u>0.00</u>
Area Moment (Normal to hinge line), Ft ³	<u>1587.25</u>	<u>0.1054</u>

TABLE III. - Continued.

MODEL COMPONENT: ELEVON - E₅₁

GENERAL DESCRIPTION: 140A/B inner mold line orbiter elevon. Unswept hingeline, dual panel, 6" elevon/elevon and elevon/wing gaps and no flapper door used. Upper elevon hingeline is unsealed; and lower elevon hingeline has been smoothed to prevent any discontinuity in the lower wing contour at large negative elevon deflections. Represents structural lines with all thermal protection systems removed.

MODEL SCALE: 0.0405 MODEL DRAWING: SS A01185

DRAWING NUMBER: VL70-000233

<u>DIMENSIONS:</u>	<u>FULL-SCALE</u>	<u>MODEL SCALE</u>
Area - Ft ²	<u>210.00</u>	<u>0.344</u>
Span (equivalent), In.	<u>349.20</u>	<u>14.143</u>
Inb'd equivalent chord, In.	<u>118.00</u>	<u>4.779</u>
Outb'd equivalent chord, In.	<u>55.19</u>	<u>2.235</u>
Ratio movable surface chord/ total surface chord		
At Inb'd equiv. chord	<u>0.210</u>	<u>0.210</u>
At Outb'd equiv. chord	<u>0.400</u>	<u>0.400</u>
Sweep Back Angles, degrees		
Leading Edge	<u>0.00</u>	<u>0.00</u>
Tailing Edge	<u>-10.056</u>	<u>-10.056</u>
Hingeline	<u>0.00</u>	<u>0.00</u>
Area Moment (Normal to hinge line), Ft ³	<u>1587.25</u>	<u>0.1054</u>

TABLE III. - Continued.

MODEL COMPONENT: BODY FLAP F₁₂

GENERAL DESCRIPTION: 140A/B inner mold line orbiter body flap used on fuselage B₆₁. Represents structural lines with all thermal protection systems removed.

MODEL SCALE: 0.0405

MODEL DRAWING: SS-A01185

DRAWING NUMBER

VL70-000233

<u>DIMENSION:</u> (Inner mold line dimensions)	<u>FULL SCALE</u>	<u>MODEL SCALE</u>
Length , In.	<u>81.00</u>	<u>3.280</u>
Max Width , In.	<u>260.00</u>	<u>10.530</u>
Max Depth , In.	<u>21.20</u>	<u>0.859</u>
Fineness Ratio	<u> </u>	<u> </u>
Area - Ft ²	<u> </u>	<u> </u>
Max Cross-Sectional	<u> </u>	<u> </u>
Planform	<u>135.00</u>	<u>0.2214</u>
Wetted	<u> </u>	<u> </u>
Base	<u>41.90</u>	<u>0.069</u>

TABLE III. - Continued.

MODEL COMPONENT: ORBITAL MANEUVERING SYSTEM - M₅₁

GENERAL DESCRIPTION: 140A/B inner mold line OMS pods used on fuselage B₆₁.
Represents structural lines with all thermal protection systems removed.

MODEL SCALE: 0.0405 MODEL DRAWING NO.: SS-A01185

DRAWING NUMBER VL70-000233

<u>DIMENSION:</u> (Inner mold line dimensions)	<u>FULL SCALE</u>	<u>MODEL SCALE</u>
Length (Fwd Sta @ $X_0 = 1207.00$), In.	<u>304.00</u>	<u>12.312</u>
Max Width ($X_0 = 1450.00$), In.	<u>94.50</u>	<u>3.827</u>
Max Depth	<u>109.00</u>	<u>4.415</u>
Fineness Ratio	<u> </u>	<u> </u>
Area		
Max Cross-Sectional	<u> </u>	<u> </u>
Planform	<u> </u>	<u> </u>
Wetted	<u> </u>	<u> </u>
Base	<u>19.48</u>	<u>0.032</u>

TABLE III. - Continued.

MODEL COMPONENT: RUDDER - R₁₅

GENERAL DESCRIPTION: 140A/B inner mold line rudder used on vertical tail
V₁₉: Represents structural lines with all thermal protection systems removed.

MODEL SCALE: 0.0405 MODEL DRAWING: SS-A01185

DRAWING NUMBER: VI77-000233

<u>DIMENSIONS:</u>	<u>FULL-SCALE</u>	<u>MODEL SCALE</u>
Area - Ft ²	<u>100.15</u>	<u>4.056</u>
Span (equivalent), In.	<u>201.00</u>	<u>8.141</u>
Inb'd equivalent chord, In.	<u>91.59</u>	<u>3.709</u>
Outb'd equivalent chord, In.	<u>50.83</u>	<u>2.059</u>
Ratio movable surface chord/ total surface chord		
At Inb'd equiv. chord	<u>0.400</u>	<u>0.400</u>
At Outb'd equiv. chord	<u>0.400</u>	<u>0.400</u>
Sweep Back Angles, degrees		
Leading Edge	<u>34.830</u>	<u>34.830</u>
Tailing Edge	<u>26.250</u>	<u>26.250</u>
Hingeline	<u>34.830</u>	<u>34.830</u>
Area Moment (Normal to hinge line), Ft ³	<u>610.92</u>	<u>0.0406</u>

TABLE III. - Continued.

MODEL COMPONENT: VERTICAL - V₁₉

GENERAL DESCRIPTION: 140A/R inner mold line centerline vertical tail

Represents structural lines with all thermal protection systems removed

MODEL SCALE: 0.0405 MODEL DRAWING: SS-A01187

MODEL SCALE: 0.0405

DRAWING NUMBER: VL70-000233

DIMENSIONS:	<u>FULL SCALE</u>	<u>MODEL SCALE</u>
TOTAL DATA		
Area (Theo) - Ft ²		
Planform	<u>413.25</u>	<u>0.678</u>
Span (Theo) - In.	<u>315.72</u>	<u>12.787</u>
Aspect Ratio	<u>1.675</u>	<u>1.675</u>
Rate of Taper	<u>0.507</u>	<u>0.507</u>
Taper Ratio	<u>0.404</u>	<u>0.404</u>
Sweep-Back Angles, Degrees.		
Leading Edge	<u>45.000</u>	<u>45.000</u>
Trailing Edge	<u>26.200</u>	<u>26.200</u>
0.25 Element Line	<u>41.130</u>	<u>41.130</u>
Chords:		
Root (Theo) WP	<u>268.50</u>	<u>10.874</u>
Tip (Theo) WP	<u>108.47</u>	<u>4.393</u>
MAC	<u>199.81</u>	<u>8.092</u>
Fus. Sta. of .25 MAC	<u>1463.50</u>	<u>59.272</u>
W.P. of .25 MAC	<u>635.52</u>	<u>25.738</u>
B.L. of .25 MAC	<u>0.00</u>	<u>0.00</u>
Airfoil Section		
Leading Wedge Angle - Deg.	<u>10.00</u>	<u>10.000</u>
Trailing Wedge Angle - Deg.	<u>14.920</u>	<u>14.920</u>
Leading Edge Radius	<u>2.000</u>	<u>2.000</u>
Void Area	<u>13.17</u>	<u>0.022</u>
Blanketed Area	<u>0.00</u>	<u>0.00</u>

REPRODUCIBILITY OF THE
ORIGINAL PAGE IS POOR

TABLE III. - Continued.

MODEL COMPONENT: WING-W₁₂₄
 GENERAL DESCRIPTION: 140A/B inner mold line orbiter double delta wing. Represents structural lines with all thermal protection systems removed

MODEL SCALE: 0.0405 MODEL DRAWING NO.: SS-A01186

TEST NO. _____ DWG. NO. VI70-000233

DIMENSIONS: FULL-SCALE MODEL SCALE

TOTAL DATA

Area (Theo.) Ft ²		
Planform	2690.00	4.412
Span (Theo) In.	936.68	37.936
Aspect Ratio	2.265	2.265
Rate of Taper	1.177	1.177
Taper Ratio	0.200	0.200
Dihedral Angle, degrees	3.500	3.500
Incidence Angle, degrees	0.500	0.500
Aerodynamic Twist, degrees	3.000	3.000
Sweep Back Angles, degrees		
Leading Edge	45.000	45.000
Trailing Edge	-10.056	-10.056
0.25 Element Line	35.209	35.209
Chords:		
Root (Theo) B.P.O.O.	689.24	27.914
Tip, (Theo) B.P.	137.85	5.583
MAC	474.81	19.230
Fus. Sta. of .25 MAC	1136.83	46.042
W.P. of .25 MAC	290.58	11.768
B.L. of .25 MAC	182.13	7.376

EXPOSED DATA

Area (Theo) Ft ²	1751.50	2.873
Span, (Theo) In. BP108	720.68	29.188
Aspect Ratio	2.059	2.059
Taper Ratio	0.245	0.245
Chords		
Root BP108	562.09	22.765
Tip 1.00 $\frac{b}{2}$	137.85	5.583
MAC	392.83	15.910
Fus. Sta. of .25 MAC	1185.98	48.032
W.P. of .25 MAC	294.30	11.919
B.L. of .25 MAC	211.77	10.197

Airfoil Section (Rockwell Mod NASA) XXXX-64

Root $\frac{b}{2}$ =	Mod NASA	XXXX-64
Tip $\frac{b}{2}$ =		

Data for (1) of (2) Sides

Leading Edge Cuff		
Planform Area Ft ²	113.18	0.186
Leading Edge Intersects Fus M. L. @ Sta	500.00	20.250
Leading Edge Intersects Wing @ Sta	1024.00	41.472

IMPROVEMENT OF THE ORIGINAL PAGE IS POOR

TABLE III. - Concluded.

MODEL COMPONENT: TRANSITION GRIT - X₂₉

GENERAL DESCRIPTION: Grit composed of glass beads located aft of model nose wing and vertical tail to provide forced boundary layer transition.


Dimensions are in the streamwise direction aft of the local leading edge.

MODEL SCALE: 0.0405

DRAWING NO.: None

DIMENSIONS:


Grit diameter - In.	
Fuselage	0.0054
Swept surfaces	0.0076
Strip width - In.	0.10
Location aft of leading edge - In.	1.00




Notes

1. Positive directions of force coefficients, moment coefficients, and angles are indicated by arrows
2. For clarity, origins of wind and stability axes have been displaced from the center of gravity

a. General
Figure 1. - Axis systems.




Rudder and Speed Brake Deflections



$$\delta_a = \frac{\delta e_L - \delta e_R}{2}$$

$$\delta_e = \frac{\delta e_L + \delta e_R}{2}$$

Aileron & Elevon Deflections



Body Flap Deflections



b. Sign Convention for Control Surfaces

Figure 1. - Concluded.

REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR

REPRODUCIBILITY OF THE
PAGE IS POOR.


Reference	Dimension
Area	Sw = 2690 ft ²
MAC	Cw = 474.8 in
C.G.	X = 1076.48 in
	Z = 375.0 in
Span	bw = 936.68 in
Length	L = 1290.3 in



a. General Arrangement - 140 Orbiter

Figure 2. - Model sketches.


NOT TO SCALE



b. Long Flapper Door Configuration E46

Figure 2. - Continued.

NOT TO SCALE



c. Short Flapper Door Configuration E47

Figure 2. - Concluded.




a. Rear View, NAAL Installation Configuration B₆₁ C₁₁ M₅₁ F₁₂ W₁₂₄ E₄₆
V₁₉ R₁₅ X₂₉



b. Side View, Left Wing, Short Flapper Door Conf. / ion E₄₇

REPRODUCIBILITY OF THE
ORIGINAL PAGE IS POOR

Figure 3. - Model photographs.




c. Side View, Left Wing, Elevon/Wing Gap Open Configuration E₄₉




d. Side View, Left Wing, Long Flapper Door Configuration E₄₆

Figure 3. - Continued.



e. Rear View, Right Wing, Flow Visualization of Elevon/Wing Gap Open Configuration E51



f. Rear View, Right Wing, Flow Visualization of Completely Sealed Configuration E48

Figure 3. - Concluded.

DATA FIGURES

L SET SYMBOL CONFIGURATION DESCRIPTION
 (AF8059) CA119A B61C11F 2MS1V124E46V19R15X29
 (AF8051) CA119A B61C11F 2MS1V124E46V19R15X29
 (AF8038) CA119A B61C11F 2MS1V124E46V19R15X29
 (AF8036) CA119A B61C11F 2MS1V124E46V19R15X29
 (AF8001) CA119A B61C11F 2MS1V124E46V19R15X29
 (AF8003) CA119A B61C11F 2MS1V124E46V19R15X29

ELEVON	BDFLAP	SPOBRK	ATLIRON	REFERENCE INFORMATION
20.000	.000	25.000	.000	SREF 2690.0100 50.FT.
15.000	.000	25.000	.000	LREF 474.6100 INCHES
10.000	.000	25.000	.000	BREF 936.6800 INCHES
5.000	.000	25.000	.000	XMRP 1076.4800 INCHES
-5.000	.000	25.000	.000	YMRP .0000 INCHES
	.000	25.000	.000	ZMRP 375.0000 INCHES
				SCALE .0405 SCALE




FIG 4 ELEVON EFFECTIVENESS - ELEVON E46 (POSITIVE ELEVON DEFLECTIONS)



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPOBRK	AILRON	REFERENCE INFORMATION
(AF8036)	0A119A B61C1IF12P5IV124E46V1SR15X29	20.000	.000	25.000	.000	SREF 2650.0100 SQ.FT.
(AF8051)	0A119A B61C1IF12P5IV124E46V1SR15X29	15.000	.000	25.000	.000	LREF 474.8100 INCHES
(AF8038)	0A119A B61C1IF12P5IV124E46V1SR15X29	10.000	.000	25.000	.000	BREF 936.6900 INCHES
(AF8036)	0A119A B61C1IF12P5IV124E46V1SR15X29	5.000	.000	25.000	.000	XTRP 1076.4800 INCHES
(AF8001)	0A119A B61C1IF12P5IV124E46V1SR15X29	.000	.000	25.000	.000	YTRP 375.0000 INCHES
(AF8031)	0A119A B61C1IF12P5IV124E46V1SR15X29	-5.000	.000	25.000	.000	ZTRP .0405 SCALE





FIG 4 ELEVON EFFECTIVENESS - ELEVON E46 (POSITIVE ELEVON DEFLECTIONS)



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BDFLAP	SPOBRK	AIIIRON	REFERENCE INFORMATION
(AF8038)	DA119A B61C1F1245V124E16V19R15X29	20.000	.000	25.000	.000	SREF 2690.0100 SQ.FT.
(AF8031)	DA119A B61C1F1245V124E16V19R15X29	15.000	.000	25.000	.000	LREF 474.8100 INCHES
(AF8036)	DA119A B61C1F1245V124E16V19R15X29	10.000	.000	25.000	.000	BREF 936.6800 INCHES
(AF8001)	DA119A B61C1F1245V124E16V19R15X29	5.000	.000	25.000	.000	XMRP 1076.4800 INCHES
(AF8031)	DA119A B61C1F1245V124E16V19R15X29	-5.000	.000	25.000	.000	ZMRP 375.0000 INCHES
						SCALE .0405




FOREBODY AXIAL FORCE COEFFICIENT, CAF

FIG 4 ELEVON EFFECTIVENESS - ELEVON E46 (POSITIVE ELEVON DEFLECTIONS)



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BDFLAP	SPOBRK	AILERON	REFERENCE INFORMATION
(AF8009)	0A119A BB1C11F12761V124E46V1SR15X29	20.000	.000	25.000	.000	SREF 2690.0100 SQ.FT.
(AF8061)	0A119A BB1C11F12761V124E46V1SR15X29	15.000	.000	23.000	.000	LREF 474.8100 INCHES
(AF8038)	0A119A BB1C11F12761V124E46V1SR15X29	10.000	.000	23.000	.000	BREF 936.6600 INCHES
(AF8006)	0A119A BB1C11F12761V124E46V1SR15X29	5.000	.000	25.000	.000	XMRP 1076.4800 INCHES
(AF8001)	0A119A BB1C11F12761V124E46V1SR15X29	.000	.000	25.000	.000	ZMRP .0000 INCHES
(AF8031)	0A119A BB1C11F12761V124E46V1SR15X29	-5.000	.000	25.000	.000	SCALE 375.0000 INCHES .0405 SCALE



BASE AXIAL FORCE COEFFICIENT, CAB

FIG 4 ELEVON EFFECTIVENESS - ELEVON E46 (POSITIVE ELEVON DEFLECTIONS)

(M)MACH = .26

PAGE 4



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPDRBK	AITLRN	REFERENCE INFORMATION
(AF8059)	GA119A B61C1F12P51V124E46V1SR15X29	20.000	.000	25.000	.000	SREF 2630.0100 SQ.FT.
(AF8061)	GA119A B61C1F12P51V124E46V1SR15X29	15.000	.000	25.000	.000	LREF 474.8100 INCHES
(AF8038)	GA119A B61C1F12P51V124E46V1SR15X29	10.000	.000	25.000	.000	BREF 136.6800 INCHES
(AF8036)	GA119A B61C1F12P51V124E46V1SR15X29	5.000	.000	25.000	.000	XMRP 1076.3800 INCHES
(AF8001)	GA119A B61C1F12P51V124E46V1SR15X29	-5.000	.000	25.000	.000	YMRP 375.0000 INCHES
(AF8031)	GA119A B61C1F12P51V124E46V1SR15X29		.000	25.000	.000	ZMRP 375.0000 INCHES
						SCALE .9405




FIG 4 ELEVON EFFECTIVENESS - ELEVON E46 (POSITIVE ELEVON DEFLECTIONS)



DATA SET SYMBOL CONFIGURATION DESCRIPTION REFERENCE INFORMATION

DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BDFLAP	SPOBRK	A1LRON	SREF	LREF	BREF	XMRP	YMRP	ZMRP	SCALE	90.F.I.
(AF8059)	0A119A 861C1F12761V124E46V19R15X29	20.000	.000	29.000	.000	2690.0100	474.8100	936.6800	1076.4800	375.0000	375.0000	.0405	INCHES
(AF8061)	0A119A 861C1F12761V124E46V19R15X29	15.000	.000	29.000	.000	474.8100	936.6800	1076.4800	375.0000	375.0000	375.0000	.0405	INCHES
(AF8038)	0A119A 861C1F12761V124E46V19R15X29	10.000	.000	29.000	.000	1076.4800	375.0000	375.0000	375.0000	375.0000	375.0000	.0405	INCHES
(AF8036)	0A119A 861C1F12761V124E46V19R15X29	5.000	.000	29.000	.000	375.0000	375.0000	375.0000	375.0000	375.0000	375.0000	.0405	INCHES
(AF8001)	0A119A 861C1F12761V124E46V19R15X29	-5.000	.000	29.000	.000	375.0000	375.0000	375.0000	375.0000	375.0000	375.0000	.0405	INCHES





FIG 4 ELEVON EFFECTIVENESS - ELEVON E46 (POSITIVE ELEVON DEFLECTIONS)



REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR

DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BDFLAP	SPOBRK	AILRON	REFERENCE INFORMATION
(AF8059)	DA119A B61C1F12751V124E46V19R15X29	20.000	.000	25.000	.000	SREF 2690.0100 SQ.FT.
(AF8061)	DA119A B61C1F12751V124E46V19R15X29	15.000	.000	25.000	.000	LREF 474.8100 INCHES
(AF8038)	DA119A B61C1F12751V124E46V19R15X29	10.000	.000	25.000	.000	BREF 936.6800 INCHES
(AF8036)	DA119A B61C1F12751V124E46V19R15X29	5.000	.000	25.000	.000	XMRP 1076.4800 INCHES
(AF8001)	DA119A B61C1F12751V124E46V19R15X29	-5.000	.000	25.000	.000	YMRP 375.0000 INCHES
(AF8031)	DA119A B61C1F12751V124E46V19R15X29					SCALE .0405 SCALE



FOREBODY LIFT COEFFICIENT, CLF

FIG 4 ELEVON EFFECTIVENESS - ELEVON E46 (POSITIVE ELEVON DEFLECTIONS)



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BD FLAP	SPOONK	ALIGN	REFERENCE INFORMATION
{AF000}	BA119A BS1C1F12P51V124E46V1SR15X29	20.000	.000	29.000	.000	SREF 2680.0100 SQ.FT.
{AF001}	BA119A BS1C1F12P51V124E46V1SR15X29	15.000	.000	29.000	.000	LREF 474.8100 INCHES
{AF002}	BA119A BS1C1F12P51V124E46V1SR15X29	10.000	.000	29.000	.000	BREF 936.6800 INCHES
{AF003}	BA119A BS1C1F12P51V124E46V1SR15X29	5.000	.000	29.000	.000	XMRP 1076.4800 INCHES
{AF004}	BA119A BS1C1F12P51V124E46V1SR15X29	-5.000	.000	29.000	.000	ZMRP 375.0000 INCHES
{AF005}	BA119A BS1C1F12P51V124E46V1SR15X29					SCALE .0405




FIG 4 ELEVON EFFECTIVENESS - ELEVON E46 (POSITIVE ELEVON DEFLECTIONS)

(A)MACH = .26



SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPOBRK	AILRON	REFERENCE INFORMATION
(AF8059)	0A119A 861C1F12V51V124E46V19R15X29	20.000	.000	25.000	.000	2690.0100 50.FT.
(AF8061)	0A119A 861C1F12V51V124E46V19R15X29	15.000	.000	25.000	.000	474.9100 INCHES
(AF8038)	0A119A 861C1F12V51V124E46V19R15X29	10.000	.000	25.000	.000	936.6300 INCHES
(AF8036)	0A119A 861C1F12V51V124E46V19R15X29	5.000	.000	25.000	.000	1076.4800 INCHES
(AF8001)	0A119A 861C1F12V51V124E46V19R15X29	-5.000	.000	25.000	.000	375.0000 INCHES
(AF8031)	0A119A 861C1F12V51V124E46V19R15X29					.0405 SCALE




FIG 4 ELEVON EFFECTIVENESS - ELEVON E46 (POSITIVE ELEVON DEFLECTIONS)




DATA SET SYMBOL CONFIGURATION DESCRIPTION

[AF8059]	0A11SA	BS1C1F1	24E46V1	SRI5X29
[AF8051]	0A11SA	BS1C1F1	24E46V1	SRI5X29
[AF8038]	0A11SA	BS1C1F1	24E46V1	SRI5X29
[AF8036]	0A11SA	BS1C1F1	24E46V1	SRI5X29
[AF8001]	0A11SA	BS1C1F1	24E46V1	SRI5X29
[AF8001]	0A11SA	BS1C1F1	24E46V1	SRI5X29

ELEVON

20.000	BDFLAP	SPDBRK	A1LRON	REFERENCE INFORMATION
15.000	.000	25.000	.000	SREF 2630.0100 50.FT.
5.000	.000	25.000	.000	LREF 474.8100 INCHES
5.000	.000	25.000	.000	EREF 936.6800 INCHES
5.000	.000	25.000	.000	XPROP 1076.4800 INCHES
5.000	.000	25.000	.000	YPROP 375.0000 INCHES
-5.000	.000	25.000	.000	ZPROP 375.0000 INCHES
				SCALE .0405



LONGITUDINAL CENTER OF PRESSURE LOCATION, XCP/L

FIG 4 ELEVON EFFECTIVENESS - ELEVON E46 (POSITIVE ELEVON DEFLECTIONS)

(A)MACH = .26



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPOBRK	AILRON	REFERENCE INFORMATION	SO.FT.
(AF8001)	0A119A 061C1F1 275 V124E16V19R15X29	.000	.000	25.000	.000	SREF 269	1100
(AF8030)	0A119A 061C1F1 275 V124E16V19R15X29	-10.000	.000	25.000	.000	LREF 474	1100
(AF8020)	0A119A 061C1F1 275 V124E16V19R15X29	-15.000	.000	25.000	.000	BREF 936	1800
(AF8013)	0A119A 061C1F1 275 V124E16V19R15X29	-20.000	.000	25.000	.000	XMRP 1076	1800
(AF8010)	0A119A 061C1F1 275 V124E16V19R15X29	-30.000	.000	25.000	.000	YMRP 375	1800
(AF8009)	0A119A 061C1F1 275 V124E16V19R15X29	-40.000	.000	25.000	.000	SCALE .0405	SCALE




FIG 5 ELEVON EFFECTIVENESS - ELEVON E46 (NEGATIVE ELEVON DEFLECTIONS)

(A)MACH = .26 PAGE 11



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	EDFLAP	SPDRBK	AIRLON	REFERENCE INFORMATION
(AF8001)	DA119A B61C1F12751V124E16V19R15X29	.000	.000	25.000	.000	SREF 2650.0100 SO.FT
(AF8030)	DA119A B61C1F12751V124E16V19R15X29	-10.000	.000	25.000	.000	LREF 474.8100 INCHES
(AF8020)	DA119A B61C1F12751V124E16V19R15X29	-15.000	.000	25.000	.000	BREF 936.6800 INCHES
(AF8013)	DA119A B61C1F12751V124E16V19R15X29	-20.000	.000	25.000	.000	XMRP 1076.4800 INCHES
(AF8010)	DA119A B61C1F12751V124E16V19R15X29	-30.000	.000	25.000	.000	ZMRP .0000 INCHES
(AF8009)	DA119A B61C1F12751V124E16V19R15X29	-40.000	.000	25.000	.000	SCALE 375.0000 INCHES SCALE .0405




FIG 5 ELEVON EFFECTIVENESS - ELEVON E46 (NEGATIVE ELEVON DEFLECTIONS)



REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR

DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPOBRK	AILERON	REFERENCE INFORMATION
(AF8001)	0A119A 861C1F12761V124E16V19R15X29	.000	.000	25.000	.000	SREF 2690 3100 SO.FT
(AF8020)	0A119A 861C1F12761V124E16V19R15X29	-10.000	.000	25.000	.000	LREF 474 8100 INCHES
(AF8021)	0A119A 861C1F12761V124E16V19R15X29	-15.000	.000	25.000	.000	BREF 936 8800 INCHES
(AF8022)	0A119A 861C1F12761V124E16V19R15X29	-20.000	.000	25.000	.000	XPRP 1076 8800 INCHES
(AF8023)	0A119A 861C1F12761V124E16V19R15X29	-25.000	.000	25.000	.000	YPRP 3000 8800 INCHES
(AF8010)	0A119A 861C1F12761V124E16V19R15X29	-30.000	.000	25.000	.000	ZPRP 375 3000 INCHES
(AF8009)	0A119A 861C1F12761V124E16V19R15X29	-40.000	.000	25.000	.000	SCALE 3405 SCALE




FIG 5 ELEVON EFFECTIVENESS - ELEVON E46 (NEGATIVE ELEVON DEFLECTIONS)

(A)MACH = .26



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPOBRK	AIRLON	REFERENCE INFORMATION
{AF8001}	0A119A B61C1F1275IV124E46V1SR15X29	.000	.000	25.000	.000	SREF 2690.0100 50.FT. INCHES
{AF8030}	0A119A B61C1F1275IV124E46V1SR15X29	-10.000	.000	25.000	.000	LREF 474.8100 INCHES
{AF8020}	0A119A B61C1F1275IV124E46V1SR15X29	-15.000	.000	25.000	.000	BREF 936.6800 INCHES
{AF8013}	0A119A B61C1F1275IV124E46V1SR15X29	-20.000	.000	25.000	.000	XMRP 1076.4800 INCHES
{AF8010}	0A119A B61C1F1275IV124E46V1SR15X29	-30.000	.000	25.000	.000	ZMRP 375.0000 INCHES
{AF8009}	0A119A B61C1F1275IV124E46V1SR15X29	-40.000	.000	25.000	.000	SCALE .0405 SCALE

BASE AXIAL FORCE COEFFICIENT, CAB





FIG 5 ELEVON EFFECTIVENESS - ELEVON E46 (NEGATIVE ELEVON DEFLECTIONS)



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPDBRK	AILRON	REFERENCE INFORMATION
(AF8001)	DA119A B61C1F12MS1V124E46V1SR15X29	.000	.000	25.000	.000	SREF 2690.0100 SQ.FT.
(AF8030)	DA119A B61C1F12MS1V124E46V1SR15X29	-10.000	.000	25.000	.000	LREF 474.8100 INCHES
(AF8070)	DA119A B61C1F12MS1V124E46V1SR15X29	-15.000	.000	25.000	.000	BREF 936.6800 INCHES
(AF8013)	DA119A B61C1F12MS1V124E46V1SR15X29	-20.000	.000	25.000	.000	XMRP 1076.4800 INCHES
(AF8010)	DA119A B61C1F12MS1V124E46V1SR15X29	-30.000	.000	25.000	.000	YMRP .0000 INCHES
(AF8009)	DA119A B61C1F12MS1V124E46V1SR15X29	-40.000	.000	25.000	.000	ZMRP 375.0000 INCHES
						SCALE .0405



FOREBODY DRAG COEFFICIENT, CDF

FIG 5 ELEVON EFFECTIVENESS - ELEVON E46 (NEGATIVE ELEVON DEFLECTIONS)

(A)MACH = .26




DATA SET SYMBOL CONFIGURATION DESCRIPTION

0A	661C11F12761V124E46V19R15X29

ELEVON BOFLAP STORBK ALLRON REFERENCE INFORMATION

.000	.000	.000	SREF	2690.0100	50 FT
-10.000	.000	.000	LREF	474.8100	INCHES
-15.000	.000	.000	BREF	936.6800	INCHES
-20.000	.000	.000	XMRP	1076.4900	INCHES
-30.000	.000	.000	YMRP	.0000	INCHES
-40.000	.000	.000	ZMRP	375.0000	INCHES
			SCALE	.0405	SCALE



PITCHING MOMENT COEFFICIENT, CLM

FIG 5 ELEVON EFFECTIVENESS - ELEVON E46 (NEGATIVE ELEVON DEFLECTIONS)



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPOBRK	AIRRON	REFERENCE INFORMATION
{ AF8001 }	0A119A B61C1F12V5IV124E46V19R15X29	.000	.000	25.000	.000	SREF 269.0100 SQ.FT.
{ AF8030 }	0A119A B61C1F12V5IV124E46V19R15X29	-10.000	.000	25.000	.000	LREF 474.3100 INCHES
{ AF8070 }	0A119A B61C1F12V5IV124E46V19R15X29	-5.000	.000	25.000	.000	BREF 936.6800 INCHES
{ AF8013 }	0A119A B61C1F12V5IV124E46V19R15X29	-20.000	.000	25.000	.000	XMRP 1076.1800 INCHES
{ AF8010 }	0A119A B61C1F12V5IV124E46V19R15X29	-30.000	.000	25.000	.000	ZMRP .0000 INCHES
{ AF8009 }	0A119A B61C1F12V5IV124E46V19R15X29	-40.000	.000	25.000	.000	SCALE .0405 SCALE




FIG 5 ELEVON EFFECTIVENESS - ELEVON E46 (NEGATIVE ELEVON DEFLECTIONS)

(A)MACH = .26

DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BDFLAP	SPOBRK	AILRON	REFERENCE INFORMATION
(AF8001)	CA119A B61C1F12761V124E46V19R15X29	.000	.000	29.000	.000	SREF 269.0100 SO.FT.
(AF8002)	CA119A B61C1F12761V124E46V19R15X29	-10.000	.000	29.000	.000	LREF 474.8100 INCHES
(AF8003)	CA119A B61C1F12761V124E46V19R15X29	-15.000	.000	29.000	.000	BREF 936.6800 INCHES
(AF8004)	CA119A B61C1F12761V124E46V19R15X29	-20.000	.000	29.000	.000	XMRP 1076.4800 INCHES
(AF8005)	CA119A B61C1F12761V124E46V19R15X29	-30.000	.000	29.000	.000	YMRP .0000 INCHES
(AF8006)	CA119A B61C1F12761V124E46V19R15X29	-40.000	.000	29.000	.000	ZMRP .0000 INCHES
						SCALE .0405 SCALE





FIG 5 ELEVON EFFECTIVENESS - ELEVON E46 (NEGATIVE ELEVON DEFLECTIONS)



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPOBRK	AIRTON	REFERENCE INFORMATION
{AF8001}	0A119A B61C1F12P51V124E46V1SR15X29	.000	.000	25.000	.000	SREF 2690 0100 50.FT.
{AF8030}	0A119A B61C1F12P51V124E46V1SR15X29	.000	.000	25.000	.000	LREF 474.8100 INCHES
{AF8020}	0A119A B61C1F12P51V124E46V1SR15X29	-10.000	.000	25.000	.000	BREF 936.6800 INCHES
{AF8013}	0A119A B61C1F12P51V124E46V1SR15X29	-20.000	.000	25.000	.000	XMRP 1076.4800 INCHES
{AF8010}	0A119A B61C1F12P51V124E46V1SR15X29	-30.000	.000	25.000	.000	YMRP .0000 INCHES
{AF8009}	0A119A B61C1F12P51V124E46V1SR15X29	-40.000	.000	25.000	.000	ZMRP 375.0000 INCHES
						SCALE .0305



LIFT/FOREBODY DRAG RATIO, L/DF

FIG 5 ELEVON EFFECTIVENESS - ELEVON E46 (NEGATIVE ELEVON DEFLECTIONS)

(A)MACH = .26


DATA SET SYMBOL CONFIGURATION DESCRIPTION

(AF8001)	GA119A	BBIC11F12751V124E16V1SR15X29
(AF8002)	GA119A	BBIC11F12751V124E16V1SR15X29
(AF8003)	GA119A	BBIC11F12751V124E16V1SR15X29
(AF8004)	GA119A	BBIC11F12751V124E16V1SR15X29
(AF8005)	GA119A	BBIC11F12751V124E16V1SR15X29

REFERENCE INFORMATION

SREF	2690.0100	SO.FT.
LREF	474.8100	INCHES
BREF	936.8600	INCHES
XTRP	1076.4800	INCHES
YTRP	.0000	INCHES
ZTRP	375.0000	INCHES
SCALE	.0405	INCHES

BDFLAP	.000
SPDRBK	25.000
AIIIRON	.000
ELEVON	.000
	10.000
	15.000
	20.000
	25.000
	30.000
	35.000
	40.000



LONGITUDINAL CENTER OF PRESSURE LOCATION, XCP/L

FIG 5 ELEVON EFFECTIVENESS - ELEVON E46 (NEGATIVE ELEVON DEFLECTIONS)

CAJMACH = .26

PAGE 20



REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR.

DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPDBRK	AIRLON	REFERENCE INFORMATION
(AF8051)	0A119A B61C11F 275 V124E47V19R15X29	20.000	.000	25.000	.000	SREF 2690.0100 SO.FT.
(AF8049)	0A119A B61C11F 275 V124E47V19R15X29	15.000	.000	25.000	.000	SREF 474.8100 INCHES
(AF8025)	0A119A B61C11F 275 V124E47V19R15X29	10.000	.000	25.000	.000	SREF 936.6800 INCHES
(AF8034)	0A119A B61C11F 275 V124E47V19R15X29	5.000	.000	25.000	.000	XTRP 1076.4800 INCHES
(AF8041)	0A119A B61C11F 275 V124E47V19R15X29	0.000	.000	25.000	.000	YTRP 375.0000 INCHES
(AF8032)	0A119A B61C11F 275 V124E47V19R15X29	-5.000	.000	25.000	.000	ZTRP .0405 SCALE




FIG 6 ELEVON EFFECTIVENESS - ELEVON E47 (POSITIVE ELEVON DEFLECTIONS)

(AJMACH = .26

PAGE 21



DATA SET SYMBOL CONFIGURATION DESCRIPTION

(AF8051) DA119A 861C11F12451V124E47V1SR15X29

(AF8049) DA119A 861C11F12451V124E47V1SR15X29

(AF8029) DA119A 861C11F12451V124E47V1SR15X29

(AF8034) DA119A 861C11F12451V124E47V1SR15X29

(AF8041) DA119A 861C11F12451V124E47V1SR15X29

(AF8032) DA119A 861C11F12451V124E47V1SR15X29

ELEVON BOFLAP SPOBRK AILRON REFERENCE INFORMATION

20.000 .000 25.000 .000 2690.0100 50.FT.

15.000 .000 25.000 .000 474.8100 INCHES

10.000 .000 25.000 .000 936.6800 INCHES

5.000 .000 25.000 .000 1076.4800 INCHES

.000 .000 25.000 .000 YPRP INCHES

-5.000 .000 25.000 .000 ZPRP INCHES

SCALE .0405 SCALE




FIG 6 ELEVON EFFECTIVENESS - ELEVON F47 (POSITIVE ELEVON DEFLECTIONS)

(A)MACH = .26



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELFVON	BOFLAP	SPOBRK	AILRON	REFERENCE INFORMATION
(AF 8051)	DA119A 861C1F12751V124E47V19R15X29	20.000	.000	25.000	.000	SREF 269C 0.00 SC.FT.
(AF 8049)	DA119A 861C1F12751V124E47V19R15X29	15.000	.000	25.000	.000	LREF 474.8100 INCHES
(AF 8025)	DA119A 861C1F12751V124E47V19R15X29	10.000	.000	25.000	.000	BREF 936.6800 INCHES
(AF 8034)	DA119A 861C1F12751V124E47V19R15X29	5.000	.000	25.000	.000	XMRP 1076.4800 INCHES
(AF 8041)	DA119A 861C1F12751V124E47V19R15X29	0.000	.000	25.000	.000	ZMRP 375.0000 INCHES
(AF 8032)	DA119A 861C1F12751V124E47V19R15X29	-5.000	.000	25.000	.000	SCALE .3405 SCALE




FIG 6 ELEVON EFFECTIVENESS - ELEVON E47 (POSITIVE ELEVON DEFLECTIONS)

CAJ MACH = .26

DATA SET SYMBOL	CONFIGURATION DESCRIPTION
(AF8001)	0A119A BS1C1F12G1V124E47V1SR1SX28
(AF8002)	0A119A BS1C1F12G1V124E47V1SR1SX28
(AF8003)	0A119A BS1C1F12G1V124E47V1SR1SX28
(AF8004)	0A119A BS1C1F12G1V124E47V1SR1SX28
(AF8005)	0A119A BS1C1F12G1V124E47V1SR1SX28
(AF8006)	0A119A BS1C1F12G1V124E47V1SR1SX28

ELEVON	BOFLAP	SPOBRK	A1LRON	REFERENCE INFORMATION
20.000	.000	25.000	.000	SREF 268L .1100 SQ.FT
15.000	.000	25.000	.000	LREF 474.8100 INCHES
10.000	.000	25.000	.000	BREF 536.6800 INCHES
5.000	.000	25.000	.000	XPRP 1076.1800 INCHES
.000	.000	25.000	.000	YPRP .0000 INCHES
-.5.000	.000	25.000	.000	ZPRP 375.0000 INCHES
				SCALE .0405 SCALE




FIG 6 ELEVON EFFECTIVENESS - ELEVON E47 (POSITIVE ELEVON DEFLECTION)



DATA SET SYMBOL CONFIGURATION DESCRIPTION

{AF8031}	□	0A119A	BS1C11F	2V6	VI24E47V	SR15X29
{AF8049}	○	0A119A	BS1C11F	2V6	VI24E47V	SR15X29
{AF8025}	◇	0A119A	BS1C11F	2V6	VI24E47V	SR15X29
{AF8034}	△	0A119A	BS1C11F	2V6	VI24E47V	SR15X29
{AF8041}	□	0A119A	BS1C11F	2V6	VI24E47V	SR15X29
{AF8032}	△	0A119A	BS1C11F	2V6	VI24E47V	SR15X29

ELEVON BDFLAP SPOBRK AILRON REFERENCE INFORMATION

20.000	.000	25.000	.000	SREF	2690.0103	SQ.FT.
15.000	.000	20.000	.000	LREF	174.8100	INCHES
10.000	.000	15.000	.000	TREF	936.6800	INCHES
5.000	.000	10.000	.000	XPRP	1076.4800	INCHES
.000	.000	5.000	.000	YPRP	.0000	INCHES
-5.000	.000	.000	.000	ZPRP	375.0000	INCHES
				SCALE	.0405	SCALE






FIG 6 ELEVON EFFECTIVENESS - ELEVON E47 (POSITIVE ELEVON DEFLECTIONS)

(A)MACH = .26



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPOBRK	AILTRON	REFERENCE INFORMATION
(AF8031)	0A119A B61C1F12M51V124E47V1SR15X29	20.000	.000	25.000	.000	SREF 2630.0100 SQ.FT.
(AF8049)	0A119A B61C1F12M51V124E47V1SR15X29	15.000	.000	25.000	.000	LREF 474.8100 INCHES
(AF8025)	0A119A B61C1F12M51V124E47V1SR15X29	10.000	.000	25.000	.000	BREF 936.6900 INCHES
(AF8034)	0A119A B61C1F12M51V124E47V1SR15X29	5.000	.000	25.000	.000	XMRP 1076.4600 INCHES
(AF8041)	0A119A B61C1F12M51V124E47V1SR15X29	.000	.000	25.000	.000	YMRP .0000 INCHES
(AF8032)	0A119A B61C1F12M51V124E47V1SR15X29	-5.000	.000	25.000	.000	ZMRP 375.0000 INCHES
						SCALE .0405



PITCHING MOMENT COEFFICIENT, CLM

FIG 6 ELEVON EFFECTIVENESS - ELEVON E47 (POSITIVE ELEVON DEFLECTIONS)



DATA SET SYMBOL CONFIGURATION DESCRIPTION

{ AF8051 }	DA119A	B61C1	F12P5	V124E	47V1	SR15X29
{ AF8049 }	DA119A	B61C1	F12P5	V124E	47V1	SR15X29
{ AF8025 }	DA119A	B61C1	F12P5	V124E	47V1	SR15X29
{ AF8034 }	DA119A	B61C1	F12P5	V124E	47V1	SR15X29
{ AF8041 }	DA119A	B61C1	F12P5	V124E	47V1	SR15X29
{ AF8032 }	DA119A	B61C1	F12P5	V124E	47V1	SR15X29

REFERENCE INFORMATION

SREF	2690.0100	50 FT
LREF	474.8100	INCHES
BREF	936.6800	INCHES
XPRP	1076.4800	INCHES
YPRP	.0000	INCHES
ZPRP	375.0000	INCHES
SCALE	.0405	SCALE

ELEVON BOFLAP SPOBRK AIRLON

ELEVON	20.000	.000	.000	.000
BOFLAP	15.000	.000	.000	.000
SPOBRK	5.000	.000	.000	.000
AIRLON	-5.000	.000	.000	.000

FOREBODY LIFT COEFFICIENT, CLF




FIG 6 ELEVON EFFECTIVENESS - ELEVON E47 (POSITIVE ELEVON DEFLECTIONS)

CLM/MACH = .26



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	REF LAP	SPDRX	ALLWON	REFERENCE	SCALE
{AF8051}	DA119A B61C1 F12M5 V124E47 V19R15X29	70.000	.000	75.000	.000	265.0100	.0405
{AF8049}	DA119A B61C1 F12M5 V124E47 V13R15X29	15.000	.000	5.000	.000	474.8100	.0405
{AF8025}	DA119A B61C1 F12M5 V124E47 V19R15X29	10.000	.000	2.000	.000	936.0300	.0405
{AF8034}	DA119A B61C1 F12M5 V124E47 V19R15X29	5.000	.000	2.000	.000	1076.4800	.0405
{AF8041}	DA119A B61C1 F12M5 V124E47 V19R15X29	0.000	.000	2.000	.000	375.0000	.0405
{AF8032}	DA119A B61C1 F12M5 V124E47 V19R15X29	-5.000	.000	25.000	.000		





FIG 6 ELEVON EFFECTIVENESS - ELEVON E47 (POSITIVE ELEVON DEFLECTIONS)

(A)MACH = .26



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPOSRK	AILRON	REFERENCE INFORMATION
(AF8051)	CA119A B61C1F12751V124E47V19R15X29	20.000	.000	25.000	.000	SREF 2690.0100 50.FT.
(AF8049)	CA119A B61C1F12751V124E47V19R15X29	15.000	.000	23.000	.000	LREF 474.8100 INCHES
(AF8025)	CA119A B61C1F12751V124E47V19R15X29	10.000	.000	23.000	.000	BREF 936.6800 INCHES
(AF8034)	CA119A B61C1F12751V124E47V19R15X29	5.000	.000	23.000	.000	XMRP 1076.1800 INCHES
(AF8041)	CA119A B61C1F12751V124E47V19R15X29	.000	.000	25.000	.000	YMRP 375.0000 INCHES
(AF8032)	CA119A B61C1F12751V124E47V19R15X29	-5.000	.000	25.000	.000	ZMRP 375.0000 INCHES
						SCALE .0405



LIFT/FOREBODY DRAG RATIO, L/D


FIG 6 ELEVON EFFECTIVENESS - ELEVON E47 (POSITIVE ELEVON DEFLECTIONS)



DATA SET SYMBOL CONFIGURATION DESCRIPTION

(AF8051)	Q	3A11SA	86	C1	F1	275	V1	24E	47V1	SR15X29
(AF8049)	X	3A11SA	86	C1	F1	275	V1	24E	47V1	SR15X29
(AF8025)	X	3A11SA	86	C1	F1	275	V1	24E	47V1	SR15X29
(AF8034)	X	3A11SA	86	C1	F1	275	V1	24E	47V1	SR15X29
(AF8041)	X	3A11SA	86	C1	F1	275	V1	24E	47V1	SR15X29
(AF8032)	X	3A11SA	86	C1	F1	275	V1	24E	47V1	SR15X29

ELEVON	REF. AD	WINDMCH	WINDMCH	PER. FORCE	WINDMCH	SCALE
20.000	.000	20.000	.000	2590.0000	37.5	.0400
15.000	.000	20.000	.000	474.8100	37.5	.0400
10.000	.000	20.000	.000	935.6800	37.5	.0400
5.000	.000	20.000	.000	1076.4800	37.5	.0400
.000	.000	20.000	.000	375.0000	37.5	.0400
-5.000	.000	20.000	.000	375.0000	37.5	.0400



LONGITUDINAL CENTER OF PRESSURE LOCATION, XCP/L

FIG 6 ELEVON EFFECTIVENESS - ELEVON E47 (POSITIVE ELEVON DEFLECTIONS)

(A)MACH = .26

PAGE 30



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPOBRK	AIRLON	REFERENCE INFORMATION
(AF8041)	DA119A B61C1F12M5IV124E47V1SR15X29	.000	.000	25.000	.000	SREF 2690.0100 SQ.FT.
(AF8026)	DA119A B61C1F12M5IV124E47V1SR15X29	-10.000	.000	25.000	.000	LREF 474.8100 INCHES
(AF8018)	DA119A B61C1F12M5IV124E47V1SR15X29	-15.000	.000	25.000	.000	BREF 536.8800 INCHES
(AF8017)	DA119A B61C1F12M5IV124E47V1SR15X29	-20.000	.000	25.000	.000	XMRP 1076.4800 INCHES
(AF8011)	DA119A B61C1F12M5IV124E47V1SR15X29	-30.000	.000	25.000	.000	YMRP .0000 INCHES
(AF8005)	DA119A B61C1F12M5IV124E47V1SR15X29	-40.000	.000	25.000	.000	ZMRP 375.0000 INCHES
						SCALE .0405




FIG 7 ELEVON EFFECTIVENESS - ELEVON E47 (NEGATIVE ELEVON DEFLECTIONS)

(A)MACH = .26



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPDRK	AILERON	REFERENCE INFORMATION
(AF6041)	0A119A 861C11F12751V124E47V19R15X29	.000	.000	25.000	.000	SREF 269C 0100 50.FT
(AF6026)	0A119A 861C11F12751V124E47V19R15X29	-10.000	.000	25.000	.000	LREF 474 8100 INCHES
(AF6018)	0A119A 861C11F12751V124E47V19R15X29	-15.000	.000	25.000	.000	BREF 932 6800 INCHES
(AF6017)	0A119A 861C11F12751V124E47V19R15X29	-20.000	.000	25.000	.000	XMRP 107E 800 INCHES
(AF6011)	0A119A 861C11F12751V124E47V19R15X29	-30.000	.000	25.000	.000	YMRP 37E 3000 INCHES
(AF6005)	0A119A 861C11F12751V124E47V19R15X29	-40.000	.000	25.000	.000	ZMRP 37E 3000 INCHES
						SCALE 0405




FIG 7 ELEVON EFFECTIVENESS - ELEVON E47 (NEGATIVE ELEVON DEFLECTIONS)
 (A)MACH = .26



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BLFLAP	SPROBK	AILERON	REFERENCE INFORMATION
(AF8041)	0A119A 661C11F12751V124E47V19R15X29	.000	.000	25.000	.000	SREF 2690.0100 SQ.FT.
(AF8026)	0A119A 661C11F12751V124E47V19R15X29	-10.000	.000	25.000	.000	LREF 47A.8100 INCH-ES
(AF8018)	0A119A 661C11F12751V124E47V19R15X29	-15.000	.000	25.000	.000	BREF 936.6800 INCH-ES
(AF8017)	0A119A 661C11F12751V124E47V19R15X29	-20.000	.000	25.000	.000	XMRP 1076.4800 INCH-ES
(AF8011)	0A119A 661C11F12751V124E47V19R15X29	-30.000	.000	25.000	.000	YMRP .0000 INCH-ES
(AF8005)	0A119A 661C11F12751V124E47V19R15X29	-40.000	.000	25.000	.000	ZMRP 375.0000 INCH-ES
						SCALE .0405





FIG 7 ELEVON EFFECTIVENESS - ELEVON E47 (NEGATIVE ELEVON DEFLECTIONS)

CAJ MACH = .26

DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPOBRK	AILRON	REFERENCE INFORMATION
(AF8041)	CA119A BS1C1F12V5V124E47V19R15X29	.000	.000	25.000	.000	SREF 2690.0100 SO.FT.
(AF8026)	CA119A BS1C1F12V5V124E47V19R15X29	-10.000	.000	25.000	.000	LREF 474.8100 INCHES
(AF8018)	CA119A BS1C1F12V5V124E47V19R15X29	-15.000	.000	25.000	.000	BREF 926.5800 INCHES
(AF8017)	CA119A BS1C1F12V5V124E47V19R15X29	-20.000	.000	25.000	.000	XMRP 1076.4800 INCHES
(AF8011)	CA119A BS1C1F12V5V124E47V19R15X29	-30.000	.000	25.000	.000	YMRP 375.0000 INCHES
(AF8005)	CA119A BS1C1F12V5V124E47V19R15X29	-40.000	.000	25.000	.000	ZMRP .0405 SCALE



BASE AXIAL FORCE COEFFICIENT, CAB

FIG 7 ELEVON EFFECTIVENESS - ELEVON E47 (NEGATIVE ELEVON DEFLECTIONS)



REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR

DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPOBRK	AILERON	REFERENCE INFORMATION
{ AF8041 }	0A119A B61C1IF1205IV124E47V1SR15X29	.000	.000	25.000	.000	2690.0100 SO.FT.
{ AF8026 }	0A119A B61C1IF1205IV124E47V1SR15X29	-10.000	.000	25.000	.000	474.3100 INCHES
{ AF8018 }	0A119A B61C1IF1205IV124E47V1SR15X29	-15.000	.000	25.000	.000	936.6800 INCHES
{ AF8017 }	0A119A B61C1IF1205IV124E47V1SR15X29	-20.000	.000	25.000	.000	1076.1800 INCHES
{ AF8011 }	0A119A B61C1IF1205IV124E47V1SR15X29	-30.000	.000	25.000	.000	375.0000 INCHES
{ AF8005 }	0A119A B61C1IF1205IV124E47V1SR15X29	-40.000	.000	25.000	.000	.0405 SCALE




FIG 7 ELEVON EFFECTIVENESS - ELEVON E47 (NEGATIVE ELEVON DEFLECTIONS)

(A)MACH = .26




DATA SET SYMBOL CONFIGURATION DESCRIPTION

{AFB041}	□	GA11SA	BBICIF	275	V124E47V	SR15X29
{AFB026}	○	GA11SA	BBICIF	275	V124E47V	SR15X29
{AFB018}	△	GA11SA	BBICIF	275	V124E47V	SR15X29
{AFB017}	◇	GA11SA	BBICIF	275	V124E47V	SR15X29
{AFB011}	□	GA11SA	BBICIF	275	V124E47V	SR15X29
{AFB005}	○	GA11SA	BBICIF	275	V124E47V	SR15X29

REFERENCE INFORMATION

SREF	2690.0100	SD, FT.
LREF	474.8100	INCHES
BREF	936.6800	INCHES
XMRP	1076.4800	INCHES
YMRP	.0000	INCHES
ZMRP	375.0000	INCHES
SCALE	.0405	SCALE

ELEVON	.000	SPDRK	.000	AIRLON	.000
BDFLAP	.000	SPDRK	25.000	AIRLON	.000
ELEVON	-10.000	SPDRK	25.000	AIRLON	.000
BDFLAP	.000	SPDRK	25.000	AIRLON	.000
ELEVON	-15.000	SPDRK	25.000	AIRLON	.000
BDFLAP	.000	SPDRK	25.000	AIRLON	.000
ELEVON	-20.000	SPDRK	25.000	AIRLON	.000
BDFLAP	.000	SPDRK	25.000	AIRLON	.000
ELEVON	-30.000	SPDRK	25.000	AIRLON	.000
BDFLAP	.000	SPDRK	25.000	AIRLON	.000
ELEVON	-40.000	SPDRK	25.000	AIRLON	.000
BDFLAP	.000	SPDRK	25.000	AIRLON	.000



PITCHING MOMENT COEFFICIENT, CLM

FIG 7 ELEVON EFFECTIVENESS - ELEVON E47 (NEGATIVE ELEVON DEFLECTIONS)

(M)MACH = .26



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPDBRK	AILEVON	REFERENCE INFORMATION
(AF8041)	CA11SA BS(C)F 275(V)24E47V1SR15X29	.000	.000	25.000	.000	SREF 2690.0100 SO.F.T.
(AF8026)	CA11SA BS(C)F 275(V)24E47V1SR15X29	-10.000	.000	25.000	.000	LREF 474.8100 I.C.H.E.S
(AF8016)	CA11SA BS(C)F 275(V)24E47V1SR15X29	-15.000	.000	25.000	.000	BREF 936.6800 I.C.H.E.S
(AF8017)	CA11SA BS(C)F 275(V)24E47V1SR15X29	-20.000	.000	25.000	.000	YMRP 1076.4800 I.C.H.E.S
(AF8011)	CA11SA BS(C)F 275(V)24E47V1SR15X29	-30.000	.000	25.000	.000	ZMRP 375.0000 I.C.H.E.S
(AF8005)	CA11SA BS(C)F 275(V)24E47V1SR15X29	-40.000	.000	25.000	.000	SCALE .0A05 SCALE




FIG 7 ELEVON EFFECTIVENESS - ELEVON E47 (NEGATIVE ELEVON DEFLECTIONS)

(A)MACH = .25



DATA SET 5 600

DESCRIPTION	SCALE	SPORADIC	REFERENCE	FUNCTION
(AF8041)	100	1000	1000	100
(AF8026)	100	1000	1000	100
(AF8018)	100	1000	1000	100
(AF8017)	100	1000	1000	100
(AF8011)	100	1000	1000	100
(AF8005)	100	1000	1000	100




FIG 7 CLF vs CD, EFFECTIVENESS - ELEVON E47 (NEGATIVE ELEVON DEFLECTION)



DATA SET: STREOL

CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPOBRK	AILTRON	REFERENCE INFORMATION
0A119A 861C11F 276 V124E47V SR15X29	.000	.000	25.000	.000	SREF 2690.0100 SO.FT.
0A119A 861C11F 276 V124E47V SR15X29	-10.000	.000	25.000	.000	LREF 474.8100 INCHES
0A119A 861C11F 276 V124E47V SR15X29	-15.000	.000	25.000	.000	BREF 936.8600 INCHES
0A119A 861C11F 276 V124E47V SR15X29	-20.000	.000	25.000	.000	XTRP 1076.0000 INCHES
0A119A 861C11F 276 V124E47V SR15X29	-30.000	.000	25.000	.000	YTRP 1076.0000 INCHES
0A119A 861C11F 276 V124E47V SR15X29	-40.000	.000	25.000	.000	ZTRP 375.0000 INCHES
					SCALE .0405




FIG 7 ELEVON EFFECTIVENESS - ELEVON E47 (NEGATIVE ELEVON DEFLECTIONS)

DATA SET SYMBOL CONFIGURATION DESCRIPTION

{AF8041}	□	GA11SA	BS1C11F	ZNS1V124E47V	SR15X28
{AF8026}	○	GA11SA	BS1C11F	ZNS1V124E47V	SR15X28
{AF8016}	△	GA11SA	BS1C11F	ZNS1V124E47V	SR15X28
{AF8017}	◇	GA11SA	BS1C11F	ZNS1V124E47V	SR15X28
{AF8011}		GA11SA	BS1C11F	ZNS1V124E47V	SR15X28
{AF8005}		GA11SA	BS1C11F	ZNS1V124E47V	SR15X28

REFERENCE INFORMATION

SREF	2690.0100	50. FT.
LREF	47A.8100	1.0465
BREF	936.6800	INCHES
XMRP	1076.1800	INCHES
YMRP	.0000	INCHES
ZMRP	375.0000	INCHES
SCALE	.0405	SCALE





FIG 7 ELEVON EFFECTIVENESS - ELEVON EA7 (NEGATIVE ELEVON DEFLECTIONS)

(A)MACH = .26



DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AF8052) CA119A B61C11F2MS1V24E48V19R15X29
 (AF8050) CA119A B61C11F2MC1V24E48V19R15X29
 (AF8074) CA119A B61C11F2MS1V24E48V19R15X29
 (AF8036) CA119A B61C11F2MS1V24E48V19R15X29
 (AF8004) CA119A B61C11F2MS1V24E48V19R15X29
 (AF8033) CA119A B61C11F2MS1V24E48V19R15X29

ELEVON BOFLAP SPOBRK AILRON REFERENCE INFORMATION
 20.000 .000 25.000 .000 2690.0100 SO.FT.
 15.000 .000 25.000 .000 474.8100 INCHES
 10.000 .000 25.000 .000 936.6900 INCHES
 5.000 .000 25.000 .000 1076.1800 INCHES
 .000 .000 25.000 .000 YMRP INCHES
 -5.000 .000 25.000 .000 ZMRP INCHES
 SCALE .0035 SCALE



FOREBODY LIFT COEFFICIENT, CLF

FIG 8 ELEVON EFFECTIVENESS - ELEVON E48 (POSITIVE ELEVON DEFLECTIONS)



DATA SET SYMBOL CONFIGURATION DESCRIPTION

(AF8052)	DA119A	B61C1	F12MS1	V124E4B	V19R15X29
(AF8050)	DA119A	B61C1	F12MS1	V124E4B	V19R15X29
(AF8024)	DA119A	B61C1	F12MS1	V124E4B	V19R15X29
(AF8035)	DA119A	B61C1	F12MS1	V124E4B	V19R15X29
(AF8004)	DA119A	B61C1	F12MS1	V124E4B	V19R15X29
(AF8033)	DA119A	B61C1	F12MS1	V124E4B	V19R15X29

ELEVON BOFLAP SPOBRK ALLRQ4 REFERENCE INFORMATION

20.000	.000	25.000	.000	SREF	2690.0100	50. FT.
15.000	.000	25.000	.000	LREF	474.8100	114. INCHES
10.000	.000	25.000	.000	BREF	935.8800	114. INCHES
5.000	.000	25.000	.000	XMRP	1076.4800	114. INCHES
.000	.000	25.000	.000	YMRP	.0000	114. INCHES
-5.000	.000	25.000	.000	ZMRP	375.0000	114. INCHES
				SCALE	.0405	SCALE





FIG 8 ELEVON EFFECTIVENESS - ELEVON E48 (POSITIVE ELEVON DEFLECTIONS)

(A)MACH = .26

PAGE 42



DATA SET SYMBOL	CONFIGURATION	DESCRIPTION	ELEVON	BOFLAP	SPOBRK	ALTRON	REFERENCE INFORMATION
(AF 8052)	DA119A 86	#124E18V19R15X29	20.000	.000	25.000	.000	SREF 2690.0100 SO.FT.
(AF 8050)	DA119A 86	#124E18V19R15X29	15.000	.000	25.000	.000	LREF 474.8100 INCHES
(AF 8024)	DA119A 86	#124E18V19R15X29	10.000	.000	25.000	.000	BREF 936.6900 INCHES
(AF 8035)	DA119A 86	#124E18V19R15X29	5.000	.000	25.000	.000	WREF 1076.1800 INCHES
(AF 8004)	DA119A 86	#124E18V19R15X29	.000	.000	25.000	.000	WREF 375.0000 INCHES
(AF 8033)	DA119A 96	#124E18V19R15X29	-5.000	.000	25.000	.000	SCALE 1:105 SCALE



FOREBODY AXIAL FORCE COEFFICIENT, CAF

FIG 8 ELEVON EFFECTIVENESS - ELEVON E48 (POSITIVE ELEVON DEFLECTIONS)

DATA SET SYMBOL CONFIGURATION DESCRIPTION REFERENCE INFORMATION SCALE

DATA SET SYMBOL	CONFIGURATION DESCRIPTION	REFERENCE INFORMATION	SCALE
(AF8052)	DA119A B61C1F12P51V124E48V1SR15X29	SREF 2690.0100	50.FT.
(AF8050)	DA119A B61C1F12P51V124E48V1SR15X29	LREF 474.6100	INCHES
(AF8024)	DA119A B61C1F12P51V124E48V1SR15X29	BREF 936.6800	INCHES
(AF8036)	DA119A B61C1F12P51V124E48V1SR15X29	XMRP 1076.4800	INCHES
(AF8004)	DA119A B61C1F12P51V124E48V1SR15X29	YMRP .0000	INCHES
(AF8033)	DA119A B61C1F12P51V124E48V1SR15X29	ZMRP .0405	INCHES

BASE AXIAL FORCE COEFFICIENT, CAB




FIG 8 ELEVON EFFECTIVENESS - ELEVON E48 (POSITIVE ELEVON DEFLECTIONS)



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	%FLAP	SPDRK	ATLRN	REFERENCE INFORMATION
(AF8052)	0A119A B61C1F12M5 V124E48V19R15X29	20.000	.000	25.000	.000	SREF 2690 0.100 SO.FT.
(AF8050)	0A119A B61C1F12M5 V124E48V19R15X29	15.000	.000	25.000	.000	LREF 474 0.100 INCHES
(AF8024)	0A119A B61C1F12M5 V124E48V19R15X29	10.000	.000	25.000	.000	BREF 936 0.000 INCHES
(AF8006)	0A119A B61C1F12M5 V124E48V19R15X29	5.000	.000	25.000	.000	XMRP 1076 0.000 INCHES
(AF8004)	0A119A B61C1F12M5 V124E48V19R15X29	.000	.000	25.000	.000	YMRP 375 0.000 INCHES
(AF8033)	0A119A B61C1F12M5 V124E48V19R15X29	-5.000	.000	25.000	.000	SCALE 1.005






FIG 8 ELEVON EFFECTIVENESS - ELEVON E48 (POSITIVE ELEVON DEFLECTIONS)

(A)MACH = .26




DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPOBRK	A1LRON	REFERENCE INFORMATION	SCALE
{AF8052}	0A119A 861C1F12751V124E48V19R15X29	20.000	.000	25.000	.000	SREF 2690.0100	50.FT.
{AF8050}	0A119A 861C1F12751V124E48V19R15X29	15.070	.000	25.000	.000	LREF 474.8100	INCHES
{AF8024}	0A119A 861C1F12751V124E48V19R15X29	10.000	.000	25.000	.000	BREF 936.6800	INCHES
{AF8033}	0A119A 861C1F12751V124E48V19R15X29	5.000	.000	25.000	.000	XMRP 1076.4800	INCHES
{AF8004}	0A119A 861C1F12751V124E48V19R15X29	-5.000	.000	25.000	.000	YMRP .0000	INCHES
{AF8033}	0A119A 861C1F12751V124E48V19R15X29		.000	25.000	.000	ZMRP 375.0000	INCHES
							SCALE



PITCHING MOMENT COEFFICIENT, CLM

FIG 8 ELEVON EFFECTIVENESS - ELEVON E48 (POSITIVE ELEVON DEFLECTIONS)



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	REF LAP	SPOBRK	AIRRON	REFERENCE INFORMATION
(AF8052)	0A119A B61C1 F1275 V124E48V1SR15X29	20.000	.000	25.000	.000	SREF 265.0100 SQ.FT.
(AF8050)	F1119A B61C1 F1275 V124E48V1SR15X29	15.000	.000	25.000	.000	LREF 47.8100 INCHES
(AF8074)	0A119A B61C1 F1275 V124E48V1SR15X29	10.000	.000	25.000	.000	BREF 93.5800 INCHES
(AF8075)	0A119A B61C1 F1275 V124E48V1SR15X29	5.000	.000	25.000	.000	XMRP 1076.4800 INCHES
(AF8004)	0A119A B61C1 F1275 V124E48V1SR15X29	.000	.000	25.000	.000	YMRP .0000 INCHES
(AF8003)	0A119A B61C1 F1275 V124E48V1SR15X29	-5.000	.000	25.000	.000	ZMRP 375.0405 INCHES
						SCALE




FIG 8 ELEVON EFFECTIVENESS - ELEVON E48 (POSITIVE ELEVON DEFLECTIONS)

(M)MACH = .26



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BDFLAP	SPOBRK	AILERON	REFERENCE INFORMATION
(AF8052)	GA11SA BS1C1F12P51V124E48V1SR15X29	20.000	.000	25.000	.000	SREF 2690.0100 SO.FT. INCHES
(AF8050)	GA11SA BS1C1F12P51V124E48V1SR15X29	15.000	.000	25.000	.000	LREF 474.8100 INCHES
(AF8024)	GA11SA BS1C1F12P51V124E48V1SR15X29	10.000	.000	25.000	.000	BREF 936.6800 INCHES
(AF8035)	GA11SA BS1C1F12P51V124E48V1SR15X29	5.000	.000	25.000	.000	XMRP 1076.4800 INCHES
(AF8004)	GA11SA BS1C1F12P51V124E48V1SR15X29	-5.000	.000	25.000	.000	ZMRP 375.0000 INCHES
(AF8033)	GA11SA BS1C1F12P51V124E48V1SR15X29					SCALE .0405 SCALE




FIG 8 ELEVON EFFECTIVENESS - ELEVON E48 (POSITIVE ELEVON DEFLECTIONS)



DATA SET SYMBOL CONFIGURATION DESCRIPTION REFERENCE INFORMATION

(AF8052)	CA119A B61C1 F12V51V124E48V19R15X29	SREF 2690.0100 SQ. FT.
(AF8050)	CA119A B61C1 F12V51V124E48V19R15X29	LREF 474.8100 INCHES
(AF8074)	CA119A B61C1 F12V51V124E48V19R15X29	BREF 936.6800 INCHES
(AF8075)	CA119A B61C1 F12V51V124E48V19R15X29	XMRP 1076.1800 INCHES
(AF8004)	CA119A B61C1 F12V51V124E48V19R15X29	ZMRP .0000 INCHES
(AF8033)	CA119A B61C1 F12V51V124E48V19R15X29	ZMRP 375.0000 INCHES

ELEVON BDFLAP SPOBRK AILTRON SCALE

20.000	.000	25.000	.000	.0495
15.000	.000	25.000	.000	
10.000	.000	25.000	.000	
5.000	.000	25.000	.000	
.000	.000	25.000	.000	
-5.000	.000	25.000	.000	





FIG 8 ELEVON EFFECTIVENESS - ELEVON E48 (POSITIVE ELEVON DEFLECTIONS)
 (A)MACH = .26 PAGE 49




DATA SET SYMBOL CONFIGURATION DESCRIPTION

{ AF8032 }	0A119A	861C1F12751V124E48V19R15X29
{ AF8033 }	0A119A	861C1F12751V124E48V19R15X29
{ AF8034 }	0A119A	861C1F12751V124E48V19R15X29
{ AF8035 }	0A119A	861C1F12751V124E48V19R15X29
{ AF8036 }	0A119A	861C1F12751V124E48V19R15X29
{ AF8037 }	0A119A	861C1F12751V124E48V19R15X29

ELEVON BOFLAP SPOBRK AILRON REFERENCE INFORMATION

20.000	.000	.000	2690.0100	50.FT
15.000	.000	.000	474.8100	INCHES
10.000	.000	.000	536.6600	INCHES
5.000	.000	.000	1076.4800	INCHES
.000	.000	.000		
.000	.000	.000	375.0000	INCHES
-5.000	.000	.000		SCALE
			.0405	SCALE



LONGITUDINAL CENTER OF PRESSURE LOCATION, XCP/L

FIG 8 ELEVON EFFECTIVENESS - ELEVON E48 (POSITIVE ELEVON DEFLECTIONS)



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPOBRK	AILDRN	REFERENCE INFORMATION
{AF8004}	DA119A B61C1 F12M5 V124E48V1 SR15X29	.000	.000	25.000	.000	SREF 2690.0100 SQ.FT.
{AF8007}	DA119A B61C1 F12M5 V124E48V1 SR15X29	-10.000	.000	25.000	.000	LREF 474.8100 INCHES
{AF8019}	DA119A B61C1 F12M5 V124E48V1 SR15X29	-15.000	.000	25.000	.000	BREF 936.6900 INCHES
{AF8016}	DA119A B61C1 F12M5 V124E48V1 SR15X29	-20.000	.000	25.000	.000	XPRP 1076.4800 INCHES
{AF8012}	DA119A B61C1 F12M5 V124E48V1 SR15X29	-30.000	.000	25.000	.000	YPRP .0000 INCHES
{AF8006}	DA119A B61C1 F12M5 V124E48V1 SR15X29	-40.000	.000	25.000	.000	ZPRP .0000 INCHES
						SCALE .0405





FIG 9 ELEVON EFFECTIVENESS - ELEVON E48 (NEGATIVE ELEVON DEFLECTIONS)



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPOBRK	AILERON	REFERENCE INFORMATION(S)
{ AF004 }	0A11SA BS1C1 F12P5 V124E48V1SR15X29	.000	.000	25.000	.000	2690 .0100 90.F.T.
{ AF007 }	0A11SA BS1C1 F12P5 V124E48V1SR15X29	-10.000	.000	25.000	.000	474 .8100 INCHES
{ AF010 }	0A11SA BS1C1 F12P5 V124E48V1SR15X29	-15.000	.000	25.000	.000	536 .6800 INCHES
{ AF016 }	0A11SA BS1C1 F12P5 V124E48V1SR15X29	-20.000	.000	25.000	.000	1076 .4800 INCHES
{ AF012 }	0A11SA BS1C1 F12P5 V124E48V1SR15X29	-30.000	.000	25.000	.000	375 .0700 INCHES
{ AF006 }	0A11SA BS1C1 F12P5 V124E48V1SR15X29	-40.000	.000	25.000	.000	SCALE .0405




FIG 9 ELEVON EFFECTIVENESS - ELEVON E48 (NEGATIVE ELEVON DEFLECTIONS)

(A.)MACH = .26



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	S-DOVRK	AIRLON	REFERENCE INFORMATION
(AF8004)	CA119A B61C1F12751V124E48V1SR15X29	.000	.000	25.000	.000	SREF 2690.0130 50.FT.
(AF8077)	CA119A B61C1F12751V124E48V1SR15X29	-10.000	.000	25.000	.000	LREF 474.8100 INCHES
(AF8019)	CA119A B61C1F12751V124E48V1SR15X29	-15.000	.000	25.000	.000	BREF 936.6800 INCHES
(AF8016)	CA119A B61C1F12751V124E48V1SR15X29	-20.000	.000	25.000	.000	XRRP 1076.4900 INCHES
(AF8012)	CA119A B61C1F12751V124E48V1SR15X29	-30.000	.000	25.000	.000	YRRP 5.0000 INCHES
(AF8006)	CA119A B61C1F12751V124E48V1SR15X29	-40.000	.000	25.000	.000	ZRRP 5.0405 INCHES
						SCALE





FIG 9 ELEVON EFFECTIVENESS - ELEVON E48 (NEGATIVE ELEVON DEFLECTIONS)

DATA SET SYMBOL CONFIGURATION DESCRIPTION REFERENCE INFORMATION

DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BDFLAP	SPOBRK	AILRON	REF	SCALE
{AF8004}	DA119A B61C1F12M5V124E48V1SR15X29	.000	.000	25.000	.000	SREF	2690.0100
{AF8027}	DA119A B61C1F12M5V124E48V1SR15X29	-10.000	.000	25.000	.000	LREF	474.8100
{AF8019}	DA119A B61C1F12M5V124E48V1SR15X29	-15.000	.000	25.000	.000	BREF	936.6800
{AF8016}	DA119A B61C1F12M5V124E48V1SR15X29	-20.000	.000	25.000	.000	XMRP	1076.4800
{AF8012}	DA119A B61C1F12M5V124E48V1SR15X29	-30.000	.000	25.000	.000	YMRP	375.0000
{AF8006}	DA119A B61C1F12M5V124E48V1SR15X29	-40.000	.000	25.000	.000	ZMRP	.0405



BASE AXIAL FORCE COEFFICIENT, CAB

FIG 9 ELEVON EFFECTIVENESS - ELEVON E48 (NEGATIVE ELEVON DEFLECTIONS)



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BUFLAP	SPOBRK	AILRON	REFERENCE INFORMATION
(AF8004)	0A119A B61C1F 2M5 V124E48V19R15X29	.000	.000	25.000	.000	SREF 2690.0100 SO.FT.
(AF8027)	0A119A B61C1F 2M5 V124E48V19R15X29	-10.000	.000	25.000	.000	LREF 474.8100 INCHES
(AF8019)	0A119A B61C1F 2M5 V124E48V19R15X29	-15.000	.000	25.000	.000	BREF 936.6807 INCHES
(AF8016)	0A119A B61C1F 2M5 V124E48V19R15X29	-20.000	.000	25.000	.000	YMRP 1076.4900 INCHES
(AF8012)	0A119A B61C1F 2M5 V124E48V19R15X29	-30.000	.000	25.000	.000	ZMRP 375.0000 INCHES
(AF8006)	0A119A B61C1F 2M5 V124E48V19R15X29	-40.000	.000	25.000	.000	SCALE .0105 SCALE




FIG 9 ELEVON EFFECTIVENESS - ELEVON E48 (NEGATIVE ELEVON DEFLECTIONS)

CAJ MACH = .26



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SFOBRK	AIIIRON	REFERENCE INFORMATION
{AF8004}	0A119A B61C1F1261V124E48V19R15X29	.000	.000	29.000	.000	SREF 2690.0100 SO.FT
{AF8007}	0A119A B61C1F1261V124E48V19R15X29	-10.000	.000	29.000	.000	LREF 474.8100 INCHES
{AF8019}	0A119A B61C1F1261V124E48V19R15X29	-15.000	.000	29.000	.000	BREF 936.6900 INCHES
{AF8016}	0A119A B61C1F1261V124E48V19R15X29	-20.000	.000	29.000	.000	XPRP 1076.1900 INCHES
{AF8012}	0A119A B61C1F1261V124E48V19R15X29	-30.000	.000	29.000	.000	YPRP .0000 INCHES
{AF8006}	0A119A B61C1F1261V124E48V19R15X29	-40.000	.000	29.000	.000	ZPRP .0000 INCHES
						SCALE .0405 SCALE




FIG 9 ELEVON EFFECTIVENESS - ELEVON E48 (NEGATIVE ELEVON DEFLECTIONS)



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPOBRK	AILRON	REFERENCE INFORMATION
(AF8004)	0A119A B61C11F 2MS1V124E48V19R15X29	.000	.000	25.000	.000	SREF 2690 0100 SQ.FT
(AF8077)	0A119A B61C11F 2MS1V124E48V19R15X29	-10.000	.000	25.000	.000	LREF 47X 8100 INCHES
(AF8019)	0A119A B61C11F 2MS1V124E48V19R15X29	-15.000	.000	25.000	.000	DRLF 936.5800 INCHES
(AF8016)	0A119A B61C11F 2MS1V124E48V19R15X29	-20.000	.000	25.000	.000	AMRP 1076.4800 INCHES
(AF8012)	0A119A B61C11F 2MS1V124E48V19R15X29	-30.000	.000	25.000	.000	YMRP .0000 INCHES
(AF8006)	0A119A B61C11F 2MS1V124E48V19R15X29	-40.000	.000	25.000	.000	ZMRP 375.0000 INCHES
						SCALE .0405




FIG 9 ELEVON EFFECTIVENESS - ELEVON E48 (NEGATIVE ELEVON DEFLECTIONS)
 (A)MACH = .26 PAGE 57

DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPODBRK	AILERON	REFERENCE INFORMATION
(AF8004)	0A119A B61C1IF12H5IV124E48V1SR1SX29	.000	.000	25.000	.000	SREF 2690 0100 SQ.FT.
(AF8007)	0A119A B61C1IF12H5IV124E48V1SR1SX29	-10.000	.000	25.000	.000	LREF 474.8100 INCHES
(AF8019)	0A119A B61C1IF12H5IV124E48V1SR1SX29	-15.000	.000	25.000	.000	BREF 936.6800 INCHES
(AF8016)	0A119A B61C1IF12H5IV124E48V1SR1SX29	-20.000	.000	25.000	.000	XREF 1076.4800 INCHES
(AF8012)	0A119A B61C1IF12H5IV124E48V1SR1SX29	-30.000	.000	25.000	.000	ZREF 375.0000 INCHES
(AF8006)	0A119A B61C1IF12H5IV124E48V1SR1SX29	-40.000	.000	25.000	.000	SCALE .0405 SCALE




FIG 9 ELEVON EFFECTIVENESS - ELEVON E48 (NEGATIVE ELEVON DEFLECTION)




REFERENCE FORMATION
 SREF 285.0100 SQ.FT.
 XREF 474.8100 INCHES
 YREF 306.8300 INCHES
 XMAP 1071.0000 INCHES
 YMAP 375.0000 INCHES
 ZMAP SCALE 375.0000 INCHES
 SCALE 375.0000 INCHES

ALLRON
 SPDRPK 25.000
 3D-LAP .000
 ELEVON .000
 .000
 -10.000
 -15.000
 -20.000
 -30.000
 -40.000

CONFIGURATION DESCRIPTION
 BA119A B610 15125.712451915151
 BA119A B610 15125.712451915151
 BA119A B610 15125.712451915151
 BA119A B610 15125.712451915151
 BA119A B610 15125.712451915151

SET SYMBOL
 (A) 0004
 (B) 0007
 (C) 0010
 (D) 0013
 (E) 0016
 (F) 0019
 (G) 0022




LIFT/FOREBODY DRAG RATIO, L/DF

FIG 9 ELEVON EFFECTIVENESS - ELEVON E48 (NEGATIVE ELEVON DEFLECTIONS)



REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR



DATA SET SYMBOL CONFIGURATION DESCRIPTION

(AF8054)	□	0A119A	861C11F	2S1V1	24E51V1	SR1SX29
(AF8048)	○	0A119A	861C11F	2S1V1	24E51V1	SR1SX29
(AF8037)	◇	0A119A	861C11F	2S1V1	24E49V1	SR1SX29
(AF8042)	△	0A119A	861C11F	2S1V1	24E49V1	SR1SX29

REFERENCE INFORMATION

SREF	7690.0100	SO, FT
LREF	474.8100	INCHES
BREF	936.6600	INCHES
XREF	1076.4800	INCHES
YREF	0.0000	INCHES
ZREF	375.0000	INCHES
SCALE	.0100	SCALE




FIG 10 ELEVON EFFECTIVENESS - ELEVONS E49 AND E51 (POSITIVE ELEVON DEFLECTIONS)

(A)MACH = .26

PAGE 6:



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPOBRK	AIRLON	REFERENCE INFORMATION
(AF8054)	GA119A B61C11F27S1V124E51V19R15X29	20.000	.000	25.000	.000	SREF 2690.0100 SQ.FT.
(AF8048)	GA119A B61C11F27S1V124E51V19R15X29	15.000	.000	25.000	.000	LREF 474.8100 INCHES
(AF8037)	GA119A B61C11F27S1V124E49V19R15X29	10.000	.000	25.000	.000	BREF 936.6800 INCHES
(AF8042)	GA119A B61C11F27S1V124E49V19R15X29	.000	.000	25.000	.000	XMRP 1076.4800 INCHES
						YMRP .0000 INCHES
						ZMRP .0000 INCHES
						SCALE .0105




FIG 10 ELEVON EFFECTIVENESS - ELEVONS E49 AND E51 (POSITIVE ELEVON DEFLECTIONS)
 (A)MACH = .26 PAGE 62

DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPOBRK	A1LRON	REFERENCE INFORMATION
[AF8054]	CA119A 86 C1 F 2 S V124E51V19R15X29	20.000	.000	25.000	.000	SREF 390.0100 SQ.FT.
[AF8048]	CA119A 86 C1 F 2 S V124E51V19R15X29	15.000	.000	25.000	.000	LREF 474.8100 INCHES
[AF8037]	CA119A 86 C1 F 2 S V124E49V19R15X29	10.000	.000	25.000	.000	BREF 936.6800 INCHES
[AF8042]	CA119A 86 C1 F 2 S V124E49V19R15X29	10.000	.000	25.000	.000	XPROP .076 .0000 INCHES
						YPROP .0000 INCHES
						ZPROP 375.0000 INCHES
						SCALE .0400 SCALE




FIG 10 ELEVON EFFECTIVENESS - ELEVONS E49 AND E51 (POSITIVE ELEVON DEFLECTIONS)
 (A)MACH = .26



DATA SET SYMBOL
 (AF8054)
 (AF8048)
 (AF8037)
 (AF8042)

CONFIGURATION DESCRIPTION
 0A119A B61C11F127S1V124E51V19R15X29
 0A119A B61C11F127S1V124E51V19R15X29
 0A119A B61C11F127S1V124E49V19R15X29
 0A119A B61C11F127S1V124E49V19R15X29

ELEVON
 20.000
 15.000
 10.000

BOFLAP
 .000
 .000
 .000

SPOBRK
 25.000
 25.000
 25.000

AILERON
 .000
 .000
 .000

REFERENCE INFORMATION
 SREF 2690.0100 SO, FT.
 LREF 474.8100 INCHES
 BRREF 936.6800 INCHES
 XMRP 1076.4800 INCHES
 YMRP .0000 INCHES
 ZMRP 375.0000 INCHES
 SCALE .0405 SCALE

BASE AXIAL FORCE COEFFICIENT, CAB




FIG 10 ELEVON EFFECTIVENESS - ELEVONS E49 AND E51 (POSITIVE ELEVON DEFLECTIONS)

(A)MACH = .26



DATA SET SYMBOL CONFIGURATION DESCRIPTION

(AF8054)	0A119A	B61C1F12S1V124E51V1SR15X29
(AF8048)	0A119A	B61C1F12S1V124E51V1SR15X29
(AF8037)	0A119A	B61C1F12S1V124E49V1SR15X29
(AF8042)	0A119A	B61C1F12S1V124E49V1SR15X29

ELEVON

80FLAP	.000
SPOBRK	25.000
A1LRON	.000
ELEVON	20.000
REF	5.000
PCG	10.000

REFERENCE INFORMATION

SREF	2590.0100	SO.FT.
LREF	474.8100	INCHES
BREF	936.6800	INCHES
XPRD	1076.4800	INCHES
YPRD	.0000	INCHES
ZPRD	379.0000	INCHES
SCALE	.0409	SCALE




FIG 10 ELEVON EFFECTIVENESS - ELEVONS E49 AND E51 (POSITIVE ELEVON DEFLECTIONS)
 (A)MACH = .26

DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPOBRK	AILROD	REFERENCE INFORMATION
(AF8054)	CA119A B6:C11F:25:V:24E51V:SR:5X29	20.000	.000	25.000	.000	SREF 2690.0100 50.FT.
(AF8C48)	CA119A B6:C11F:25:V:24E51V:SR:5X29	15.000	.000	25.000	.000	LREF 474.8100 0.FT.
(AF8C37)	CA119A B6:C11F:25:V:24E49V:SR:5X29	0.000	.000	25.000	.000	BREF 936.6800 0.FT.
(AF8C42)	CA119A B6:C11F:25:V:24E49V:SR:5X29	0.000	.000	25.000	.000	XREF 1076.4800 0.FT.
						ZREF 375.0000 0.FT.
						SCALE .0405





FIG 10 ELEVON EFFECTIVENESS - ELEVONS E49 AND E51 (POSITIVE ELEVON DEFLECTIONS)
 (A)MACH = .26



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPDBRK	AILTRON	REFERENCE INFORMATION
{ AF8054 }	0A119A B61C1F1245 V124E51V19R15X29	20.000	.000	25.000	.000	SQ. FT. 2690.0100
{ AF8048 }	0A119A B61C1F1245 V124E51V19R15X29	15.000	.000	25.000	.000	SCALE 4.418100
{ AF8037 }	0A119A B61C1F1245 V124E49V19R15X29	10.000	.000	25.000	.000	SCALE 9.961800
{ AF8042 }	0A119A B61C1F1245 V124E49V19R15X29	.000	.000	25.000	.000	SCALE 1076.1800
						SCALE 375.0000



FOREBODY LIFT COEFFICIENT, CLF

FIG 10 ELEVON EFFECTIVENESS - ELEVONS E49 AND E51 (POSITIVE ELEVON DEFLECTIONS)
 (A) MACH = .26

DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPOBRK	AILERON	REFERENCE INFORMATION
(AF8054)	0A119A B61C1F1ZMS1V124E51V19R15X29	20.000	.000	25.000	.000	SREF 250.0100 SQ.FT
(AF8048)	0A119A B61C1F1ZMS1V124E51V19R15X29	15.000	.000	25.000	.000	LREF 474.8100 INCHES
(AF8037)	0A119A B61C1F1ZMS1V124E49V19R15X29	10.000	.000	25.000	.000	BREF 936.8600 INCHES
(AF8042)	0A119A B61C1F1ZMS1V124E49V19R15X29	.000	.000	25.000	.000	XMPP 376.4800 INCHES
						ZMPP 375.0000 INCHES
						SCALE .0105




FIG 10 ELEVON EFFECTIVENESS - ELEVONS E49 AND E51 (POSITIVE ELEVON REFLECTIONS)
 (A)MACH = .26 PAGE 68



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPDRK	AITLRN	REFERENCE INFORMATION
(AF8054)	CA119A B61C1F12451V124E51V19R15X29	20.000	.000	25.000	.000	SPEF .0690.0100 50.FT.
(AF8048)	CA119A B61C1F12451V124E51V19R15X29	15.000	.000	25.000	.000	LREF 474.8100 INCHES
(AF8037)	CA119A B61C1F12451V124E49V19R15X29	10.000	.000	25.000	.000	BREF 536.6800 INCHES
(AF8042)	CA119A B61C1F12451V124E45V19R15X29	.000	.000	25.000	.000	XMRP .0716.0800 INCHES
						YMRP .0000 INCHES
						ZMRP .0000 INCHES
						SCALE 375.0000 INCHES
						SCALE .0405





FIG 10 ELEVON EFFECTIVENESS - ELEVONS E49 AND E51 (POSITIVE ELEVON DEFLECTIONS)
 (A)MACH = .26 PAGE 69

DATA SET SYMBOL CONFIGURATION DESCRIPTION

(AF8054)	□	0A119A	B61C1	F1275	V124E5	V19R1	S129
(AF8048)	○	0A119A	B61C1	F1275	V124E5	V19R1	S129
(AF8037)	◇	0A119A	B61C1	F1275	V124E49V	V19R1	S129
(AF8042)	△	0A119A	B61C1	F1275	V124E49V	V19R1	S129

ELEVON BOFLAP SPOBRK AILRON REFERENCE INFORMATION SO. FT.

20.000	.000	.000	2690.0100
15.000	.000	.000	474.8100
10.000	.000	.000	938.6900
	.000	.000	1076.4800
	.000	.000	375.0000
			.0405



LONGITUDINAL CENTER OF PRESSURE LOCATION, XCP/L

FIG 10 ELEVON EFFECTIVENESS + ELEVONS E49 AND E51 (POSITIVE ELEVON DEFLECTIONS)
 (A)MACH = .26



DATA SET SYMBOL CONFIGURATION DESCRIPTION

(AF8042)	0A119A	361C11F12M51V124E49V19R15X23	ELEVON	BOFLAP	SPOBRK	A1LRON	REFERENCE INFORMATION
(AF8043)	0A119A	861C11F12M51V124E49V19R15X29	.000	.000	25.000	.000	SREF 2690.0100 SQ.FT
(AF8047)	0A119A	861C11F12M51V124E51V19R15X29	-10.000	.000	25.000	.000	LREF 474.8100 INCHES
(AF8046)	0A119A	861C11F12M51V124E51V19R15X29	-20.000	.000	25.000	.000	BREF 936.6900 INCHES
(AF8045)	0A119A	861C11F12M51V124E51V19R15X29	-30.000	.000	25.000	.000	XMRP 1076.4800 INCHES
			-40.000	.000	25.000	.000	ZMRP 375.0000 INCHES
							SCALE .0405




FIG 11 ELEVON EFFECTIVENESS - ELEVONS E49 AND E51 (NEGATIVE ELEVON DEFLECTIONS)
 (A)MACH = .26

DATA SET SYMBOL
 (AF8042)
 (AF8043)
 (AF8047)
 (AF8046)
 (AF8045)

CONFIGURATION DESCRIPTION
 0A119A 861C11F127S1V124E49V1SR15X29
 0A119A 861C11F127S1V124E49V1SR15X29
 0A119A 861C11F127S1V124E51V1SR15X29
 0A119A 861C11F127S1V124E51V1SR15X29
 0A119A 861C11F127S1V124E51V1SR15X29

ELEVON
 .000
 -10.000
 -20.000
 -30.000
 -40.000

BDF LAP
 .000
 .000
 .000
 .000
 .000

SPOBRK
 25.000
 25.000
 25.000
 25.000
 25.000

AILRON
 .000
 .000
 .000
 .000
 .000

REFERENCE INFORMATION
 SREF 2690.0100 SQ.FT.
 LREF 474.8100 INCHES
 BREF 936.6800 INCHES
 XMRP 1076.4800 INCHES
 YMRP .0000 INCHES
 ZMRP 375.0000 INCHES
 SCALE .0405 SCALE





FIG 11 ELEVON EFFECTIVENESS - ELEVONS E49 AND E51 (NEGATIVE ELEVON DEFLECTIONS)
 (A)MACH = .26
 PAGE 72



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPOBRK	AIRLON	REFERENCE INFORMATION
(AF8042)	GA119A B61C11F12MS1V124E49V19R15X29	.000	.000	25.000	.000	2690.0100 SQ.FT.
(AF8043)	GA119A B61C11F12MS1V124E49V19R15X29	-10.000	.000	25.000	.000	474.8100 INCHES
(AF8047)	GA119A B61C11F12MS1V124E51V19R15X29	-20.000	.000	23.000	.000	936.6800 INCHES
(AF8046)	GA119A B61C11F12MS1V124E51V19R15X29	-30.000	.000	25.000	.000	1076.4800 INCHES
(AF8045)	GA119A B61C11F12MS1V124E51V19R15X29	-40.000	.000	25.000	.000	.0000 INCHES
						375.0000 INCHES
						.0400 SCALE



FOREBODY AXIAL FORCE COEFFICIENT, CAF

FIG 11 ELEVON EFFECTIVENESS - ELEVONS E49 AND E51 (NEGATIVE ELEVON DEFLECTIONS)
 (A)MACH = .26 PAGE 73



DATA SET TYPE: \square \otimes

DATA SET TYPE	CONFIGURATION DESCRIPTION	ELEVON	EDFLAP	SPOBRK	AIRLON	REFERENCE INFORMATION
(AF8042)	GA119A BS1C11F12M51V124E49V1SR15X29	.000	.000	25.000	.000	SREF 2690.0100 SQ.FT
(AF8043)	GA119A BS1C11F12M51V124E49V1SR15X29	-10.000	.000	25.000	.000	LREF 474.8100 INCHES
(AF8047)	GA119A BS1C11F12M51V124E51V1SR15X29	-20.000	.000	25.000	.000	BREF 536.8600 INCHES
(AF8046)	GA119A BS1C11F12M51V124E51V1SR15X29	-30.000	.000	25.000	.000	XMRP 1076.4800 INCHES
(AF8045)	GA119A BS1C11F12M51V124E51V1SR15X29	-40.000	.000	25.000	.000	YMRP .0000 INCHES
						ZMRP 375.0000 INCHES
						SCALE .0405 SCALE




FIG 11 ELEVON EFFECTIVENESS - ELEVONS E49 AND E51 (NEGATIVE ELEVON DEFLECTIONS)
 (A)MACH = .26 PAGE 74



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPODBRK	AIRLON	REFERENCE INFORMATION
(AF8042)	0A119A B61C11F12MS1V124E49V19R15X29	.000	.000	25.000	.000	SREF 2690.0100 SQ.FT.
(AF8043)	0A119A B61C11F12MS1V124E49V19R15X29	-10.000	.000	25.000	.000	LREF 474.8100 INCHES
(AF8047)	0A119A B61C11F12MS1V124E51V19R15X29	-20.000	.000	25.000	.000	BREF 936.6800 INCHES
(AF8046)	0A119A B61C11F12MS1V124E51V19R15X29	-30.000	.000	25.000	.000	XPROP 1076.4800 INCHES
(AF8045)	0A119A B61C11F12MS1V124E51V19R15X29	-40.000	.000	25.000	.000	YPROP 375.0000 INCHES
						ZPROP 375.0000 INCHES
						SCALE .0100 SCALE




FIG 11 ELEVON EFFECTIVENESS - ELEVONS E49 AND E51 (NEGATIVE ELEVON DEFLECTIONS)
 (A)MACH = .26 PAGE 75




DATA SET SYMBOL
 (AF8042) □
 (AF8043) ⊗
 (AF8047) ⊗
 (AF8046) ⊗
 (AF8045) ⊗

CONFIGURATION DESCRIPTION
 CA119A 861C11F2MS1V24E49V19R15X29
 CA119A 861C11F2MS1V24E49V19R15X29
 CA119A 861C11F2MS1V24E51V19R15X29
 CA119A 861C11F2MS1V24E51V19R15X29
 CA119A 861C11F2MS1V24E51V19R15X29

ELEVON DEF LAR SPDRRA AILRON
 .000 .000 .000
 -10.000 .000 .000
 -20.000 .000 .000
 -30.000 .000 .000
 -40.000 .000 .000

REFERENCE INFORMATION
 SREF 2650.0100 SQ.FT.
 LREF 474.8100 INCHES
 BREF 936.6800 INCHES
 YPRP 10.61800 INCHES
 ZPRP 375.0000 INCHES
 SCALE .04CS



PITCHING MOMENT COEFFICIENT, CLM

FIG 11 ELEVON EFFECTIVENESS - ELEVONS 549 AND 551 (NEGATIVE ELEVON DEFLECTIONS)

(A)MACH = .26

DATA SET SYMBOL	CONF:IGURATION DESCRIPTION	ELEVON	BOFLAP	SPDBRK	AIRLON	REFERENCE INFORMATION
(AF8042)	CA119A B61C11F 275 V124E49V1915X29	.000	.000	25.000	.000	SREF 2690.0100 SQ.FT.
(AF8043)	CA119A B61C11F 275 V124E49V1915X29	-10.000	.000	25.000	.000	LREF 474.8100 INCHES
(AF8044)	CA119A B61C11F 275 V124E51V1915X29	-20.000	.000	25.000	.000	BREF 956.6800 INCHES
(AF8045)	CA119A B61C11F 275 V124E51V1915X29	-30.000	.000	25.000	.000	XREF 109.4800 INCHES
(AF8046)	CA119A B61C11F 275 V124E51V1915X29	-40.000	.000	25.000	.000	YREF 979.0000 INCHES
						ZREF .0000 INCHES
						SCALE .0005




FIG 11 ELEVON EFFECTIVENESS - ELEVONS E49 AND E51 (NEGATIVE ELEVON DEFLECTIONS)
 (A)MACH = .26 PAGE 77



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPDRK	AILERON	REFERENCE INFORMATION
{AF8042}	DA119A B61C1F12451V124E49V19R15X29	.000	.000	25.000	.000	SREF 2690.0100 SQ.FT.
{AF8043}	DA119A B61C1F12451V124E49V19R15X29	-10.000	.000	25.000	.000	LREF 474.8100 INCHES
{AF8047}	DA119A B61C1F12451V124E51V19R15X29	-20.000	.000	25.000	.000	BREF 936.6800 INCHES
{AF8046}	DA119A B61C1F12451V124E51V19R15X29	-30.000	.000	25.000	.000	XMRP 1076.4800 INCHES
{AF8045}	DA119A B61C1F12451V124E51V19R15X29	-40.000	.000	25.000	.000	YMRP 375.0000 INCHES
						ZMRP 1040.0000 INCHES
						SCALE 10.000




FIG 11 ELEVON EFFECTIVENESS - ELEVONS 548 AND 551 (NEGATIVE ELEVON DEFLECTIONS)
 (M)MACH = .26 FOREBODY DRAG COEFFICIENT, CDF



LIFT/FOREBODY DRAG RATIO, L/DF

DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPOBRK	ATLRON	REFERENCE INFORMATION
(A)8042)	86(C)1F125(V)24E49(V)9R(1)5123	.000	.000	25.000	.000	SCALE 2690.0100 SCALE
(A)8043)	86(C)1F125(V)24E49(V)9R(1)5123	-10.000	.000	25.000	.000	SCALE 44.8150 SCALE
(A)8044)	86(C)1F125(V)24E49(V)9R(1)5123	-20.000	.000	25.000	.000	SCALE 936.5600 SCALE
(A)8045)	86(C)1F125(V)24E49(V)9R(1)5123	-30.000	.000	25.000	.000	SCALE 16.1900 SCALE
(A)8046)	86(C)1F125(V)24E49(V)9R(1)5123	-40.000	.000	25.000	.000	SCALE 5.0000 SCALE




FIG 11 ELEVON EFFECTIVENESS - ELEVONS E49 AND E51 (NEGATIVE ELEVON DEFLECTIONS)
 (A)MACH = .26
 PAGE 79



LONGITUDINAL CENTER OF PRESSURE LOCATION, XCP/L

DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPOBRK	AIRLON	REFERENCE INFORMATION
(AF8042)	GA11SA 86 C1 F2MS V124E19V19815X28	.000	.000	25.000	.000	SREF 2690.0100 SCALE
(AF8043)	GA11SA 86 C1 F2MS V124E19V19815X20	.000	.000	25.000	.000	LREF 474.8100 SCALE
(AF8044)	GA11SA 86 C1 F2MS V124E19V19815X29	.000	.000	25.000	.000	BREF 936.6600 SCALE
(AF8045)	GA11SA 86 C1 F2MS V124E19V19815X29	.000	.000	25.000	.000	XREF 1076.4800 SCALE
		.44	.000	25.000	.000	YREF 375.0000 SCALE
		.44	.000	25.000	.000	SCALE 375.0000 SCALE




FIG 11 ELEVON EFFECTIVENESS - ELEVONS EAST AND WEST (NEGATIVE ELEVON DEFLECTIONS)
 (A)MACH = .26 PAGE 80




DATA SET SYMBOL CONFIGURATION DESCRIPTION REFERENCE INFORMATION

(AF8001)	CA119A	BSICIF12P5IV124E48V1SR15X29	SREF	2690.0100	SQ.FT.
(AF8004)	CA119A	BSICIF12P5IV124E47V1SR15X29	LREF	74.8100	INCHES
(AF8004)	CA119A	BSICIF12P5IV124E48V1SR15X29	BREF	936.6800	INCHES
(AF8036)	CA119A	BSICIF12P5IV124E48V1SR15X29	XMRP	1076.4800	INCHES
(AF8034)	CA119A	BSICIF12P5IV124E47V1SR15X29	ZMRP	375.0000	INCHES
(AF8036)	CA119A	BSICIF12P5IV124E48V1SR15X29	SCALE	.0405	SCALE

ELEVON BOFLAP SPOBRK AIRLON

.000	.000	.000	.000
.000	.000	.000	.000
.000	.000	.000	.000
.000	.000	.000	.000
.000	.000	.000	.000
.000	.000	.000	.000
.000	.000	.000	.000
.000	.000	.000	.000
.000	.000	.000	.000
.000	.000	.000	.000




FOREBODY LIFT COEFFICIENT, CLF

FIG 12 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = 0 AND 5 DEG
 (A)MACH = .26 PAGE 81




DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BD/FLAP	SPDBRK	AILERON	REFERENCE INFORMATION
(AF8001)	0A119A F61C11F12751V124E16V19R15X29	.000	.000	25.000	.000	2690.0130 SO.FT.
(AF8002)	0A119A B61C11F12751V124E17V19R15X29	.000	.000	25.000	.000	474.8130 INCHES
(AF8003)	0A119A B61C11F12751V124E18V19R15X29	.000	.000	25.000	.000	956.6800 INCHES
(AF8004)	0A119A B61C11F12751V124E16V19R15X29	5.000	.000	25.000	.000	1076.4800 INCHES
(AF8005)	0A119A B61C11F12751V124E17V19R15X29	5.000	.000	25.000	.000	.0000 INCHES
(AF8006)	0A119A B61C11F12751V124E18V19R15X29	5.000	.000	25.000	.000	375.0000 INCHES
						.0405 SCALE



NORMAL FORCE COEFFICIENT, CN

FIG 12 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = 0 AND 5 DEG
 (A)MACH = .26 PAGE 82



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPOBRK	AILTRON	REFERENCE INFORMATION	SO.FT.
(AF8001)	0A119A 861C11F12M51V124E48V19R15X29	.000	.000	25.000	.000	SREF 2690.0100	INCHES
(AF8001)	0A119A 861C11F12M51V124E47V19R15X29	.000	.000	25.000	.000	LREF 474.8100	INCHES
(AF8004)	0A119A 861C11F12M51V124E48V19R15X29	.000	.000	25.000	.000	BREF 936.5900	INCHES
(AF8036)	0A119A 861C11F12M51V124E48V19R15X29	5.000	.000	25.000	.000	XMRP 1076.4800	INCHES
(AF8034)	0A119A 861C11F12M51V124E47V19R15X29	5.000	.000	25.000	.000	YMRP .0000	INCHES
(AF8035)	0A119A 861C11F12M51V124E48V19R15X29	5.000	.000	25.000	.000	ZMRP 375.0000	INCHES
						SCALE	SCALE




FIG 12 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = 0 AND 5 DEG
 (A)MACH = .26 PAGE 83



DATA SET SYMBOL CONFIGURATION DESCRIPTION

(AF8001) 0A119A 861C11F12751V124E16V19R15X29

(AF8002) 0A119A 861C11F12751V124E17V19R15X29

(AF8003) 0A119A 861C11F12751V124E18V19R15X29

(AF8004) 0A119A 861C11F12751V124E19V19R15X29

(AF8005) 0A119A 861C11F12751V124E20V19R15X29

(AF8006) 0A119A 861C11F12751V124E21V19R15X29

(AF8007) 0A119A 861C11F12751V124E22V19R15X29

(AF8008) 0A119A 861C11F12751V124E23V19R15X29

(AF8009) 0A119A 861C11F12751V124E24V19R15X29

(AF8010) 0A119A 861C11F12751V124E25V19R15X29

ELEVON 8DFLAP SPDRK AILRON REFERENCE INFORMATION

.000 .000 .000 .000 SREF 2650.0100 50.FT.

.000 .000 .000 .000 LREF 474.8100 INCHES


.000 .000 .000 .000 BREF 936.6800 INCHES

.000 .000 .000 .000 XMRP 1076.2800 INCHES

.000 .000 .000 .000 YMRP 375.0000 INCHES

.000 .000 .000 .000 ZMRP 375.0000 INCHES

.000 .000 .000 .000 SCALE .0100 SCALE



BASE AXIAL FORCE COEFFICIENT, CAB

FIG 12 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = 0 AND 5 DEG

(AJMACH = .26

PAGE 84



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPODBK	AILERON	REFERENCE INFORMATION
(AF8001)	DA119A B61C11F127S1V124E46V19R15X29	.000	.000	25.000	.000	SREF 2690.0100 SQ.FT
(AF8004)	DA119A B61C11F127S1V124E47V19R15X29	.000	.000	25.000	.000	LREF 474.8100 INCHES
(AF8036)	DA119A B61C11F127S1V124E48V19R15X29	.000	.000	25.000	.000	BREF 936.6800 INCHES
(AF8034)	DA119A B61C11F127S1V124E47V19R15X29	5.000	.000	25.000	.000	XMRP 1076.4800 INCHES
(AF8035)	DA119A B61C11F127S1V124E48V19R15X29	5.000	.000	25.000	.000	YMRP .0000 INCHES
						ZMRP 375.0000 INCHES
						SCALE .0105 SCALE




FIG 12 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = 0 AND 5 DEG
 (A)MACH = .26 PAGE 85



DATA SET SYMBOL CONFIGURATION DESCRIPTION

(AF8001)	0A119A	B61C1F127S1V124E16V1SR15X29
(AF8001)	0A119A	B61C1F127S1V124E17V1SR15X29
(AF8001)	0A119A	B61C1F127S1V124E18V1SR15X29
(AF8001)	0A119A	B61C1F127S1V124E19V1SR15X29
(AF8001)	0A119A	B61C1F127S1V124E20V1SR15X29
(AF8001)	0A119A	B61C1F127S1V124E21V1SR15X29
(AF8001)	0A119A	B61C1F127S1V124E22V1SR15X29
(AF8001)	0A119A	B61C1F127S1V124E23V1SR15X29
(AF8001)	0A119A	B61C1F127S1V124E24V1SR15X29
(AF8001)	0A119A	B61C1F127S1V124E25V1SR15X29
(AF8001)	0A119A	B61C1F127S1V124E26V1SR15X29
(AF8001)	0A119A	B61C1F127S1V124E27V1SR15X29
(AF8001)	0A119A	B61C1F127S1V124E28V1SR15X29
(AF8001)	0A119A	B61C1F127S1V124E29V1SR15X29
(AF8001)	0A119A	B61C1F127S1V124E30V1SR15X29
(AF8001)	0A119A	B61C1F127S1V124E31V1SR15X29
(AF8001)	0A119A	B61C1F127S1V124E32V1SR15X29
(AF8001)	0A119A	B61C1F127S1V124E33V1SR15X29
(AF8001)	0A119A	B61C1F127S1V124E34V1SR15X29
(AF8001)	0A119A	B61C1F127S1V124E35V1SR15X29
(AF8001)	0A119A	B61C1F127S1V124E36V1SR15X29
(AF8001)	0A119A	B61C1F127S1V124E37V1SR15X29
(AF8001)	0A119A	B61C1F127S1V124E38V1SR15X29
(AF8001)	0A119A	B61C1F127S1V124E39V1SR15X29
(AF8001)	0A119A	B61C1F127S1V124E40V1SR15X29
(AF8001)	0A119A	B61C1F127S1V124E41V1SR15X29
(AF8001)	0A119A	B61C1F127S1V124E42V1SR15X29
(AF8001)	0A119A	B61C1F127S1V124E43V1SR15X29
(AF8001)	0A119A	B61C1F127S1V124E44V1SR15X29
(AF8001)	0A119A	B61C1F127S1V124E45V1SR15X29
(AF8001)	0A119A	B61C1F127S1V124E46V1SR15X29
(AF8001)	0A119A	B61C1F127S1V124E47V1SR15X29
(AF8001)	0A119A	B61C1F127S1V124E48V1SR15X29
(AF8001)	0A119A	B61C1F127S1V124E49V1SR15X29
(AF8001)	0A119A	B61C1F127S1V124E50V1SR15X29

ELEVON 80FLAP SPDBRK AILRON REFERENCE INFORMATION

.000	.000	.000	SREF	2690.0100	90.FT
.000	.000	.000	LREF	474.8100	INCHES
.000	.000	.000	BREF	536.6800	INCHES
.000	.000	.000	XMRP	1076.4800	INCHES
.000	.000	.000	YMRP	.0000	INCHES
.000	.000	.000	ZMRP	375.0000	INCHES
.000	.000	.000	SCALE	.0405	SCALE




FIG 12 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = 0 AND 5 DEG
 (A)MACH = .26 PAGE 86



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BDFLAP	SPOBRK	A1LRON	REFERENCE INFORMATION
(AF8001)	GA119A B61C11F 2N61V124E46V19R15X29	.000	.000	29.000	.000	SREF 2690.0100 SQ.FT.
(AF8001)	GA119A B61C11F 2N61V124E47V19R15X29	.000	.000	29.000	.000	LREF 474.8100 INCHES
(AF8004)	GA119A B61C11F 2N61V124E48V19R15X29	.000	.000	29.000	.000	BREF 936.6800 INCHES
(AF8036)	GA119A B61C11F 2N61V124E46V19R15X29	5.000	.000	29.000	.000	XMRP 1076.4800 INCHES
(AF8034)	GA119A B61C11F 2N61V124E47V19R15X29	5.000	.000	29.000	.000	YMRP .0000 INCHES
(AF8035)	GA119A B61C11F 2N61V124E48V19R15X29	5.000	.000	29.000	.000	ZMRP 375.0000 INCHES
						SCALE .0405




FIG 12 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = 0 AND 5 DEG
 (A)MACH = .26 PAGE 87



DATA SET SYMBL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPDRBK	AILRON	REFERENCE INFORMATION
(AF8001)	0A119A B61C1F12751V124E16V19R15X29	.000	.000	25.000	.000	SREF 2690.0100 SQ.FT.
(AF8001)	0A119A B61C1F12751V124E17V19R15X29	.000	.000	25.000	.000	LREF 474.9100 INCHES
(AF8004)	0A119A B61C1F12751V124E16V19R15X29	.000	.000	25.000	.000	BREF 938.6900 INCHES
(AF8036)	0A119A B61C1F12751V124E16V19R15X29	5.000	.000	25.000	.000	XMPR 1076.0000 INCHES
(AF8034)	0A119A B61C1F12751V124E17V19R15X29	5.000	.000	25.000	.000	ZMPR 375.0000 INCHES
(AF8035)	0A119A B61C1F12751V124E16V19R15X29	5.000	.000	25.000	.000	SCALE .0405 SCALE





FIG 12 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = 0 AND 5 DEG
 (A)MACH = .26 PAGE 88



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPOBRK	AILERON	REFERENCE INFORMATION
(AF8001)	0A119A 861C1F12M51V124E46V1SR15X29	.000	.000	25.000	.000	SREF 2690.0100 SQ.FT.
(AF8041)	0A119A 861C1F12M51V124E47V1SR15X29	.000	.000	25.000	.000	LREF 474.8100 INCHES
(AF8004)	0A119A 861C1F12M51V124E48V1SR15X29	.000	.000	25.000	.000	BREF 936.6800 INCHES
(AF8036)	0A119A 861C1F12M51V124E46V1SR15X29	5.000	.000	25.000	.000	XPRP 1076.4800 INCHES
(AF8034)	0A119A 861C1F12M51V124E47V1SR15X29	5.000	.000	25.000	.000	YPRP .0000 INCHES
(AF8035)	0A119A 861C1F12M51V124E48V1SR15X29	5.000	.000	25.000	.000	ZPRP .0405 INCHES
						SCALE



LIFT/FOREBODY DRAG RATIO, L/DF


FIG 12 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = 0 AND 5 DEG

(A)MACH = .26

PAGE 89



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPOBRK	AIRLON	REFERENCE INFORMATION
(AF8001)	DA119A B61C1F124S1V124E46V1SR15X29	.000	.000	25.000	.000	SREF 2690.0100 50.FT.
(AF8004)	DA119A B61C1F124S1V124E47V1SR15X29	.000	.000	25.000	.000	LREF 474.0100 INCHES
(AF8006)	DA119A B61C1F124S1V124E48V1SR15X29	.000	.000	25.000	.000	BREF 936.6800 INCHES
(AF8034)	DA119A B61C1F124S1V124E46V1SR15X29	5.000	.000	25.000	.000	XMRP 1076.4800 INCHES
(AF8035)	DA119A B61C1F124S1V124E48V1SR15X29	5.000	.000	25.000	.000	ZMRP 375.0000 INCHES
						SCALE .0405 SCALE



LONGITUDINAL CENTER OF PRESSURE LOCATION, XCP/L

FIG 12 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = 0 AND 5 DEG
 CAJMAC H = .26 PAGE 90



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPDBRK	A1LRON	REFERENCE INFORMATION
(AF8021)	DA119A B61C11F12H51V124E16V19R15X29	10.000	.000	25.000	.000	SREF 2690.0100 SQ.FT.
(AF8025)	DA119A B61C11F12H51V124E17V19R15X29	10.000	.000	25.000	.000	LREF 474.8100 INCHES
(AF8024)	DA119A B61C11F12H51V124E18V19R15X29	10.000	.000	25.000	.000	BREF 936.6800 INCHES
(AF8061)	DA119A B61C11F12H51V124E16V19R15X29	15.000	.000	25.000	.000	XPRP 1076.4800 INCHES
(AF8049)	DA119A B61C11F12H51V124E17V19R15X29	15.000	.000	25.000	.000	YPRP .0000 INCHES
(AF8050)	DA119A B61C11F12H51V124E18V19R15X29	15.000	.000	25.000	.000	ZPRP 375.0000 INCHES
						SCALE .0405 SCALE





FIG 13 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = 10 AND 15 DEG

(A)MACH = .26

PAGE 91



100-2517 (REV. 1-15-52)
 100-2517 (REV. 1-15-52)
 100-2517 (REV. 1-15-52)
 100-2517 (REV. 1-15-52)
 100-2517 (REV. 1-15-52)



NORMAL FORCE COEFFICIENT, CN

FIG 13 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = 10 AND 15 DEG
 (A) MACH = .25



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPOBRK	AII, RON	REFERENCE INFORMATION
(AF8021)	OA119A B61C1IF12MSIV124E46V1SR15X29	10.000	.000	25.000	.000	SREF 2690.0100 SQ.FT.
(AF8023)	OA119A B61C1IF12MSIV124E47V1SR15X29	10.000	.000	25.000	.000	LREF 474.8100 INCHES
(AF8024)	OA119A B61C1IF12MSIV124E48V1SR15X29	10.000	.000	25.000	.000	BREF 936.6800 INCHES
(AF8061)	OA119A B61C1IF12MSIV124E46V1SR15X29	15.000	.000	25.000	.000	XMRP 1076.4800 INCHES
(AF8049)	OA119A B61C1IF12MSIV124E47V1SR15X29	15.000	.000	25.000	.000	YMRP 375.0000 INCHES
(AF8050)	OA119A B61C1IF12MSIV124E48V1SR15X29	15.000	.000	25.000	.000	ZMRP 375.0000 INCHES
						SCALE .0405




FIG 13 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = 10 AND 15 DEG

CAJMACB = .26

PAGE 33



DATA SET SYMBOLS: (AF802), (AF803), (AF804), (AF805), (AF806), (AF807), (AF808), (AF809), (AF810)

DATA SET SYMBOLS	CONFIGURATION DESCRIPTION	ELEVON	SPAZRM	BOFLAP	ELEVON	REF ELEVON	SCALE
0A119A	B6(C)1F 2-051V124E46 9R15X29	10.000	25.000	0.00	1.000	0.10	0.10
0A119A	B6(C)1F 2-051V124E47 9R15X29	10.000	25.000	0.00	1.000	0.10	0.10
0A119A	B6(C)1F 2-051V124E48 9R15X29	10.000	25.000	0.00	1.000	0.10	0.10
0A119A	B6(C)1F 2-051V124E49 9R15X29	10.000	25.000	0.00	1.000	0.10	0.10
0A119A	B6(C)1F 2-051V124E50 9R15X29	10.000	25.000	0.00	1.000	0.10	0.10
0A119A	B6(C)1F 2-051V124E51 9R15X29	10.000	25.000	0.00	1.000	0.10	0.10
0A119A	B6(C)1F 2-051V124E52 9R15X29	10.000	25.000	0.00	1.000	0.10	0.10
0A119A	B6(C)1F 2-051V124E53 9R15X29	10.000	25.000	0.00	1.000	0.10	0.10
0A119A	B6(C)1F 2-051V124E54 9R15X29	10.000	25.000	0.00	1.000	0.10	0.10
0A119A	B6(C)1F 2-051V124E55 9R15X29	10.000	25.000	0.00	1.000	0.10	0.10
0A119A	B6(C)1F 2-051V124E56 9R15X29	10.000	25.000	0.00	1.000	0.10	0.10
0A119A	B6(C)1F 2-051V124E57 9R15X29	10.000	25.000	0.00	1.000	0.10	0.10
0A119A	B6(C)1F 2-051V124E58 9R15X29	10.000	25.000	0.00	1.000	0.10	0.10
0A119A	B6(C)1F 2-051V124E59 9R15X29	10.000	25.000	0.00	1.000	0.10	0.10
0A119A	B6(C)1F 2-051V124E60 9R15X29	10.000	25.000	0.00	1.000	0.10	0.10

BASE AXIAL FORCE COEFFICIENT, CAB





FIG 13 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS. ELEVON = 10 AND 15 DEG
 (AJMACH = .26) PAGE 94



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BD FLAP	SPOBRK	AJLRON	REFERENCE INFORMATION
(AF8021)	CA119A B61C11F 2MS1V124E46V1SR15X29	10.000	.000	25.000	.000	SREF 2690.0100 SQ.FT.
(AF8023)	CA119A B61C11F 2MS1V124E47V1SR15X29	10.000	.000	25.000	.000	LREF 474.8100 INCHES
(AF8024)	CA119A B61C11F 2MS1V124E46V1SR15X29	10.000	.000	25.000	.000	BREF 936.6800 INCHES
(AF8061)	CA119A B61C11F 2MS1V124E47V1SR15X29	15.000	.000	25.000	.000	XMRP 1076.3000 INCHES
(AF8049)	CA119A B61C11F 2MS1V124E47V1SR15X29	15.000	.000	25.000	.000	YMRP 375.3000 INCHES
(AF8050)	CA119A B61C11F 2MS1V124E48V1SR15X29	15.000	.000	25.000	.000	ZMRP 375.3000 INCHES
						SCALE 0405




FOREBODY DRAG COEFFICIENT, CDF

FIG 13 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = 10 AND 15 DEG



DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AF8021) O 0119A 861C11F 2MS V124E46V SR15X29
 (AF8025) X 0119A 861C11F 2MS V124E47V SR15X29
 (AF8024) X 0119A 861C11F 2MS V124E48V SR15X29
 (AF8061) X 0119A 861C11F 2MS V124E46V SR15X29
 (AF8049) X 0119A 861C11F 2MS V124E47V SR15X29
 (AF8050) X 0119A 861C11F 2MS V124E48V SR15X29

ELEVON 30FLAP SPOON AIRMAN REFERENCE +GUMMID
 10.000 000 25.000 000 2690.0100 50.000
 10.000 000 25.000 000 474.8100 10.000
 10.000 000 25.000 000 936.6800 10.000
 15.000 000 25.000 000 1076.4500 10.000
 15.000 000 25.000 000 375.0000 10.000
 15.000 000 25.000 000 SCALE



PITCHING MOMENT COEFFICIENT, CLM

FIG 13 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = 10 AND 15 DEG
 (A)MACH = .26 PAGE 96



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPOBRK	AILTRON	REFERENCE INFORMATION
(AF8021)	DA119A B61C1F12H5V124E46V1SR1SX29	10.000	.000	25.000	.000	SREF 2690.0100 SQ.FT.
(AF8025)	DA119A B61C1F12H5V124E47V1SR1SX29	10.000	.000	25.000	.000	LREF 474.8100 INCHES
(AF8024)	DA119A B61C1F12H5V124E48V1SR1SX29	10.000	.000	25.000	.000	BREF 936.8800 INCHES
(AF8061)	DA119A B61C1F12H5V124E46V1SR1SX29	5.000	.000	25.000	.000	XMRP 1078.4800 INCHES
(AF8049)	DA119A B61C1F12H5V124E47V1SR1SX29	5.000	.000	25.000	.000	YMRP .0000 INCHES
(AF8050)	DA119A B61C1F12H5V124E48V1SR1SX29	5.000	.000	25.000	.000	ZMRP 375.0000 INCHES
						SCALE 0.0105





FIG 13 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = 10 AND 15 DEG



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPDBRK	AIRLON	REFERENCE INFORMATION
(AF8021)	CA119A B61C1 F12M5 V124E46V19R15X29	10.000	.000	25.000	.000	SREF 2690.0100 SO FT.
(AF8025)	CA119A B61C1 F12M5 V124E47V19R15X29	10.000	.000	25.000	.000	LREF 474.8100 I-C-F-S
(AF8024)	CA119A B61C1 F12M5 V124E48V19R15X29	10.000	.000	25.000	.000	BREF 936.6800 I-C-F-S
(AF8061)	CA119A B61C1 F12M5 V124E46V19R15X29	15.000	.000	25.000	.000	XPRP 1076.1900 I-C-F-S
(AF8049)	CA119A B61C1 F12M5 V124E47V19R15X29	15.000	.000	25.000	.000	YPRP 375.3000 I-C-F-S
(AF8050)	CA119A B61C1 F12M5 V124E48V19R15X29	15.000	.000	25.000	.000	ZPRP 375.3000 I-C-F-S
						SCALE .0405 SCALE




FIG 13 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = 10 AND 15 DEG
 (A)MACH = .26



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPOBRK	AILRON	REFERENCE INFORMATION
{ AF 8021 }	DA119A B61C1F12H5 124E46V19R15X29	10.000	.000	25.000	.000	SREF 2690.0100 SO.FT.
{ AF 8023 }	DA119A B61C1F12H5 124E47V19R15X29	10.000	.000	25.000	.000	LREF 474.8100 INCHES
{ AF 8024 }	DA119A B61C1F12H5 124E48V19R15X29	10.000	.000	25.000	.000	BREF 936.3800 INCHES
{ AF 8061 }	DA119A B61C1F12H5 124E46V19R15X29	15.000	.000	25.000	.000	XMRP 1076.4800 INCHES
{ AF 8049 }	DA119A B61C1F12H5 124E47V19R15X29	15.000	.000	25.000	.000	ZMRP 375.3405 INCHES
{ AF 8050 }	DA119A B61C1F12H5 124E48V19R15X29	15.000	.000	25.000	.000	SCALE




FIG 13 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = 10 AND 15 DEG

(A)MACH = .26

PAGE 99



DATA SET SYMBOL CONFIGURATION DESCRIPTION

{ AF8021 } 0A119A 861C11F12451V124E16V1915X29

{ AF8025 } 0A119A 861C11F12451V124E17V1915X29

{ AF8024 } 0A119A 861C11F12451V124E18V1915X29

{ AF8061 } 0A119A 861C11F12451V124E16V1915X29

{ AF8049 } 0A119A 861C11F12451V124E17V1915X29

{ AF8050 } 0A119A 861C11F12451V124E18V1915X29

ELEVON BDFLAP SPOBRV AILPPN REFERENCE INFORMATION

10.000 .000 25.000 .000 SREF 2690.0100 50.FT.

10.000 .000 25.000 .000 LREF 474.8100 INCHES


10.000 .000 25.000 .000 BREF 936.5800 INCHES

15.000 .000 25.000 .000 XMRP 1076.180 INCHES

15.000 .000 25.000 .000 YMRP .0000 INCHES

15.000 .000 25.000 .000 ZMRP 375.0000 INCHES

SCALE .0405 SCALE



LONGITUDINAL CENTER OF PRESSURE LOCATION, XCP/L

FIG 13 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS. ELEVON = 10 AND 15 DEG
CAJMACH = .26 PAGE 100



DATA SET SYMBOL CONFIGURATION DESCRIPTION

(AFB59)	GA119A	86	C	I	F	2	5	V	1	24	E	4	6	V	1	9	R	1	5	X	2	9
(AFB051)	GA119A	86	C	I	F	2	5	V	1	24	E	4	7	V	1	9	R	1	5	X	2	9
(AFB052)	GA119A	86	C	I	F	2	5	V	1	24	E	4	8	V	1	9	R	1	5	X	2	9

ELEVON 20.000
 ELEVON 20.000
 ELEVON 20.000

BDLAP .000
 BDLAP .000
 BDLAP .000

SPOBRK 25.000
 SPOBRK 25.000
 SPOBRK 25.000

A1LRON .000
 A1LRON .000
 A1LRON .000

REFERENCE INFORMATION

SREF	2690.0100	SO.FT
LREF	474.8100	INCHES
BREF	936.6800	INCHES
XMRP	1076.4800	INCHES
YMRP	.0000	INCHES
ZMRP	375.0000	INCHES
SCALE	.0405	SCALE




FIG 14 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = 20 DEG

(A)MACH = .26



DATA SET SYMBOL
 { AF8059 }
 { AF8051 }
 { AF8052 }

CONFIGURATION DESCRIPTION

CA119A BS1C1F12M5V124E46V1SR15X29
 CA119A BS1C1F12M5V124E47V1SR15X29
 CA119A BS1C1F12M5V124E48V1SR15X29

ELEVON 20.000
 20.000
 20.000

8DFLAP .000
 .000
 .000

SPOBRK .000
 25.000
 25.000

AILRON .000
 .000
 .000

REFERENCE INFORMATION

SREF 2690.0100 SQ. FT.
 LREF 474.8100 INCHES
 BREF 936.5800 INCHES
 XMRP 1076.1800 INCHES
 YMRP .0000 INCHES
 ZMRP 375.0000 INCHES
 SCALE .0405 SCALE





FIG 14 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = 20 DFG

(A)MACH = .26

PAGE 102



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPDRK	A TLRN	REFERENCE INFORMATION
{ AF8050 }	0A119A B61C1F12751V124E46V19R15X29	20.000	.20	25.000	.000	SREF 2690.0100 SO.FT.
{ AF8051 }	0A119A B61C1F12751V124E47V19R15X29	20.000	.000	25.000	.000	LREF 474.8100 INCHES
{ AF8052 }	0A119A B61C1F12751V124E46V19R15X29	20.000	.000	25.000	.000	BREF 956.6800 INCHES
						XMRP 1076.4800 INCHES
						YMRP .0000 INCHES
						ZMRP 375.0000 INCHES
						SCALE .0405



FOREBODY AXIAL FORCE COEFFICIENT, CAF

FIG 14 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = 20 DEG



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BD FLAP	SPD BRK	AIRLON	REFERENCE INFORMATION
{ AF 6050 }	DA119A BS1C1F12V51V124E46V18R15X29	20.000	.000	25.000	.000	SREF 2690.0100 90.FT.
{ AF 6051 }	DA119A BS1C1F12V51V124E47V19R15X29	20.000	.000	25.000	.000	LREF 474.8100 INCHES
{ AF 6052 }	DA119A BS1C1F12V51V124E48V19R15X29	20.000	.000	25.000	.000	XREF 936.6800 INCHES
						YMRP 1076.4800 INCHES
						ZMRP .0000 INCHES
						SCALE .0405 SCALE

BASE AXIAL FORCE COEFFICIENT, CAB




FIG 14 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = 20 DEG

(A)MACH = .26 PAGE 104



DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AF8059) O 0A119V B61C1F12M51V124E46V19R15X29
 (AF8051) O 0A119A B61C1F12M51V124E47V19R15X29
 (AF8052) O 0A119A B61C1F12M51V124E48V19R15X29

ELEVON 20.000
 BOFLAP .000
 SPOBRK 25.000
 AIRLON .000

REFERENCE INFORMATION
 SREF 2690.0100 SO.FT
 LREF 474.8100 INCHES
 BRPF 936.6800 INCHES
 XMRP 1076.1800 INCHES
 YMRP .0000 INCHES
 ZMRP 375.0000 INCHES
 SCALE .0405




FIG 14 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = 20 DEG

(A)MACH = .26



DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AF8059) 0A119A BS1C1F1ZP51V12AF46V1SR15X29
 (AF8051) 0A119A BS1C1F1ZP51V12AF47V1SR15X29
 (AF8052) 0A119A BS1C1F1ZP51V12AF46V1SR15X29

ELEVON SPOBRK AIRLON
 20.000 .000 .000
 20.000 25.000 .000
 20.000 25.000 .000

REFERENCE INFORMATION
 SREF 2690.0100 50.FT.
 LREF 474.8100 INCHES
 BRFF 936.6800 INCHES
 XMRP 1076.1800 INCHES
 YMRP .0000 INCHES
 ZMRP 375.0000 INCHES
 SCALE .0A05 SCALE

PITCHING MOMENT COEFFICIENT, CLM




FIG 14 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = 20 DEG

(AJMACH = .26) PAGE 106



DATA SET SYMBOL: (AF0059) (AF0051) (AF0052)

CONFIGURATION DESCRIPTION:
 0A11SA B61C1F12V51V124E46V19R15X29
 0A11SA B61C1F12V51V124E47V19R15X29
 0A11SA B61C1F12V51V124E46V19R15X29

ELEVON: 20.000 20.000 20.000
 FLAP: .000 .000 .000
 SPOBRK: 25.000 25.000 25.000
 AIRLON: .000 .000 .000

REFERENCE INFORMATION:
 SREF: 2690.0100 SQ.FT.
 LREF: 474.8100 INCHES
 BREF: 936.6800 INCHES
 XMRP: 1076.4800 INCHES
 YMRP: .0000 INCHES
 ZMRP: 375.0000 INCHES
 SCALE: .0405




FIG 14 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = 20 DEG

(A)MACH = .26

DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AF8059) 0A111SA 861C11F12W51V124E46V19R15X29
 (AF8051) 0A111SA 861C11F12W51V124E47V19R15X29
 (AF8052) 0A111SA 861C11F12W51V124E48V19R15X29

ELEVON 8DFLAP SPOBRK AILRON REFERENCE INFORMATION
 20.000 .000 25.000 SREF 2650.0100 50.FT.
 20.000 .000 25.000 LREF 474.8100 INCHES
 20.000 .000 25.000 XMRP 936.6800 INCHES
 YMRP 1076.4800 INCHES
 ZMRP 375.0000 INCHES
 SCALE .0405 SCALE





FIG 14 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = 20 DEG
 (A)MACH = .26

DATA SET SYMBOL: 31
 REFERENCE INFORMATION: 31
 REFERENCE INFORMATION: 31
 REFERENCE INFORMATION: 31

ELEVATION: 5000
 HORIZONTAL: 5000
 ALTIMETER: 5000

REFERENCE INFORMATION: 31
 REFERENCE INFORMATION: 31
 REFERENCE INFORMATION: 31



ANGLE OF ATTACK, ALPHA, DEGREES
 20 30 40
 50

REFERENCE INFORMATION: 31
 REFERENCE INFORMATION: 31
 REFERENCE INFORMATION: 31

DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AF8059) 0119A 861C11F12V51V124E46V18R15X29
 (AF8051) 0119A 861C11F12V51V124E47V18R15X29
 (AF8052) 0119A 861C11F12V51V124E48V18R15X29


ELEVON 20.000
 20.000
 20.000

BOFLAP .000
 .000
 .000

SPDRBK 25.000
 25.000
 25.000

AILRON .000
 .000
 .000

REFERENCE INFORMATION
 SREF 2690.0100 SQ.FT.
 LREF 474.8100 INCHES
 BRFP 956.8600 INCHES
 XMRP 1076.4800 INCHES
 ZMRP .0000 INCHES
 SCALE 375.0000 INCHES
 .0405 SCALE



LONGITUDINAL CENTER OF PRESSURE LOCATION, XCP/L

FIG 14 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = 20 DLG

(A)MACH = .26

PAGE 110



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPOBRK	A1LRON	REFERENCE INFORMATION	SOFT
(AF8030)	0A119A 8S111F12451124E45V19R13K29	-10.000	.000	25.000	.000	SREF 269C 3100	1000
(AF8031)	0A119A 8S111F12451124E45V19R15A29	-10.000	.000	25.000	.000	LREF 474 3100	1000
(AF8032)	0A119A 8S111F12451124E45V19R15A29	-10.000	.000	5.000	.000	BREF 93 3100	1000
(AF8033)	0A119A 8S111F12451124E45V19R15A29	-10.000	.000	25.000	.000	VMRO 1075 3100	1000
(AF8034)	0A119A 8S111F12451124E45V19R15A29	-10.000	.000	25.000	.000	VMRO 700 3100	1000
(AF8035)	0A119A 8S111F12451124E45V19R15A29	-10.000	.000	25.000	.000	VMRO 370 3100	1000
(AF8036)	0A119A 8S111F12451124E45V19R15A29	-15.000	.000	25.000	.000	SCALE	SCALE




FIG 15 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = -10 AND -15 DEG
 CLMACH = .26 PAGE 111



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPDRBK	AILRON	REFERENCE INFORMATION
(AF8030)	DA119A B61C1F12751V124E46V1SR15X29	-10.000	.000	25.000	.000	SREF 2690 0100 90.FT.
(AF8026)	DA119A B61C1F12751V124E47V1SR15X29	-10.000	.000	25.000	.000	LREF 474.8100 INCHES
(AF8027)	DA119A B61C1F12751V124E48V1SR15X29	-10.000	.000	25.000	.000	BREF 936.6800 INCHES
(AF8020)	DA119A B61C1F12751V124E46V1SR15X29	-15.000	.000	25.000	.000	XPRP 1076.4800 INCHES
(AF8018)	DA119A B61C1F12751V124E47V1SR15X29	-15.000	.000	25.000	.000	ZPRP 375.0000 INCHES
(AF8019)	DA119A B61C1F12751V124E48V1SR15X29	-15.000	.000	25.000	.000	SCALE .0405 SCALE





FIG 15 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = -10 AND -15 DEG
 (A)MACH = .26 PAGE 112



DATA SET SYMBOL CONFIGURATION DESCRIPTION REFERENCE INFORMATION


DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BDFLAP	SPOBRK	A1LRGN	SREF	2690.0100	50.FT.
(AF8030)	CA119A B61C1F12MS1V124E46V1SR15X29	-10.000	.000	25.000	.000	LREF	474.8100	INCHES
(AF8036)	CA119A B61C1F12MS1V124E47V1SR15X29	-10.000	.000	25.000	.000	BREF	936.5800	INCHES
(AF8027)	CA119A B61C1F12MS1V124E48V1SR15X29	-15.000	.000	25.000	.000	XMRP	1076.1800	INCHES
(AF8020)	CA119A B61C1F12MS1V124E45V1SR15X29	-15.000	.000	25.000	.000	ZMRP	375.0000	INCHES
(AF8018)	CA119A B61C1F12MS1V124E47V1SR15X29	-15.000	.000	25.000	.000	SCALE	.2405	SCALE
(AF8019)	CA119A B61C1F12MS1V124E48V1SR15X29	-15.000	.000	25.000	.000			



FOREBODY AXIAL FORCE COEFFICIENT, CAF

FIG 15 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = -10 AND -15 DEG

DATA SET SPIN	CONFIGURATION DESCRIPTION	ELEVON	REFLAP	SPORNK	AFJORN	REFERENCE INFORMATION
{ AF8020 }	DA119A 861C1F12451V124E46V1SR15X29	-10.000	.000	25.000	.000	WREF 2000.0100 50.FT
{ AF8026 }	DA119A 861C1F12451V124E47V1SR15X29	-10.000	.000	25.000	.000	LREF 174.8100 INCHES
{ AF8027 }	DA119A 861C1F12451V124E46V1SR15X29	-10.000	.000	25.000	.000	BREF 538.8500 INCHES
{ AF8020 }	DA119A 861C1F12451V124E46V1SR15X29	-15.000	.000	25.000	.000	YMRP 1076.4800 INCHES
{ AF8018 }	DA119A 861C1F12451V124E47V1SR15X29	-15.000	.000	25.000	.000	ZMRP 375.0000 INCHES
{ AF8018 }	DA119A 861C1F12451V124E46V1SR15X29	-15.000	.000	25.000	.000	SCALE .0405 INCHES



BASE AXIAL FORCE COEFFICIENT, CAB


FIG 15 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = -10 AND -15 DEG
 CAJMACH = .26 PAGE 114



DATA SET SYMBOL CONFIGURATION DESCRIPTION ELEVON BOFLAP SPOBRK AILTRON REFERENCE INFORMATION

(AF8030) 0A119A B61C11F12M5V124E46V19R15X29 -10.000 .000 25.000 .000 SREF 2690.0100 SO.FT.
 (AF8026) 0A119A B61C11F12M5V124E47V19R15X29 -10.000 .000 25.000 .000 LREF 474.8100 INCHES
 (AF8027) 0A119A B61C11F12M5V124E48V19R15X29 -10.000 .000 25.000 .000 BREF 936.6800 INCHES
 (AF8020) 0A119A B61C11F12M5V124E46V19R15X29 -15.000 .000 25.000 .000 XMRP 1076.4800 INCHES
 (AF8018) 0A119A B61C11F12M5V124E47V19R15X29 -15.000 .000 25.000 .000 YMRP .0000 INCHES
 (AF8019) 0A119A B61C11F12M5V124E48V19R15X29 -15.000 .000 25.000 .000 ZMRP 375.0405 INCHES SCALE

0A119A B61C11F12M5V124E46V19R15X29
 0A119A B61C11F12M5V124E47V19R15X29
 0A119A B61C11F12M5V124E48V19R15X29
 0A119A B61C11F12M5V124E46V19R15X29
 0A119A B61C11F12M5V124E47V19R15X29
 0A119A B61C11F12M5V124E48V19R15X29




FOREBODY DRAG COEFFICIENT, CDF

FIG 15 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = -10 AND -15 DEG



REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR

DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SFOBRK	AUTLON	REFERENCE INFORMATION
{AF8000}	DA119A BS1C1F12H51V124E46V1SR15X29	-10.000	.000	25.000	.000	SREF 2000.0100 90.FT
{AF8026}	DA119A BS1C1F12H51V124E47V1SR15X29	-10.000	.000	25.000	.000	LREF 474.8100 INCHES
{AF8027}	DA119A BS1C1F12H51V124E48V1SR15X29	-10.000	.000	25.000	.000	BREF 936.5800 INCHES
{AF8020}	DA119A BS1C1F12H51V124E46V1SR15X29	-15.000	.000	25.000	.000	XMRP 1076.4800 INCHES
{AF8018}	DA119A BS1C1F12H51V124E47V1SR15X29	-15.000	.000	25.000	.000	YMRP .0000 INCHES
{AF8019}	DA119A BS1C1F12H51V124E48V1SR15X29	-15.000	.000	25.000	.000	ZMRP 375.0000 INCHES
						SCALE .0405



PITCHING MOMENT COEFFICIENT, C_M

FIG 15 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = -10 AND -15 DEG (A)MACH = .26



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPOBRK	AILRON	REFERENCE INFORMATION
(AF8030)	0A119A 861C1F12H51V124E16V19R15X29	-10.000	.000	25.000	.000	SREF 2630.0100 SQ.FT.
(AF8026)	0A119A 861C1F12H51V124E17V19R15X29	-10.000	.000	25.000	.000	LREF 474.8100 INCHES
(AF8027)	0A119A 861C1F12H51V124E18V19R15X29	-10.000	.000	25.000	.000	BREF 936.6800 INCHES
(AF8020)	0A119A 861C1F12H51V124E16V19R15X29	-15.000	.000	25.000	.000	XMRP 10716.0000 INCHES
(AF8018)	0A119A 861C1F12H51V124E17V19R15X29	-15.000	.000	25.000	.000	YMRP 375.0000 INCHES
(AF8019)	0A119A 861C1F12H51V124E18V19R15X29	-15.000	.000	25.000	.000	ZMRP 375.0000 INCHES
						SCALE .0100 SCALE




FIG 15 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = -10 AND -15 DEG
 (A) MACH = .26 PAGE 117



DATA SET SYMBD	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPDRBK	AIRBON	REFERENCE INFORMATION
(AF8030)	GA119A B61C1F2V61V124E48V1SR15X29	-10.000	.000	25.000	.000	SREF 2690.0100 SC.FT
(AF8026)	GA119A B61C1F2V61V124E47V1SR15X29	-10.000	.000	25.000	.000	LREF 474.8100 INCHES
(AF8027)	GA119A B61C1F2V61V124E48V1SR15X29	-10.000	.000	25.000	.000	BREF 936.8600 INCHES
(AF8020)	GA119A B61C1F2V61V124E46V1SR15X29	-15.000	.000	25.000	.000	XPRP 1076.4600 INCHES
(AF8018)	GA119A B61C1F2V61V124E47V1SR15X29	-15.000	.000	25.000	.000	YPRP .0000 INCHES
(AF8019)	GA119A B61C1F2V61V124E48V1SR15X29	-15.000	.000	25.000	.000	ZPRP 375.0000 INCHES
						SCALE .0405 SCALE




FIG 15 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = -10 AND -15 DEG
 (A)MACH = .26 PAGE 118



UNFA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPOBRK	AILRON	REFERENCE INFORMATION	SO.FT.
(AF8030)	0A119A B61C1F12M5V124E46V19R15X29	-10.000	.000	25.000	.000	SREF 2690.0100	INCHES
(AF8076)	0A119A B61C1F12M5V124E47V19R15X29	-10.000	.000	25.000	.000	LREF 474.8100	INCHES
(AF8077)	0A119A B61C1F12M5V124E48V19R15X29	-10.000	.000	25.000	.000	BREF 936.6800	INCHES
(AF8078)	0A119A B61C1F12M5V124E46V19R15X29	-15.000	.000	25.000	.000	XMRP 1076.4800	INCHES
(AF8018)	0A119A B61C1F12M5V124E47V19R15X29	-15.000	.000	25.000	.000	YMRP 375.3000	INCHES
(AF8019)	0A119A B61C1F12M5V124E48V19R15X29	-15.000	.000	25.000	.000	ZMRP .0405	SCALE




FIG 15 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = -10 AND -15 DEG
 (A)MACH = .26 PAGE 119



DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AF8030) □ ○ △
 (AF8026) □ ○ △
 (AF8027) □ ○ △
 (AF8020) □ ○ △
 (AF8018) □ ○ △
 (AF8019) □ ○ △


ELEVATION
 10.000
 10.000
 10.000
 15.000
 15.000

W/FLAP
 .000
 .000
 .000
 .000
 .000

W/POBRK
 25.000
 25.000
 25.000
 25.000
 25.000

ALIGN
 .000
 .000
 .000
 .000
 .000

REFERENCE INFORMATION
 SREF 2690.0100 SQ.FT
 LREF 474.8100 INCHES
 BREF 506.6800 INCHES
 XPRP 1076.1800 INCHES
 YPRP 375.0000 INCHES
 ZPRP .0405 INCHES
 SCALE



LONGITUDINAL CENTER OF PRESSURE LOCATION, XCP/L

FIG 15 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = -10 AND -15 DEG
 (A) MACH = .26




TA SET SYMBOL. CONFIGURATION DESCRIPTION

(AF8013)	DA119A	B61C1F1275	V124E16V19R15X29
(AF8017)	DA119A	B61C1F1275	V124E17V19R15X29
(AF8016)	DA119A	B61C1F1275	V124E18V19R15X29
(AF8010)	DA119A	B61C1F1275	V124E16V19R15X29
(AF8011)	DA119A	B61C1F1275	V124E17V19R15X29
(AF8012)	DA119A	B61C1F1275	V124E18V19R15X29

ELEVON .000 BO-LAP .000 SPEEDRY .000 ALIGN .000 REFERENCE INFORMATION

2690	.0100	50-FT.
474	.8100	INC-ES
936	.6800	INC-ES
1076	.1800	INC-ES
375	.0000	INC-ES
3405		SCALE



FOREBODY LIFT COEFFICIENT, CLF

FIG 16 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON =-20 AND-30 DEG



DATA SET	SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	EDFLAP	SPOBRK	AILERON	REFERENCE INFORMATION
(AF0013)	□	DA119A BS1C1 IF1295 V124E46V1 SR19C29	-20.000	.000	20.000	.000	SREF 2690.0100 SQ.FT.
(AF0017)	○	DA119A BS1C1 IF1295 V124E47V1 SR15C29	-20.000	.000	20.000	.000	LREF 174.8100 INCHES
(AF0016)	△	DA119A BS1C1 IF1295 V124E46V1 SR15C29	-20.000	.000	20.000	.000	BREF 936.6800 INCHES
(AF0010)	◇	DA119A BS1C1 IF1295 V124E46V1 SR15C29	-20.000	.000	20.000	.000	XMRP 1076.4800 INCHES
(AF0011)	×	DA119A BS1C1 IF1295 V124E47V1 SR15C29	-20.000	.000	20.000	.000	ZMRP 375.0000 INCHES
(AF0012)	◇	DA119A BS1C1 IF1295 V124E46V1 SR15C29	-30.000	.000	20.000	.000	SCALE .0405 SCALE




FIG 16 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON #20 AND 30 DEG
 (A)MACH = .26



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPDRK	AILERON	REFERENCE INFORMATION
(AF8013)	0A119A 861C11F 2W51V124E48V19R15X29	-20.000	.000	25.000	.000	SREF 2690.0100 SO.F.T.
(AF8017)	0A119A 861C11F 2W51V124E47V19R15X29	-20.000	.000	25.000	.000	LREF 474.8100 INCHES
(AF8016)	0A119A 861C11F 2W51V124E48V19R15X29	-20.000	.000	25.000	.000	BREF 936.6800 INCHES
(AF8010)	0A119A 861C11F 2W51V124E48V19R15X29	-30.000	.000	23.000	.000	XREF 1076.4800 INCHES
(AF8011)	0A119A 861C11F 2W51V124E47V19R15X29	-30.000	.000	23.000	.000	YREF .0000 INCHES
(AF8012)	0A119A 861C11F 2W51V124E48V19R15X29	-30.000	.000	23.000	.000	ZREF 375.0000 INCHES
						SCALE .0405 SCALE





FIG 16 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = -20 AND -30 DEG

CAJMACH = .26

PAGE 123



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BD FLAP	SPUBRN	AILUVN	REFERENCE INFORMATION
(AF8013)	0A11SA BS1C11F124S1V124E46V1SR15X29	-20.000	.000	25.000	.000	SREF 2690.0100 50.FT.
(AF8017)	0A11SA BS1C11F124S1V124E47V1SR15X29	-20.000	.000	25.000	.000	LREF 474.8100 INCHES
(AF8016)	0A11SA BS1C11F124S1V124E48V1SR15X29	-20.000	.000	25.000	.000	BREF 836.6800 INCHES
(AF8010)	0A11SA BS1C11F124S1V124E45V1SR15X29	-30.000	.000	25.000	.000	XMRP 1076.1800 INCHES
(AF8011)	0A11SA BS1C11F124S1V124E47V1SR15X29	-30.000	.000	25.000	.000	YMRP .0000 INCHES
(AF8012)	0A11SA BS1C11F124S1V124E48V1SR15X29	-30.000	.000	25.000	.000	ZMRP 375.0000 INCHES
						SCALE .0405




BASE AXIAL FORCE COEFFICIENT, CAB

FIG 16 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = 20 AND 30 DEG
 (A)MACH = .26 PAGE :24



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BD FLAP	SPDRBK	AILERON	REFERENCE INFORMATION
{ AF8013 }	0A119A B61C1F12M5V124E46V1SR15X29	-20.000	.000	25.000	.000	SREF 2690.0100 SQ.FT.
{ AF8017 }	0A119A B61C1F12M5V124E47V1SR15X29	-20.000	.000	25.000	.000	LREF 474.8100 INCHES
{ AF8016 }	0A119A B61C1F12M5V124E48V1SR15X29	-20.000	.000	25.000	.000	BREF 936.6800 INCHES
{ AF8010 }	0A119A B61C1F12M5V124E46V1SR15X29	-30.000	.000	25.000	.000	XMRP 1076.4800 INCHES
{ AF8011 }	0A119A B61C1F12M5V124E47V1SR15X29	-30.000	.000	25.000	.000	YMRP .0000 INCHES
{ AF8012 }	0A119A B61C1F12M5V124E48V1SR15X29	-30.000	.000	25.000	.000	ZMRP 375.0000 INCHES
						SCALE .0405 SCALE




FOREBODY DRAG COEFFICIENT, CDF

FIG 16 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = -20 AND -30 DEG
 (A)MACH = .26



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BDFLAP	SPDRK	AILERON	REFERENCE INFORMATION	SO. FT.
{AF8013}	0A119A B61C1 F12M5 V124E46V SR15X29	-20.000	.000	25.000	.000	SREF	2680.0100
{AF8017}	0A119A B61C1 F12M5 V124E47V SR15X29	-20.000	.000	25.000	.000	LREF	474.8100
{AF8018}	0A119A B61C1 F12M5 V124E48V SR15X29	-20.000	.000	25.000	.000	SREF	936.6800
{AF8010}	0A119A B61C1 F12M5 V124E46V SR15X29	-30.000	.000	25.000	.000	XMRP	1076.4800
{AF8011}	0A119A B61C1 F12M5 V124E47V SR15X29	-30.000	.000	25.000	.000	ZMRP	375.0000
{AF8012}	0A119A B61C1 F12M5 V124E48V SR15X29	-30.000	.000	25.000	.000	SCALE	.0405



PITCHING MOMENT COEFFICIENT, CLM

FIG 16 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = -20 AND -30 DEG

(A)MACH = .26

PAGE 126



REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR

DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BDFLAP	SPDRBK	AIRTRON	REFERENCE INFORMATION
{ AF8013 }	DA119A B61C1F12H5IV124E46V19R15X29	-20.000	.000	25.000	.000	SREF 2690.0100 SQ.FT.
{ AF8017 }	DA119A B61C1F12H5IV124E47V19R15X29	-20.000	.000	25.000	.000	LREF 474.8100 INCHES
{ AF8016 }	DA119A B61C1F12H5IV124E48V19R15X29	-20.000	.000	25.000	.000	BREF 936.8600 INCHES
{ AF8010 }	DA119A B61C1F12H5IV124E46V19R15X29	-30.000	.000	25.000	.000	XMRP 1076.4800 INCHES
{ AF8011 }	DA119A B61C1F12H5IV124E47V19R15X29	-30.000	.000	25.000	.000	YMRP .0000 INCHES
{ AF8012 }	DA119A B61C1F12H5IV124E48V19R15X29	-30.000	.000	25.000	.000	ZMRP 375.0000 INCHES
						SCALE .0405




FIG 16 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = -20 AND -30 DEG (A)MACH = .26 PAGE 127



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	DFLAP	SPOBRK	AILERON	REFERENCE INFORMATION
{AF8013}	0A119A 861C1 F127S V124E46V SR15X29	-20.000	.000	25.000	.000	SREF 2650.0100 SQ.FT.
{AF8017}	0A119A 861C1 F127S V124E47V SR15X29	-20.000	.000	25.000	.000	LREF 474.8100 INCHES
{AF8016}	0A119A 861C1 F127S V124E48V SR15X29	-20.000	.000	25.000	.000	BREF 938.6800 INCHES
{AF8010}	0A119A 861C1 F127S V124E46V SR15X29	-30.000	.000	25.000	.000	XMPR 1076.1800 INCHES
{AF8011}	0A119A 861C1 F127S V124E47V SR15X29	-30.000	.000	25.000	.000	ZMPR .0000 INCHES
{AF8012}	0A119A 861C1 F127S V124E48V SR15X29	-30.000	.000	25.000	.000	SCALE .0405 SCALE




FIG 16 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = -20 AND -30 DEG
 (A)MACH = .26



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BD FLAP	SPODBRK	A1LRON	REFERENCE INFORMATION
{AF8013}	0A1119A 861C11F 2M51V124E46V19R15X29	-20.000	.000	25.000	.000	SREF 2690.0100 SD.FT.
{AF8017}	0A1119A 861C11F 2M51V124E47V19R15X29	-20.000	.000	25.000	.000	LREF 474.8100 INCHES
{AF8016}	0A1119A 861C11F 2M51V124E46V19R15X29	-20.000	.000	25.000	.000	BREF 936.6800 INCHES
{AF8010}	0A1119A 861C11F 2M51V124E46V19R15X29	-30.000	.000	25.000	.000	XMRP 1076.4800 INCHES
{AF8011}	0A1119A 861C11F 2M51V124E47V19R15X29	-30.000	.000	25.000	.000	YMRP .0000 INCHES
{AF8012}	0A1119A 861C11F 2M51V124E46V19R15X29	-30.000	.000	25.000	.000	ZMRP .0405 INCHES
						SCALE




FIG 16 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = -20 AND -30 DEG

(A)MACH = .26 PAGE 129



DATA SET SYMBOL CONFIGURATION DESCRIPTION

{AF0013}	CA11SA	BS1C11F	2N61V1	24E46V1	SR15X29
{AF0017}	CA11SA	BS1C11F	2N61V1	24E47V1	SR15X29
{AF0016}	CA11SA	BS1C11F	2N61V1	24E48V1	SR15X29
{AF0010}	CA11SA	BS1C11F	2N61V1	24E46V1	SR15X29
{AF0011}	CA11SA	BS1C11F	2N61V1	24E47V1	SR15X29
{AF0012}	CA11SA	BS1C11F	2N61V1	24E48V1	SR15X29

ELEVON
 0.000
 -20.000
 -20.000
 -20.000
 -20.000
 -20.000

BD LAP
 .000
 .000
 .000
 .000
 .000

SPDRK
 25.000
 25.000
 25.000
 25.000
 25.000

AIRLON
 .000
 .000
 .000
 .000
 .000

REFERENCE INFORMATION
 GREF 2680.0100 SO.FT.
 LREF 474.8100 INCHES
 BREF 936.6800 INCHES
 XMRP 1076.4800 INCHES
 YMRP .0000 INCHES
 ZMRP 375.0000 INCHES
 SCALE .0405




FIG 16 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = -20 AND -30 DEG
 (A)MACH = .26



DATA SET SYMBOL CONFIGURATION DESCRIPTION REFERENCE INFORMATION

(AF8078)	0A119A 861C1F12451V124E46V19R15X29	SREF 2690.0100 SQ.FT.
(AF8079)	0A119A 861C1F12451V124E47V19R15X29	LREF 474.8100 INCH-ES
(AF8006)	0A119A 861C1F12451V124E46V19R15X29	BREF 936.6800 INCH-ES
		YMRP 1076.4800 INCH-ES
		ZMRP 375.0000 INCH-ES
		SCALE .0405 SCALE




FIG 17 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = -40 DEG

(A)MACH = .26



DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AF8009) □ GA119A BS1C11F12MS1V124E46V1SR15X29
 (AF8005) ◇ GA119A BS1C11F12MS1V124E47V1SR15X29
 (AF8006) ◇ GA119A BS1C11F12MS1V124E48V1SR15X29

ELEVON EDOFLAP SPOBRK AILTRON REFERENCE INFORMATION
 -40.000 .000 .000 .000 2690.0100 50. FT.
 -40.000 .000 .000 .000 474.8100 INCHES
 -40.000 .000 .000 .000 936.6800 INCHES
 -40.000 .000 .000 .000 1076.1800 INCHES
 YMRP .0000 INCHES
 ZMRP .0000 INCHES
 SCALE .0405 SCALE




FIG 17 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = -40 DEG
 (A)MACH = .26



DATA SET SYMBOL CONFIGURATION DESCRIPTION

(AF8009) 0 0A113A 861C11F1 2751V1 24E16V1 9R15X28

(AF8005) 0 0A113A 861C11F1 2751V1 24E17V1 9R15X29

(AF8006) 0 0A113A 861C11F1 2751V1 24E18V1 9R15X29

ELEVON BDFLAP SPDB-X ALLRON

-40.000 .000 25.000 .000

-40.000 .000 25.000 .000

-40.000 .000 25.000 .000

REFERENCE INFORMATION

SREF 2690.0100 50.FT.

LREF 474.8100 INCHES


B²-F 936.6800 INCHES

XMRP 1076.4800 INCHES

YMRP 375.0000 INCHES

ZMRP 375.0000 INCHES

SCALE .0405 SCALE



FOREBODY AXIAL FORCE COEFFICIENT, CAF

FIG 17 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = -40 DEG

CAJ MACH = .26



DATA SE, SYMBOL, CONFIGURATION DESCRIPTION

(AF8008)	Q1119A	BS1C11F	276	V124E48V	SR15X29
(AF8005)	Q1119A	BS1C11F	276	V124E47V	SR15X29
(AF8006)	Q1119A	BS1C11F	276	V124E48V	SR15X29

REFERENCE INFORMATION

SREF	269C	010C	50	FT
LREF	474	810C		INCHES
BREF	926	680C		INCHES
XMRP	1076	480C		INCHES
YMRP		0000		INCHES
ZMRP	375	0000		INCHES
SCALE		0405		SCALE

ELEVON	BOFLAP	SFOBRK	ALLRON
-40.000	.000	25.000	.000
-40.000	.000	25.000	.000
-40.000	.000	25.000	.000

BASE AXIAL FORCE COEFFICIENT, C₉




FIG 17 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = -40 DEG

(A)MACH = .26

PAGE 134




REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR

DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AF 8009) 0A11SA B6C1IF 2MS W124E16V SR15X29
 (AF 8005) 0A11SA B6C1IF 2MS W124E17V SR15X29
 (AF 8006) 0A11SA B6C1IF 2MS W124E16V SR15X29

ELEVON 8DFLAP SPOBRK ALLRON
 -40.000 .000 .000
 -40.000 .000 25.000
 -40.000 .000 25.000

REFERENC INFORMATION
 SREF 269 0100 SQ.FT
 LREF 474 8100 INCHES
 BREF 936 6800 INCHES
 XMRP 1073 4800 INCHES
 YMRP 375 0000 INCHES
 ZMRP 0105 INCHES



FOREBODY DRAG COEFFICIENT, CDF

FIG 17 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = -40 DEG

(A)MACH = .26



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	DOFLAP	SPOBRK	AILRON	REFERENCE INFORMATION
(AF8008)	0A119A BS1C1F12P51V124E46V1SR15K28	-40.000	.000	25.000	.000	SREF 2690.0100 SQ.F.T.
(AF8009)	0A119A BS1C1F12P51V124E47V1SR15K28	-40.000	.000	25.000	.000	LREF 174.8100 INCHES
(AF8005)	0A119A BS1C1F12P51V124E46V1SR15K28	-40.000	.000	25.000	.000	BREF 356.6800 INCHES
						XMRP 1076.4800 INCHES
						YMRP .0000 INCHES
						ZMRP 375.0000 INCHES
						SCALE .0405 SCALE




FIG 17 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = 40 DEG
 (A)MACH = .26 PAGE 136



DATA SET SYMBOL CONFIGURATION DESCRIPTION

(AF8009) O GA119A B61C1F12H51V124E46V1SR15X29

(AF8005) X GA119A B61C1F12H51V124E47V1SR15X29

(AF8006) X GA119A B61C1F12H51V124E48V1SR15X29

ELEVON .000

-40.000

-40.000

-40.000

BOFLAP .000

.000

.000

.000

SPOBRK .000

25.000

23.000

23.000

ILRON .000

.000

.000

.000

REFERENCE INFORMATION

SREF 2690.0100 SQ.FT.

LREF 474.8100 INCHES

BREF 936.5900 INCHES

XMRP 1076.4800 INCHES

YMRP .0000 INCHES

ZMRP 375.0000 INCHES

SCALE .3105 SCALE




FIG 17 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = -40 DEG

(M)MACH = .26



DATA SET SYMBOL
(A'9009)
(AF9005)
(AF9006)

CONFIGURATION DESCRIPTION

CA119A B61C11F1251V124E46V19R15X29
 CA119A B61C11F1251V124E47V19R15X29
 CA119A B61C11F1251V124E48V19R15X29

ELEVON
-40.000
-40.000
-40.000

BRFLAP
.000
.000
.000

SPOBRK
25.000
25.000
25.000

A1LRON
.000
.000
.000

REFERENCE INFORMATION
 SREF 2030.0100 50. FT.
 LREF 474.8100 INCHES
 BREF 936.5800 INCHES
 XMRP 1076.4800 INCHES
 YMRP .0000 INCHES
 ZMRP 375.0000 INCHES
 SCALE .0405 SCALE




FIG 17 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = 40 DEG


(A)MACH = .26



17

Ultrasonic sensor for 800

DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BDFLAP	SPOBRK	AIRLON	REFERENCE INFORMATION
(AF8009)	0A119A B61C1F124E16V19R15X29	-40.000	.000	25.000	.000	SREF 2690.0100 SQ.FT.
(AF8005)	0A119A B61C1F124E17V19R15X29	-40.000	.000	25.000	.000	LREF 474.8100 INCHES
(AF8006)	0A119A B61C1F124E18V19R15X29	-40.000	.000	25.000	.000	BREF 936.6800 INCHES
						XMRP 1076.4800 INCHES
						ZMRP .0000 INCHES
						SCALE 375.0000 INCHES




LIFT/FOREBODY DRAG RATIO, L/D

FIG 17 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = -40 DEG



DATA SET SYMBO. CONFIGURATION DESCRIPTION
 { AF6005 } CA119A 661C11F12761V124E48V19R15X29
 { AF6005 } CA119A 661C11F12761V124E47V19R15X29
 { AF6005 } CA119A 661C11F12761V124E48V19R15X29

ELEVON BOFLAP SPOBRK AILTRON REFERENCE INFORMATION
 -40.000 .000 25.000 .000 2690.0100 SQ.FT.
 -40.000 .000 25.000 .000 174.8100 INCHES
 .000 .000 .000 .000 826.6800 INCHES
 .000 .000 .000 .000 1076.4800 INCHES
 .000 .000 .000 .000 .0000 INCHES
 .000 .000 .000 .000 .0000 INCHES
 .000 .000 .000 .000 .0405 SCALE



LONGITUDINAL CENTER OF PRESSURE LOCATION, XCP/L

FIG 17 EFFECT OF FLAPPER DOOR ON ELEVON EFFECTIVENESS, ELEVON = -40 DEG

(A)MACH = .26



DATA SET SYMBOL	CONF IGURATION DESCRIPTION	ELEVON	BOFLAP	SPOBRK	AILERON	REFERENCE INFORMATION
(AF8004)	CA119A B61C1F12M5V124E18V19R15X29	.000	.000	25.000	.000	SREF 2690.0100 SQ.FT.
(AF8042)	CA119A B61C1F12M5V124E18V19R15X29	.000	.000	25.000	.000	LREF 474.6100 INCHES
(AF8024)	CA119A B61C1F12M5V124E18V19R15X29	10.000	.000	25.000	.000	BREF 936.6800 INCHES
(AF8037)	CA119A B61C1F12M5V124E18V19R15X29	10.000	.000	25.000	.000	YMRP 1076.1800 INCHES
(AF8050)	CA119A B61C1F12M5V124E18V19R15X29	15.000	.000	25.000	.000	ZMRP 375.0000 INCHES
(AF8C48)	CA119A B61C1F12M5V124E18V19R15X29	15.000	.000	25.000	.000	SCALE .0100 INCHES




FIG 18 EFFECT OF WING/ELEVON GAP ON ELEVON EFFECTIVENESS, ELEVON = 0, 10, 15
 (A)MACH = .26 PAGE 141



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPOBRK	AIIIRON	REFERENCE INFORMATION
[AF8004]	CA119A B61C11F 2M51V124E48V19R15X29	.000	.000	25.000	.000	SREF 2690.0100 50.FT.
[AF8042]	CA119A B61C11F 2M51V124E48V19R15X29	.000	.000	25.000	.000	LREF 474.8100 INCHES
[AF8074]	CA119A B61C11F 2M51V124E48V19R15X29	10.000	.000	25.000	.000	BREF 936.6900 INCHES
[AF8037]	CA119A B61C11F 2M51V124E48V19R15X29	10.000	.000	25.000	.000	XMRP 1076.4800 INCHES
[AF3050]	CA119A B61C11F 2M51V124E48V19R15X29	15.000	.000	25.000	.000	ZMRP 375.0000 INCHES
[AF8048]	CA119A B61C11F 2M51V124E51V19R15X29	15.000	.000	25.000	.000	ZMRP 375.0000 INCHES
						SCALE .04CS




FIG 18 EFFECT OF WING/ELEVON GAP ON ELEVON EFFECTIVENESS, ELEVON - J, 10, 15
 (A)MACH = .26 PAGE 152



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPOBRK	AILEVON	REFERENCE INFORMATION
(AF8004)	GA119A 86 C1 F1 2MS V124E48V1 9R15X29	.000	.000	25.000	.000	SREF 2690.0100 SQ.FT.
(AF8042)	GA119A 86 C1 F1 2MS V124E48V1 9R15X29	.000	.000	25.000	.000	LREF 474.8100 INCHES
(AF8024)	GA119A 86 C1 F1 2MS V124E48V1 9R15X29	10.000	.000	25.000	.000	BREF 936.6800 INCHES
(AF8037)	GA119A 86 C1 F1 2MS V124E48V1 9R15X29	10.000	.000	25.000	.000	XMRP 1076.4800 INCHES
(AF8050)	GA119A 86 C1 F1 2MS V124E48V1 9R15X29	15.000	.000	25.000	.000	YMRP 375.0000 INCHES
(AF8048)	GA119A 86 C1 F1 2MS V124E48V1 9R15X29	15.000	.000	25.000	.000	SCALE .0405 SCALE





FIG 18 EFFECT OF WING/ELEVON GAP ON ELEVON EFFECTIVENESS, ELEVON = 0, 10, 15
 (A) MACH = .26 PAGE 143



DATA SET BY SOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPOBRK	AILRON	REFERENCE INFORMATION
{ AF8004 }	CA119A 56 C1 F1 245 V1 24E18V1 9R1 5X29	.000	.000	23.000	.000	WRET 2650.0100 SO.FT.
{ AF8042 }	CA119A 56 C1 F1 245 V1 24E18V1 9R1 5X29	.000	.000	23.000	.000	LRET 474.8100 INCHES
{ AF8024 }	CA119A 56 C1 F1 245 V1 24E18V1 9R1 5X29	.000	.000	23.000	.000	SRET 938.5800 INCHES
{ AF8037 }	CA119A 56 C1 F1 245 V1 24E18V1 9R1 5X29	.000	.000	23.000	.000	XPRB 1076.4800 INCHES
{ AF8050 }	CA119A 56 C1 F1 245 V1 24E18V1 9R1 5X29	.000	.000	23.000	.000	YPRB 375.0000 INCHES
{ AF8048 }	CA119A 56 C1 F1 245 V1 24E18V1 9R1 5X29	.000	.000	23.000	.000	ZPRB 375.0000 INCHES
		.000	.000	23.000	.000	SCALE .0405



BASE AXIAL FORCE COEFFICIENT, CAB

FIG 18 EFFECT OF WING/ELEVON GAP ON ELEVON EFFECTIVENESS, ELEVON = 0, 10, 15

(A)MACH = .26

PAGE 144

DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	ROFLAP	SPOBRK	A1LRON	REFERENCE INFORMATION
(AF8004)	0A119A B61C11F 2MS V124E48V19R15X29	.000	.000	25.000	.000	SRFF 2690.0100 SQ.FT.
(AF8042)	0A119A B61C11F 2MS V124E48V19R15X29	.000	.000	25.000	.000	LREF 474.8100 INCHES
(AF8024)	0A119A B61C11F 2MS V124E48V19R15X29	10.000	.000	25.000	.000	BREF 936.6600 INCHES
(AF8037)	0A119A B61C11F 2MS V124E48V19R15X29	10.000	.000	25.000	.000	XMRP 1076.4800 INCHES
(AF8050)	0A119A B61C11F 2MS V124E48V19R15X29	15.000	.000	25.000	.000	YMRP .0000 INCHES
(AF8048)	0A119A B61C11F 2MS V124E51V19R15X29	15.000	.000	25.000	.000	ZMRP 375.0000 INCHES
					.000	SCALE .0405




FIG 18 EFFECT OF WING/ELEVON GAP ON ELEVON EFFECTIVENESS, ELEVON = 0, 10, 15
 (A)MACH = .26 PAGE 145

DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPOBRK	ALIRDN	REFERENCE INFORMATION
(AF8004)	CA119A B61C1F2M5V124E48V19R15X29	.000	.000	25.000	.000	SREF 2690.0100 SQ.FT.
(AF8042)	CA119A B61C1F2M5V124E48V19R15X29	.000	.000	25.000	.000	LREF 474.8100 INCHES
(AF8024)	CA119A B61C1F2M5V124E48V19R15X29	10.000	.000	25.000	.000	BREF 9.36.6800 INCHES
(AF8037)	CA119A B61C1F2M5V124E48V19R15X29	10.000	.000	25.000	.000	XMRP 1076.4600 INCHES
(AF8050)	CA119A B61C1F2M5V124E48V19R15X29	15.000	.000	25.000	.000	YMRP 375.0000 INCHES
(AF8048)	CA119A B61C1F2M5V124E51V19R15X29	15.000	.000	25.000	.000	ZMRP 375.0000 INCHES
						SCALE .0405





FIG 18 EFFECT OF WING/ELEVON GAP ON ELEVON EFFECTIVENESS. ELEVON = 0, 10, 15
 (A)MACH = .26 PAGE 146



DATA SET SYMBO	CONFIGURATION DESCRIPTION	ELEVON	BDFLAP	SPOBRM	AILRON	REFERENCE INFORMATION
(AF8004)	CA119A B61C F12-S1V124E48V19R15X29	.000	.000	25.000	.000	SREF 2690.0100 SQ.FT.
(AF8042)	CA119A B61C F12-S1V124E49V19R15X29	.000	.000	25.000	.000	LREF 474.81C3
(AF8024)	CA119A B61C F12-S1V124E49V19R15X29	10.000	.000	25.000	.000	BREF 936.6800 INCHES
(AF8037)	CA119A B61C F12-S1V124E49V19R15X29	10.000	.000	25.000	.000	XREF 1076.4800 INCHES
(AF8050)	CA119A B61C F12-S1V124E48V19R15X29	5.000	.000	25.000	.000	YREF 375.0000 INCHES
(AF8048)	CA119A B61C F12-S1V124E51V19R15X29	5.000	.000	25.000	.000	ZREF 375.0000 INCHES
						SCALE .0400 SCALE



FOREBODY LIFT COEFFICIENT, CLF

FIG 18 EFFECT OF WING/ELEVON GAP ON ELEVON EFFECTIVENESS. ELEVON = 0. 10. 15
 (A) MACH = .26 PAGE 147

DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPDRBK	AILRON	REFERENCE INFORMATION
(AF8004)	CA119A B6 C1 F1 275 V124E18V 9R15X29	.000	.000	25.000	.000	SREF 2690.0100 SO.FT.
(AF8042)	CA119A B6 C1 F1 275 V124E19V 9R15X29	.000	.000	25.000	.000	LREF 174.8100 INCHES
(AF8024)	CA119A B6 C1 F1 275 V124E18V 9R15X29	10.000	.000	25.000	.000	BREF 936.8600 INCHES
(AF8037)	CA119A B6 C1 F1 275 V124E19V 9R15X29	10.000	.000	25.000	.000	XPRP 1076.4800 INCHES
(AF8050)	CA119A B6 C1 F1 275 V124E18V 9R15X29	15.000	.000	25.000	.000	YPRP .0000 INCHES
(AF8048)	CA119A B6 C1 F1 275 V124E19V 9R15X29	15.000	.000	25.000	.000	ZPRP 375.0700 INCHES
						SCALE .0405 SCALE




FIG 18 EFFECT OF WING/ELEVON GAP ON ELEVON EFFECTIVENESS, ELEVON = 0, 10, 15
 (A)MACH = .26 PAGE 148



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPOBRK	AILRON	REFERENCE INFORMATION
{AF8004}	0A 18A 881C F1231V 24E48V SR15X23	.000	.000	25.000	.000	BREF 2690.0100 50. FT
{AF8042}	0A 18A 881C F1231V 24E49V SR15X23	.000	.000	25.000	.000	LREF 174.6100 NCLES
{AF8024}	0A 18A 881C F1231V 24E48V SR15X23	10.000	.000	25.000	.000	BREF 936.6900 NCLES
{AF8037}	0A 18A 881C F1231V 24E49V SR15X23	15.000	.000	25.000	.000	XPRP .076 4800 NCLES
{AF8050}	0A 18A 881C F1231V 24E48V SR15X23	15.000	.000	25.000	.000	XPRP .0000 NCLES
{AF8048}	0A 18A 881C F1231V 24E51V SR15X23	15.000	.000	25.000	.000	ZPRP 375.0000 NCLES
						SCALE .0405 SCALE




FIG 18 EFFECT OF WING/ELEVON GAP ON ELEVON EFFECTIVENESS, ELEVON = 0, 10, 15
 (A)MACH = .26 PAGE 149

DATA SET #	SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	ROTFLAP	SPDRGN	AIRLON	REFERENCE INFORMATION
[AF8004]	CA11SA	BS C F 2 5 V 24E 8V 9R 5X29	.000	.000	25.000	.000	SREF 70.0100 SQ.FT.
[AF8012]	CA11SA	BS C F 2 5 V 24E 8V 9R 5X29	.000	.000	25.000	.000	LREF 74.8100 INCHES
[AF8024]	CA11SA	BS C F 2 5 V 24E 8V 9R 5X29	10.000	.000	25.000	.000	BREF 936.6800 INCHES
[AF8037]	CA11SA	BS C F 2 5 V 24E 8V 9R 5X29	10.000	.000	25.000	.000	XPRP 1076.4800 INCHES
[AF8050]	CA11SA	BS C F 2 5 V 24E 8V 9R 5X29	15.000	.000	25.000	.000	YPRP .0000 INCHES
[AF8048]	CA11SA	BS C F 2 5 V 24E 8V 9R 5X29	15.000	.000	25.000	.000	ZPRP 375.0000 INCHES
							SCALE .0105

LONGITUDINAL CENTER OF PRESSURE LOCATION, XCP/L




FIG 18 EFFECT OF WING/ELEVON GAP ON ELEVON EFFECTIVENESS, ELEVON = 0, 10, 15 (A)MACH = .26 PAGE 150



DATA SET SYMBOL: (AF8052) (AF8054)

CONFIGURATION DESCRIPTION: 0A119A B61C1F12751V124E48V19R15X29
 0A119A B61C1F12751V124E51V19R15X29

ELEVON: 20.000
 BDFLAP: .000
 SPOBRK: 25.000
 ALLRON: .000

REFERENCE INFORMATION:
 SREF: 2690.0100 SQ.FT.
 LREF: 474.8100 INCHES
 BREF: 936.6800 INCHES
 XMRP: 1076.1600 INCHES
 YMRP: .0000 INCHES
 ZMRP: 375.0000 INCHES
 SCALE: .0405





FIG 19 EFFECT OF WING/ELEVON GAP ON ELEVON EFFECTIVENESS, ELEVON = 20 DEG



DATA SET SYMBOL: 0
 {AF8052} 0A119A 881C11F12-31V124E48V18R15X23
 {AF8054} 0A119A 881C11F12-31V124E51V18R15X28

ELEVON DEF LAP SPOBRK AIRLON
 20.000 .000 .000
 20.000 .000 25.000

REFERENCE INFORMATION:
 SREF 2690.0100 50.07
 LREF 474.8100 INCHES
 BREF 936.6800 INCHES
 XMRP 1076.4800 INCHES
 YMRP .0000 INCHES
 ZMRP 375.0000 INCHES
 SCALE .0405



NORMAL FORCE COEFFICIENT, CN

FIG 19 EFFECT OF WING/ELEVON GAP ON ELEVON EFFECTIVENESS, ELEVON - 20 DEG

(A)MACH = .26



DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AF8052) 0A119A 861C11F12M51W124E48V19R15X29
 (AF8054) 0A119A 861C11F12M51W124E51V19R15X29

ELEVON 80FLAP SPOBRK AILRON
 20.000 .000 .000
 20.000 .000 25.000

REFERENCE INFORMATION
 SREF 2690.3100 50.FT.
 LREF 474.6100 INCHES
 BREF 936.6800 INCHES
 XMRP 1076.4800 INCHES
 YMRP .0000 INCHES
 ZMRP 375.0000 INCHES
 SCALE .0405 SCALE




FIG 19 EFFECT OF WING/ELEVON GAP ON ELEVON EFFECTIVENESS, ELEVON = 20 DEG


(A)MACH = .26



DATA SET SYMBOL: 0
 (AF8032) 0A118A 081C11F12751V124E4M18R15X28
 (AF8034) 0A118A 081C11F12751V124E31V18R15X28

ELEVON 20.000
 IDP .AP .000
 SPDRBK 25.000
 AIRDRN .000

REFERENCE INFORMATION
 SREF 2690.0100 90.FT.
 LREF 474.8100 INC-ES
 BREF 936.6600 INC-ES
 YMRP 1076.4800 INC-ES
 ZMRP .0000 INC-ES
 SCALE 375.0000 INC-ES
 .0405 SCALE



BASE AXIAL FORCE COEFFICIENT, CAB

FIG 19 EFFECT OF WING/ELEVON GAP ON ELEVON EFFECTIVENESS, ELEVON = 20 DEG

(A)MACH = .26 PAGE 154



DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AF8052) 0A119A B61C11F12H51V124E48V1SR15X29
 (AF8054) 0A119A B61C11F12H51V124E51V1SR15X29


ELEVON 20.000
 20.000
 20.000

BOFLAP .000
 .000
 .000

SPOBRK 25.000
 25.000
 25.000

A1LRON .000
 .000
 .000

REFERENCE INFORMATION
 SREF 2690.0100 SQ.FT.
 LREF 474.8100 INCHES
 BREF 936.6800 INCHES
 XMRP 1076.4800 INCHES
 YMRP .0000 INCHES
 ZMRP .0000 INCHES
 SCALE .0405 INCHES



FOREBODY DRAG COEFFICIENT, CDF

FIG 19 EFFECT OF WING/ELEVON GAP ON ELEVON EFFECTIVENESS, ELEVON = 20 DEG


(A)MACH = .26



DATA SET SYMBOL: 8
 CONFIGURATION DESCRIPTION: 0A119A 881C11F12751V124E4M19R15X29
 {AF8052} 0A119A 881C11F12751V124E51V19R15X29
 {AF8054}

ELEVON: 20.000
 BDFLAP: .000
 SPOBRK: 25.000
 AIRLON: .000
 SREF: 2690.0100
 LREF: 474.8100
 BREF: 936.6800
 XMRP: 1076.1800
 YMRP: .0000
 ZMRP: .0000
 SCALE: .0405

REFERENCE INFORMATION
 SQ. FT. INCHES
 INCHES
 INCHES
 INCHES
 INCHES
 INCHES
 SCALE



PITCHING MOMENT COEFFICIENT, CLM

FIG 19 EFFECT OF WING/ELEVON GAP ON ELEVON EFFECTIVENESS; ELEVON = 20 DEG


(A)MACH = .26

PAGE 156



DATA SET SYMBOL: (AF8052) (AF8054)
 CONFIGURATION DESCRIPTION: 0A11SA 86C11F 2751V124E48V|9R15X29
 0A11SA 86C11F 2751V124E51V|9R15X29

ELEVON 80FLAP SPDERR AILTRON REFERENCE INFORMATION
 20.000 .000 25.000 2650.0100 SQ.FT
 20.000 .000 25.000 474.9100 INCHES
 XMRP 1076.4800 INCHES
 YMRP .0000 INCHES
 ZMRP 375.0000 INCHES
 SCALE .0105



FOREBODY LIFT COEFFICIENT, CLF

FIG 19 EFFECT OF WING/ELEVON GAP ON ELEVON EFFECTIVENESS, ELEVON = 20 DEG

(A)MACH = .26




DATA SET SYMBOL: (AF8052) (AF8054)

CONFIGURATION DESCRIPTION

0A119A 861C11F12761V124E48V19R15X29
 0A119A 861C11F12761V124E51V19R15X29

ELEVON 20,000
 BDFLAP 0,000
 SPOBRK 25,000
 AILRON 0,000

REFERENCE IN DIMENSION
 SREF 2690.0100 SO, FT INCHES
 LREF 474.8100 INCHES
 XMRP 836.6800 INCHES
 YMRP 1076.4800 INCHES
 ZMRP 0,0000 INCHES
 SCALE 375.0000 INCHES
 SCALE .0405



FOREBODY LIFT COEFFICIENT, CLF

FIG 19 EFFECT OF WING/ELEVON GAP ON ELEVON EFFECTIVENESS, ELEVON = 20 DEG

(A)MACH = .26



DATA SET SYMBOL: CONFIGURATION DESCRIPTION
 (AF8052) CA119A B611F12451W24E18V19R15X29
 (AF8054) CA119A B611F12451W24E51V19R15X25

ELEVON: 20.000
 BOULAP: .000
 SPOBRK: 25.000
 AILRON: .000
 SREF: 2690.0100 SCALF: INCHES
 LREF: 474.8100 INCHES
 BRFF: 936.6800 INCHES
 XMRP: 1076.1800 INCHES
 YMRP: .0000 INCHES
 ZMRP: .0000 INCHES
 SCALE: .0405 SCALE





FIG 19 EFFECT OF +ING/ELEVON GAP ON ELEVON EFFECTIVENESS, ELEVON = 20 DEG



DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AF 8052) □ 0A119A 861C11F12761V124E48V1SR15X23
 (AF 8054) □ 0A119A 861C11F12761V124E51V1SR15X28

LONGITUDINAL CENTER OF PRESSURE LOCATION, XCP/L



ELEVON 803 LAR SPOBRK AILRON
 20.000 .000
 20.000 .000

SREF 2650.0100
 LREF 474.8100
 XMPR 936.6800
 YMPR 1076.4800
 ZMPR .0000
 SCALE 375.0000

REFERENCE INFORMATION
 50.0 FT.
 INCHES
 INCHES
 INCHES
 INCHES
 INCHES
 SCALE

FIG 19 EFFECT OF WING/ELEVON GAP ON ELEVON EFFECTIVENESS, ELEVON = 20 DEG

(A)MACH = .26

PAGE 160



DATA SET SYMBOL	CONF. DESCRIPTION	ELEVON	BOFLAP	SPOSK	AIRION	REF. INFO	SCALE
AE8004	0110A 96 C1E 251V 24E48V 96 15X29	.000	.000	23.000	.000	2500 0.00	60 FT
AE8042	0110A 96 C1E 251V 24E48V 96 15X29	.000	.000	23.000	.000	174.8 0.00	SCALE
AE8073	0110A 96 C1E 251V 24E48V 96 15X29	.000	.000	23.000	.000	936.8000	VCES
AE8043	0110A 96 C1E 251V 24E48V 96 15X29	.000	.000	23.000	.000	1076.1000	VCES
AE8048	0110A 96 C1E 251V 24E48V 96 15X29	.000	.000	23.000	.000	1000.0000	VCES
AE8041	0110A 96 C1E 251V 24E48V 96 15X29	.000	.000	23.000	.000	1000.0000	VCES
		.000	.000	23.000	.000	1000.0000	SCALE




FIG 20 EFFECT OF WING/ELEVON GAP ON ELEVON EFFECTIVENESS, ELEVON GAP = 0.0, -20
 CA2MACH = 0.26
 SCALE: 1:6

FOREBODY LIFT COEFFICIENT, CLF

DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPOBRK	AILERON	REFERENCE INFORMATION
{AF8004}	CA119A B61C11F12MS1V124E48V1SR15X29	.000	.000	25.000	.000	SREF 2690.0100 SQ.FT.
{AF8042}	CA119A B61C11F12MS1V124E48V1SR15X29	.000	.000	25.000	.000	LREF 474.8100 INCHES
{AF8027}	CA119A B61C11F12MS1V124E48V1SR15X29	-10.000	.000	25.000	.000	BREF 936.6600 INCHES
{AF8043}	CA119A B61C11F12MS1V124E48V1SR15X29	-10.000	.000	25.000	.000	XPRP 1076.4800 INCHES
{AF8016}	CA119A B61C11F12MS1V124E48V1SR15X29	-20.000	.000	25.000	.000	YPRP .0000 INCHES
{AF8047}	CA119A B61C11F12MS1V124E51V1SR15X29	-20.000	.000	25.000	.000	ZPRP 375.0000 INCHES
						SCALE .0405





FIG 20 EFFECT OF WING/ELEVON GAP ON ELEVON EFFECTIVENESS, ELEVON - 0,-10,-20
 CAJMACH = .26 PAGE 162



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPOBRK	AILRON	REFERENCE INFORMATION
(AF8004)	DA119A B61C1F12M51V124E48V19R15X29	.000	.000	25.000	.000	SREF 2690.0100 SQ.FT.
(AF8042)	DA119A B61C1F12M51V124E49V19R15X29	.000	.000	25.000	.000	SREF 174.8100 INCHES
(AF8027)	DA119A B61C1F12M51V124E48V19R15X28	-10.000	.000	25.000	.000	SREF 936.6800 INCHES
(AF8043)	DA119A B61C1F12M51V124E49V19R15X28	-10.000	.000	25.000	.000	XMRP 1076.1800 INCHES
(AF8016)	DA119A B61C1F12M51V124E48V19R15X28	-20.000	.000	25.000	.000	ZMRP .0000 INCHES
(AF8047)	DA119A B61C1F12M51V124E51V19R15X29	-20.000	.000	25.000	.000	ZMRP 375.0000 INCHES
						SCALE .0405 SCALE



BASE AXIAL FORCE COEFFICIENT, CAB

FIG 20 EFFECT OF WING/ELEVON GAP ON ELEVON EFFECTIVENESS, ELEVON = 0, -10, -20
 (A)MACH = .25 PAGE 164



DATA SET SYMBOL	CD	SURFACE DESCRIPTION	ELEVON	SPDRK	ATTEN	REFERENCE INFORMATION
AE8004	19A	25.1124E4BY 5R 15X29	.000	.000	.000	2500 0100 50.FT. S
AE8002	19A	25.1124E4BY 5R 15X29	.000	.000	.000	2500 0100 50.FT. S
AE8003	19A	25.1124E4BY 5R 15X29	.000	.000	.000	2500 0100 50.FT. S
AE8005	19A	25.1124E4BY 5R 15X29	.000	.000	.000	2500 0100 50.FT. S
AE8006	19A	25.1124E4BY 5R 15X29	.000	.000	.000	2500 0100 50.FT. S
AE8007	19A	25.1124E4BY 5R 15X29	.000	.000	.000	2500 0100 50.FT. S
AE8008	19A	25.1124E4BY 5R 15X29	.000	.000	.000	2500 0100 50.FT. S
AE8009	19A	25.1124E4BY 5R 15X29	.000	.000	.000	2500 0100 50.FT. S
AE8010	19A	25.1124E4BY 5R 15X29	.000	.000	.000	2500 0100 50.FT. S
AE8011	19A	25.1124E4BY 5R 15X29	.000	.000	.000	2500 0100 50.FT. S
AE8012	19A	25.1124E4BY 5R 15X29	.000	.000	.000	2500 0100 50.FT. S
AE8013	19A	25.1124E4BY 5R 15X29	.000	.000	.000	2500 0100 50.FT. S
AE8014	19A	25.1124E4BY 5R 15X29	.000	.000	.000	2500 0100 50.FT. S
AE8015	19A	25.1124E4BY 5R 15X29	.000	.000	.000	2500 0100 50.FT. S
AE8016	19A	25.1124E4BY 5R 15X29	.000	.000	.000	2500 0100 50.FT. S
AE8017	19A	25.1124E4BY 5R 15X29	.000	.000	.000	2500 0100 50.FT. S
AE8018	19A	25.1124E4BY 5R 15X29	.000	.000	.000	2500 0100 50.FT. S
AE8019	19A	25.1124E4BY 5R 15X29	.000	.000	.000	2500 0100 50.FT. S
AE8020	19A	25.1124E4BY 5R 15X29	.000	.000	.000	2500 0100 50.FT. S

FOREBODY DRAG COEFFICIENT, CDF





FIG 20 EFFECT OF WING/ELEVON GAP ON ELEVON EFFECTIVENESS, ELEVON = 0, -10, -20
 (M)MACH = .26



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	ROFLAP	SPDBRK	AILERON	REFERENCE IN-DIRECTION	SO. FT.
(AF8004)	CA119A B61C11F2MS1V124E48V19R15X29	.000	.000	25.000	.000	SREF 2650.0100	INCHES
(AF8042)	CA119A B61C11F2MS1V124E49V19R15X29	.000	.000	25.000	.000	LREF 474.8100	INCHES
(AF8027)	CA119A B61C11F2MS1V124E48V19R15X29	-10.000	.000	25.000	.000	BREF 936.6800	INCHES
(AF8043)	CA119A B61C11F2MS1V124E49V19R15X29	-10.000	.000	25.000	.000	XREF 1076.4800	INCHES
(AF8016)	CA119A B61C11F2MS1V124E48V19R15X29	-20.000	.000	25.000	.000	ZREF 0.0000	INCHES
(AF8047)	CA119A B61C11F2MS1V124E51V19R15X29	-20.000	.000	25.000	.000	SCALE .0405	SCALE



PITCHING MOMENT COEFFICIENT, CLM

FIG 20 EFFECT OF WING/ELEVON GAP ON ELEVON EFFECTIVENESS, ELEVON = 0, -10, -20
 (A)MACH = .26 PAGE 166



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPDBRK	AILRON	REFERENCE INFORMATION
AL8004	9A119A 361015 2051 24E48 9915X23	.000	.000	25.000	.000	300.0100 SQ.FT
AL8005	9A119A 361015 2051 24E48 9915X23	.000	.000	25.000	.000	475.8100 SQ.FT
AL8006	9A119A 361015 2051 24E48 9915X23	.000	.000	25.000	.000	930.6500 SQ.FT
AL8007	9A119A 361015 2051 24E48 9915X23	.000	.000	25.000	.000	2000.0000 SQ.FT
AL8008	9A119A 361015 2051 24E48 9915X23	.000	.000	25.000	.000	4000.0000 SQ.FT
AL8009	9A119A 361015 2051 24E48 9915X23	.000	.000	25.000	.000	8000.0000 SQ.FT
AL8010	9A119A 361015 2051 24E48 9915X23	.000	.000	25.000	.000	16000.0000 SQ.FT
AL8011	9A119A 361015 2051 24E48 9915X23	.000	.000	25.000	.000	32000.0000 SQ.FT
AL8012	9A119A 361015 2051 24E48 9915X23	.000	.000	25.000	.000	64000.0000 SQ.FT
AL8013	9A119A 361015 2051 24E48 9915X23	.000	.000	25.000	.000	128000.0000 SQ.FT
AL8014	9A119A 361015 2051 24E48 9915X23	.000	.000	25.000	.000	256000.0000 SQ.FT
AL8015	9A119A 361015 2051 24E48 9915X23	.000	.000	25.000	.000	512000.0000 SQ.FT
AL8016	9A119A 361015 2051 24E48 9915X23	.000	.000	25.000	.000	1024000.0000 SQ.FT
AL8017	9A119A 361015 2051 24E48 9915X23	.000	.000	25.000	.000	2048000.0000 SQ.FT
AL8018	9A119A 361015 2051 24E48 9915X23	.000	.000	25.000	.000	4096000.0000 SQ.FT
AL8019	9A119A 361015 2051 24E48 9915X23	.000	.000	25.000	.000	8192000.0000 SQ.FT
AL8020	9A119A 361015 2051 24E48 9915X23	.000	.000	25.000	.000	16384000.0000 SQ.FT




FIG 20 EFFECT OF WING/ELEVON GAP ON ELEVON EFFECTIVENESS, ELEVON = 0, -10, -20
 (A)MACH = .26 PAGE 167



DATA SET SYMBOL CONFIGURATION DESCRIPTION
 [AF8004] CA119A B6C1F1 275 V124E18V19R15X29
 [AF8002] CA119A B6C1F1 275 V124E18V19R15X29
 [AF8007] CA119A B6C1F1 275 V124E18V19R15X29
 [AF8013] CA119A B6C1F1 275 V124E18V19R15X29
 [AF8016] CA119A B6C1F1 275 V124E18V19R15X29
 [AF8017] CA119A B6C1F1 275 V124E18V19R15X29

ELEVON BOFLAP SPOBRN AILRON REFERENCE INFORMATION
 .000 .000 25.000 .000 2690.0100 SQ.FT.
 .000 .000 25.000 .000 474.6100 IN.CHS
 -10.000 .000 25.000 .000 936.6800 IN.CHS
 -20.000 .000 25.000 .000 576.4800 IN.CHS
 -20.000 .000 25.000 .000 375.0000 IN.CHS
 -20.000 .000 25.000 .000 SCALE .0405 SCALE




FIG 20 EFFECT OF WING/ELEVON GAP ON ELEVON EFFECTIVENESS, ELEVON = 0, -10, -20

(A)MACH = .26

PAGE 168

DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOE LAP	SPDBRK	AIRLON	REFERENCE INFORMATION
AF8004	0A119A 861C11E1251V124E48V19R15X29	.000	.000	25.000	.000	SREF 2690.0100 SQ.FT.
AF8002	0A119A 861C11E1251V124E48V19R15X29	.000	.000	25.000	.000	L REF 474.8100 L.CES
AF8007	0A119A 861C11E1251V124E48V19R15X29	-10.000	.000	25.000	.000	Y REF 936.6800 Y.CES
AF8003	0A119A 861C11E1251V124E48V19R15X29	-10.000	.000	25.000	.000	X REF 1076.4800 X.CES
AF8005	0A119A 861C11E1251V124E48V19R15X29	-20.000	.000	25.000	.000	Z REF 375.0000 Z.CES
AF8001	0A119A 861C11E1251V124E48V19R15X29	-20.000	.000	25.000	.000	TURP SCALE
						SCALE .0405




FIG 20 EFFECT OF WING/ELEVON GAP ON ELEVON EFFECTIVENESS, ELEVON = 0, -10, -20
 (A)MACH = .26 PAGE 169

LONGITUDINAL CENTER OF PRESSURE LOCATION, XCP/L

DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AF8004) 0A119A B61C11F12MS1V124E48V19R15X29
 (AF8042) 0A119A B61C11F12MS1V124E48V19R15X29
 (AF8027) 0A119A B61C11F12MS1V124E48V19R15X29
 (AF8043) 0A119A B61C11F12MS1V124E48V19R15X29
 (AF8016) 0A119A B61C11F12MS1V124E48V19R15X29
 (AF8047) 0A119A B61C11F12MS1V124E51V19R15X29

ELEVON BOFLAP SPDCRA ALLRON REFERENCE INFORMATION
 .000 .000 25.000 .000 SREF 2690.0100 50. FT.
 .000 .000 25.000 .000 LREF 474.8100 INCHES
 -10.000 .000 25.000 .000 XMRP 936.6800 INCHES
 -10.000 .000 25.000 .000 YMRP 1075.4800 INCHES
 -20.000 .000 25.000 .000 ZMRP 375.0000 INCHES
 -20.000 .000 25.000 .000 SCALE .0405 SCALE




FIG 20 EFFECT OF WING/ELEVON GAP ON ELEVON EFFECTIVENESS, ELEVON 0, -10, -20

(A)MACH = .26

PAGE 170

DATA SET SYMBOL CONFIGURATION DESCRIPTION

(AF8012)	Q	3A119A	36	C11E	2-5	V124E18V	98	15X29
(AF8046)	X	3A119A	36	C11E	2-5	V124E18V	98	15X29
(AF8006)	X	3A119A	36	C11E	2-5	V124E18V	98	15X29
(AF8015)	X	3A119A	36	C11E	2-5	V124E18V	98	15X29

ELEVON

-30.000	BDCLAP	SPOBRK	A1LRON	SREF	2690.0100	SO.FT.
-20.000	.000	25.000	.000	LREF	474.8100	INCHES
-10.000	.000	25.000	.000	BREF	936.6800	INCHES
-40.000	.000	25.000	.000	XMPP	1076.4800	INCHES
				ZMPP	375.0000	INCHES
				SCALE	.0405	SCALE





FIG 21 EFFECT OF WING/ELEVON GAP ON ELEVON EFFECTIVENESS, ELEVON = -30, -40
 (A)MACH = .26
 PAGE 171



DATA SET SYMBOL CONFIGURATION DESCRIPTION

(AF8012)	CA119A	BB1C11F	275	V124E48V	SR15X29
(AF8046)	CA119A	BB1C11F	275	V124E51V	SR15X29
(AF8006)	CA119A	BB1C11F	275	V124E48V	SR15X29
(AF8045)	CA119A	BB1C11F	275	V124E51V	SR15X29

ELEVON BDFLAP SPOBRK AIRION

-30.000	.000	.000	.000
-30.000	.000	.000	.000
-40.000	.000	.000	.000
-40.000	.000	.000	.000

REFERENCE INFORMATION

SREF	2690.0100	SO, FT
LREF	474.8100	INCHES
BREF	936.6800	INCHES
ZMRP	1076.4800	INCHES
ZMRP	375.0000	INCHES
SCALE	.0405	SCALE




FIG 21 EFFECT OF WING/ELEVON GAP ON ELEVON EFFECTIVENESS, ELEVON = -30, -40
 (A)MACH = .26 PAGE 172



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPDRK	AILERON	REFERENCE INFORMATION
(AF8012)	0A119A 36(C)1F12M5V124E48V19R15X29	-30.000	.000	25.000	.000	SREF 2890.0100 50.FT.
(AF8046)	CA119A 36(C)1F12M5V124E51V19R15X29	-30.000	.000	25.000	.000	LREF 474.8100 INCHES
(AF8006)	CA119A 36(C)1F12M5V124E48V19R15X29	-40.000	.000	25.000	.000	BREF 836.6800 INCHES
(AF8045)	CA119A 36(C)1F12M5V124E51V19R15X29	-40.000	.000	25.000	.000	XPRP 1076.1800 INCHES
						YPRP 375.0000 INCHES
						ZPRP 375.0000 INCHES
						SCALE .0405 SCALE




FIG 21 EFFECT OF WING/ELEVON GAP ON ELEVON EFFECTIVENESS, ELEVON = -30, -40
 (A)MACH = .26 PAGE 173

DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BD/LAP	SPDRBK	A/LRON	REFERENCE INFORMATION
(AF8012)	GA119A 861C11F12751V124E48V19R15X29	-30.000	.000	25.000	.000	SREF 2690.0100 SQ.FT.
(AF8046)	GA119A 861C11F12751V124E51V19R15X29	-30.000	.000	25.000	.000	LREF 874.8100 INCHES
(AF8006)	GA119A 861C11F12751V124E48V19R15X29	-40.000	.000	25.000	.000	BREF 936.6600 INCHES
(AF8045)	GA119A 861C11F12751V124E51V19R15X29	-40.000	.000	25.000	.000	XMRP 1076.4800 INCHES
						ZMRP .0000 INCHES
						SCALE 375.0000 INCHES
						SCALE .0405

BASE AXIAL FORCE COEFFICIENT, CAB




FIG 21 EFFECT OF WING/ELEVON GAP ON ELEVON EFFECTIVENESS, ELEVON = -30, -40



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPOBRK	AIRLRN	REFERENCE INFORMATION
{ AF8012 }	CA119A 96 C11F 2-5 V124E48V 9A15X29	-30.000	.000	25.000	.000	7690.0100 SQ.FT.
{ AF8046 }	CA119A 96 C11F 2-5 V124E51V 9A15X29	-30.000	.000	25.000	.000	474.8100 NCLES
{ AF8006 }	CA119A 96 C11F 2-5 V124E48V 9A15X29	-40.000	.000	25.000	.000	936.6800 NCLES
{ AF8045 }	CA119A 96 C11F 2-5 V124E51V 9A15X29	-40.000	.000	25.000	.000	1076.4800 NCLES
						375.0000 NCLES
						SCALE .0400





FIG 21 EFFECT OF WING/ELEVON GAP ON ELEVON EFFECTIVENESS, ELEVON = -30, -40
 (A)MACH = .26 PAGE 175

DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BUFLAP	SFCGRK	ALLROD	REFERENCE INFORMATION
(AF8012)	CA119A B61C11F 2MS1V124E4BVI SR1SX29	-30.000	.000	25.000	.000	SREF 2690.0100 SQ.FT.
(AF8046)	CA119A B61C11F 2MS1V124E51V SR1SX29	-30.000	.000	25.000	.000	LREF 474.8100 INCHES
(AF8006)	CA119A B61C11F 2MS1V124E4BVI SR1SX29	-40.000	.000	25.000	.000	BREF 936.6800 INCHES
(AF8045)	CA119A B61C11F 2MS1V124E51V SR1SX29	-40.000	.000	25.000	.000	XTRP 1076.4800 INCHES
						YTRP .0000 INCHES
						ZTRP .0000 INCHES
						SCALE .0405



PITCHING MOMENT COEFFICIENT, CLM

FIG 21 EFFECT OF WING/ELEVON GAP ON ELEVON EFFECTIVENESS, ELEVON = -30, -40 (A)MACH = .26 PAGE 176



DATA SET SYMOL CONFIGURATION DESCRIPTION

[AF8012]	Q	BA119A	B61C11F125	V124E49	9915X29
[AF8016]	X	BA119A	B61C11F125	V124E51V	9915X29
[AF8036]	X	CA119A	B61C11F125	V124E49	9915X29
[AF8045]	X	CA119A	B61C11F125	V124E51V	9915X29

ELEVON BOFLAP SPOBRK AILRON REFERENCE INFORMATION

-30.000	.000	25.000	.000	SREF	2650.0100	SO.LFT.
-30.000	.000	25.000	.000	LREF	174.8100	LC-ES
-40.000	.000	25.000	.000	BREF	936.6800	LC-ES
-40.000	.000	25.000	.000	YREF	1076.4800	LC-ES
				ZREF	375.0000	LC-ES
				SCALE	.0105	SCALE




FIG 21 EFFECT OF WING/ELEVON GAP ON ELEVON EFFECTIVENESS, ELEVON = -30, -40
 (M)MACH = .26 PAGE 177

DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPDBRK	A TLON	REFERENCE INFORMATION
(AF8012)	0A119A B61C1 F12 S1V 24E48V SR 5X29	-30.000	.000	25.000	.000	SREF 2690.0100 SO.FY.
(AF8046)	0A119A B61C1 F12 S1V 24E51V SR 5X29	-30.000	.000	25.000	.000	LREF 474.8100 INCHES
(AF8006)	0A119A B61C1 F12 S1V 24E48V SR 5X29	-40.000	.000	25.000	.000	SREF 936.6800 INCHES
(AF8045)	0A119A B61C1 F12 S1V 24E51V SR 5X29	-40.000	.000	25.000	.000	XPRP 1076.4600 INCHES
						ZMRP .0000 INCHES
						SCALE .0405 SCALE




FIG 21 EFFECT OF WING/ELEVON GAP ON ELEVON EFFECTIVENESS, ELEVON = -30, -40
 (A)MACH = .26



REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR

DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPOBRK	ALLRON	REFERENCE INFORMATION
(AF8012)	GA119A B61C F1251V124E48V19R15X29	-30.000	.000	25.000	.000	SREF 2690.0100 SQ.FT.
(AF8045)	GA119A B61C F1251V124E51V19R15X29	-30.000	.000	25.000	.000	LREF 474.8100 INCHES
(AF8008)	GA119A B61C F1251V124E48V19R15X29	-40.000	.000	25.000	.000	BREF 938.6800 INCHES
(AF8045)	GA119A B61C F1251V124E51V19R15X29	-40.000	.000	25.000	.000	YMPD 1076.4800 INCHES
						ZMPD 375.0000 INCHES
						SCALE .0405



LIFT/FOREBODY DRAG RATIO, L/D

FIG 21 EFFECT OF WING/ELEVON GAP ON ELEVON EFFECTIVENESS, ELEVON = -30, -40
 (A) MACH = .26 PAGE 179



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPDBRK	AIIIRON	REFERENCE INFORMATION
{AF8012}	GA119A B61C1F12MS1V124E48V19815X29	-31.000	.000	29.000	.000	SREF 2690.0100 SO.FT.
{AF8046}	GA119A B61C1F12MS1V124E51V19815X29	-31.000	.000	29.000	.000	LREF 474.8100 NO.EG
{AF8006}	GA119A B61C1F12MS1V124E48V19815X29	-49.000	.000	29.000	.000	BREF 936.6800 NO.EG
{AF8045}	GA119A B61C1F12MS1V124E51V19815X29	-49.000	.000	29.000	.000	XMRP 1076.4800 NO.EG
						YMRP .0007 NO.EG
						ZMRP .0007 NO.EG
						SCALE .0425 SCALE

LONGITUDINAL CENTER OF PRESSURE LOCATION, XCP/L




FIG 21 EFFECT OF WING/ELEVON GAP ON ELEVON EFFECTIVENESS, ELEVON = -30, -40
 (A)MACH = .26 PAGE 180



DATA SET SYMBOL CONFIGURATION DESCRIPTION

(AF8009) □ 0A119A B61C11F12MS1V124E46V19R15X29

(AF8044) □ 0A119A B61C11F12MS1V124E50V19R15X29

ELEVON BOFLAP SPOBRK AIRTRON

-40.000 .000 25.000 .000

-40.000 .000 25.000 .000

REFERENCE INFORMATION

SREF 2690.0100 SQ.FT.

LREF 4.48100 INCHES

BREF 936.6600 INCHES

XMRP 1076.4800 INCHES

YMRP .0000 INCHES

ZMRP 375.0000 INCHES

SCALE .0405 SCALE





FIG 22 EFFECT OF ELEVON HINGELINE ROUGHNESS

(A)MACH = .26

DATA SET SYMBOL (AF8009) (AF8044) 6
 CONFIGURATION DESCRIPTION 8A119A B6C11F 275 V124E6V 9R15X23
 8A119A B6C11F 275 V124E5V 9R15X23

ELEVON BDELAP SPOBRK ALLRON
 -40.000 .000 75.000 .000
 -40.000 .000 75.000 .000

REFERENCE INFORMATION
 SREF 2690.0100 SQ.FT.
 LREF 474.8100 INCHES
 BREF 936.6800 INCHES
 XMRP 1076.4800 INCHES
 ZMRP 375.0000 INCHES
 SCALE .0405 SCALE



NORMAL FORCE COEFFICIENT, CN

FIG 22 EFFECT OF ELEVON HINGELINE ROUGHNESS

(A)MACH - .26

PAGE 162



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPOBRK	AILRON	REFERENCE INFORMATION
(AF8009)	0A119A B6 C1 F1 MS V124E46V19R15X29	-40.000	.000	25.000	.000	SREF 2690.0170 SO.FT.
(AF8044)	0A119A B6 C1 F1 MS V124E50V19R15X29	-40.000	.000	25.000	.000	REF 474.8110 INCHES
						BREF 336.6600 INCHES
						YMRP 1076.4800 INCHES
						ZMRP .0000 INCHES
						SCALE 375.0000 INCHES
						SCALE .0400




FIG 22 EFFECT OF ELEVON HINGELINE ROUGHNESS

(A)MACH = .26

DATA SET SYMBOL (AF8009) (AF8044) □

CONFIGURATION DESCRIPTION

0A119A B61C11F12M51V124E46V19R15X29
 0A119A B61C11F12M51V124E50V19R15X29

ELEVON BOFLAP SPUBRK AILRON SREF 2690.0100 SO.FT.
 -40.000 .000 .000 424.8100 INCHES
 -40.000 .000 .000 936.6800 INCHES
 XMRP 1076.4800 INCHES
 YMRP .0000 INCHES
 ZMRP 375.0000 INCHES
 SCALE .0405 SCALE

REFERENCE INFORMATION

BASE AXIAL FORCE COEFFICIENT, CAB




FIG 22 EFFECT OF ELEVON HINGELINE ROUGHNESS

(A)MACH = .26



DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AF8009) Q 0A119A 861C1F12751V124E16V1SR15X29
 (AF8014) Q 0A119A 861C1F12751V124E50V1SR15X29

ELEVON BOFLAP SPOBRK AILRON REFERENCE INFORMATION
 -40.000 .000 25.000 .000 SREF 2690.0100 SQ.FT.
 -40.000 .000 25.000 .000 LREF 474.8100 INCHES
 XMRP .000 .000 .000 BRPF 936.6800 INCHES
 YMRP .000 .000 .000 XMRP 1076.4800 INCHES
 ZMRP .000 .000 .000 YMRP .0000 INCHES
 SCALE .0405 SCALE 375.0000 INCHES




FIG 22 EFFECT OF ELEVON HINGELINE ROUGHNESS

(A)MACH = .26


DATA SET SYMBOL (AF8009) (AF8044) □

CONFIGURATION DESCRIPTION

0A119A B61C11F12M5:V124E46V19R15X29
 0A119A B61C11F12M5:V124E50V19R15X29

ELEVON BOFLAP SPARK AIRION
 -40.000 .000 25.000 .000
 -40.000 .000 25.000 .000


REFERENCE INFORMATION
 SREF 2690.0100 SQ.FT.
 LREF 474.8100 INCHES
 BREF 936.6800 INCHES
 XMRP 1076.4800 INCHES
 YMRP .0000 INCHES
 ZMRP 375.0000 INCHES
 SCALE .0405 SCALE



PITCHING MOMENT COEFFICIENT, CLM

FIG 22 EFFECT OF ELEVON HINGELINE ROUGHNESS

(M)MACH = .26



DATA SET SYMBOL: (AF8009) (AF8044)

CONFIGURATION DESCRIPTION: DA119A 861C11F12451V124E46V19R15X29
 DA119A 861C11F12451V124E50V19R15X29

ELEVON: -40.000
 BOFLAP: .000
 SPOBRK: 25.000
 AILRON: .000

REFERENCE INFORMATION:
 SREF: 3690.0100 SQ.FT.
 LREF: 414.8100 INCHES
 BREF: 936.6800 INCHES
 VREF: 1076.4800 INCHES
 WREF: 375.0000 INCHES
 SCALE: .0105 SCALE




FIG 22 EFFECT OF ELEVON HINGELINE ROUGHNESS

(A) MACH = .26

DATA SET SYMBOL: (AF8009) (AF8014)

CONFIGURATION DESCRIPTION: GA119A B61C1F12M51V124E46V19Z: XZ9 GA119A B61C1F12M51V124E50V19R15Y29

ELEVON: -40.0000
-40.0000

SOFLAP: .000
.000

SPUBRY: .000
.000

AIRFO: .000
.000

REFERENCE INFORMATION:
SREF: 2690.0100 50. FT.
LREF: 474.8100 INCHES
BREF: 936.6800 INCHES
XMRP: 1076.4800 INCHES
YMRP: .0000 INCHES
ZMRP: 375.0000 INCHES
SCALE: .0405





FIG 22 EFFECT OF ELEVON WINGLINE ROUGHNESS

(A)MACH = .26



DATA SET SYMBOL CONFIGURATION DESCRIPTION REFERENCE INFORMATION

(AF8009)	0A119A B61C1F12751V124E46V19R15X29	SREF 2690.0100 SQ.FT
(AF8044)	0A119A B61C1F12751V124E50V19R15X29	LREF 4.48100 INCHES
		BREF 936.6800 INCHES
		XMRP .0764800 INCHES
		YMRP .0000 INCHES
		ZMRP 375.0000 INCHES
		SCALE .0405 SCALE




LIFT/FOREBODY DRAG RATIO, L/DF

FIG 22 EFFECT OF ELEVON HINGELINE ROUGHNESS

(A)MACH = .26

DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AF8009) B 0A119A B61C1F12M51V124E46V1SR15X29
 (AF8044) B 0A119A B61C1F12M51V124E50V1SR15X29

ELEVON REF. AP SP. CLARK N. L. ROY REFERENCE INFORMATION
 -10.000 .000 25.000 .000 SREF 3690.0110 50. FT.
 -40.000 .000 25.000 .000 LREF 474.8100 INCHES
 BREF 936.6800 INCHES
 XMRP 1076.4800 INCHES
 YMRP .0000 INCHES
 ZMRP 375.0000 INCHES
 SCALE .10X05 SCALE



LONGITUDINAL CENTER OF PRESSURE LOCATION, XCP/L

FIG 22 EFFECT OF ELEVON HINGELINE ROUGHNESS

(A)MACH = .26

PAGE 190



DATA SET SYMBOL CONFIGURATION DESCRIPTION REFERENCE INFORMATION

DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPOBRK	AILRON	SREF	SCALE
(AF8004)	CA119A 96C11F 25 V124E18V 9615X29	.000	.000	25.000	.000	.590	.0100
(AF8075)	CA119A 96C11F 25 V124E18V 9615X29	.000	.000	25.000	.000	474.8100	1.00E5
(AF8075)	CA119A 96C11F 25 V124E18V 9615X29	15.000	-12.000	25.000	.000	936.6800	1.00E5
(AF8075)	CA119A 96C11F 25 V124E18V 9615X29	15.000	-12.000	25.000	.000	176.4800	1.00E5
(AF8075)	CA119A 96C11F 25 V124E18V 9615X29	15.000	-12.000	25.000	.000	375.0000	1.00E5
(AF8075)	CA119A 96C11F 25 V124E18V 9615X29	15.000	-12.000	25.000	.000	375.0000	1.00E5




FIG 23 BODY FLAP EFFECTIVENESS

(A)MACH = .26

DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	50FLAP	SPUSK	AILRON	REFERENCE INFORMATION
(AF8004)	0A119A B61C1F12MS1V124E48V19R15X29	.000	.000	20.000	.000	2690.0100 SQ. FT.
(AF8005)	0A119A B61C1F12MS1V124E48V19R15X29	.000	-12.000	20.000	.000	474.8100 IN. CL
(AF8030)	0A119A B61C1F12MS1V124E48V19R15X29	15.000	.000	20.000	.000	936.6800 IN. CL
(AF8036)	0A119A B61C1F12MS1V124E48V19R15X29	15.000	-12.000	20.000	.000	1076.4800 IN. CL
						375.0000 IN. CL
						SCALE .0405





FIG 23 BODY FLAP EFFECTIVENESS

(A)MACH = .26



DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPOBRK	AILRON	REFERENCE INFORMATION
(AF8004)	GA119A 861C11F 2-5 V124E48V19R15X29	.000	.000	25.000	.000	SREF 2690.0100 SO.FT.
(AF8053)	GA119A 861C11F 2-5 V124E48V19R15X29	.000	-12.000	25.000	.000	LREF 474.8100 INCHES
(AF8050)	GA119A 861C11F 2-5 V124E48V19R15X29	15.000	.000	25.000	.000	BREF 926.6800 INCHES
(AF8055)	GA119A 861C11F 2-5 V124E48V19R15X29	15.000	-2.000	25.000	.000	XREF 1076.4800 INCHES
					YREF .0000 INCHES	ZREF 375.0000 INCHES
					SCALE .0405	SCALE



FOREBODY AXIAL FORCE COEFFICIENT, CAF

FIG 23 BODY FLAP EFFECTIVENESS

CA)MACH = .26

DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPDRK	AILERON	REFERENCE INFORMATION
[AF8004]	CA119A B6C1F12MSV124E48V19R15X29	.000	.000	25.000	.000	SREF 2690.0100 SQ.FT. INCHES
[AF8005]	CA119A B6C1F12MSV124E48V19R15X29	.000	-12.000	25.000	.000	LREF 474.6100 INCHES
[AF8050]	CA119A B6C1F12MSV124E48V19R15X29	15.000	.000	25.000	.000	BREF 936.6800 INCHES
[AF8056]	CA119A B6C1F12MSV124E48V19R15X29	5.000	-12.000	25.000	.000	XMRP 1076.4800 INCHES
						YMRP .0000 INCHES
						ZMRP 375.0000 INCHES
						SCALE .0405 INCHES





FIG 23 BODY FLAP EFFECTIVENESS

(M)MACH = .26

DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPOBRK	AIRLON	REFERENCE INFORMATION
(AF8004)	DA119A 86:CI:F:2:S:V:24E48V:9R:15X:29	.000	.000	25.000	.000	SREF 2890.0:00 SO:FT:
(AF8055)	DA119A 86:CI:F:2:S:V:24E48V:9R:15X:29	.000	-12.000	25.000	.000	LREF 414.8:00 INCHES
(AF8050)	DA119A 86:CI:F:2:S:V:24E48V:9R:15X:29	15.000	.000	25.000	.000	BREF 936.6800 INCHES
(AF8056)	DA119A 86:CI:F:2:S:V:24E48V:9R:15X:29	15.000	-12.000	25.000	.000	YREF 1076.4800 INCHES
						ZREF .0000 INCHES
						SCALE 375.0000 INCHES
						SCALE .0405



FOREBODY DRAG COEFFICIENT, CDF

FIG 23 BODY FLAP EFFECTIVENESS

(A)MACH = .26

DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPOBRK	AILRON	REFERENCE INFORMATION
(AF8004)	0A119A B61C1F12M5V124E48V19R15X29	.000	.000	25.000	.000	SREF 2690.0100 SO.FT.
(AF8055)	0A119A B51C1F12M5V124E48V19R15X29	.000	-12.000	25.000	.000	LREF 474.8100 INCHES
(AF8050)	0A119A B61C1F12M5V124E48V19R15X29	15.000	.000	25.000	.000	BREF 836.6800 INCHES
(AF8056)	0A119A B61C1F12M5V124E48V19R15X29	15.000	-12.000	25.000	.000	YMRP 1076.4800 INCHES
					ZMRP .0000 INCHES	SCALE
						.0105




FIG 23 BODY FLAP EFFECTIVENESS

(A)MACH = .26

DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPOBRK	AILRON	REFERENCE INFORMATION
(AF8004)	0A119A B61C11F12S1V124E48V19R15X29	.00	.000	25.000	.000	SREF 2690.0100 SQ.FT.
(AF8005)	0A119A B61C11F12S1V124E48V19R15X29	.000	-12.000	25.000	.000	LREF 474.19100 INCHES
(AF8030)	0A119A B61C11F12S1V124E48V19R15X29	15.000	.000	25.000	.000	BREF 936.6800 INCHES
(AF8056)	0A119A B61C11F12S1V124E48V19R15X29	15.000	-12.000	25.000	.000	XMRP 1076.4800 INCHES
						ZMRP .0000 INCHES
						SCALE 375.0000
						SCALE .0405




FIG 23 BODY FLAP EFFECTIVENESS

(A)MACH = .26

DATA SET SYMBOL	CONFIGURATION DESCRIPTION	ELEVON	BOFLAP	SPOBRK	AILERON	SREF	LREF	BREF	XREF	YREF	ZREF	SCALE	REFERENCE INFORMATION
: AF8004)	0A119A B61C1F12M5 V124E18V 9R15X29	.000	.000	25.000	.000	2690.0100	474.8100	936.6800	1076.4900	0.000	0.000	.0405	SO.FT. INCHES
: AF8015)	0A119A B61C1F12M5 V124E18V 9R15X29	.000	-12.000	25.000	.000								INCHES
: AF8020)	0A119A B61C1F12M5 V124E18V 9R15X29	15.000	.000	25.000	.000								INCHES
: AF8036)	0A119A B61C1F12M5 V124E18V 9R15X29	15.000	-12.000	25.000	.000								INCHES




FIG 23 BODY FLAP EFFECTIVENESS


(A)MACH = .26

DATA SET SYMBOL CONFIGURATION DESCRIPTION

(AE8004)	Q	CA119A	B6 C F12~S V 24E48V 9R 5X29
(AE8055)	X	CA119A	B6 C F12~S V 24E48V 9R 5X29
(AE8050)	X	CA119A	B6 C F12~S V 24E48V 9R 5X29
(AE8056)	X	CA119A	B6 C F12~S V 24E48V 9R 5X29

ELEVON BDFLAP SPDBRK AILRON REFERENCE INFORMATION

.000	.000	25.000	.000	SREF	2690.0100	50. FT.
.000	.000	25.000	.000	LREF	474.8100	INCHES
15.000	-12.000	25.000	.000	BREF	936.6800	INCHES
15.000	-12.000	25.000	.000	VREF	1076.8600	INCHES
				ZMRP	.0000	INCHES
				ZMRP	375.0000	INCHES
				SCALE	.0405	SCALE




LIFT/FOREBODY DRAG RATIO, L/DF

FIG 23 BODY FLAP EFFECTIVENESS

(M)MACH = .26

DATA SET SYMBOL CONFIGURATION DESCRIPTION
 (AF8004) O119A B61C11F121S1V124E48V1SR1SX29
 (AF8055) O119A B61C11F121S1V124E48V1SR1SX29
 (AF8050) O119A B61C11F121S1V124E48V1SR1SX29
 (AF8056) O119A B61C11F121S1V124E48V1SR1SX29

ELEVON BOFLAP SPOBRK AILRON REFERENCE INFORMATION
 SREF 2690.0100 SQ.FT.
 LREF 474.8100 INCHES
 BREF 836.6800 INCHES
 XMRP 1076.4800 INCHES
 YMRP .0000 INCHES
 ZMRP 375.0000 INCHES
 SCALE .0405 SCALE



LONGITUDINAL CENTER OF PRESSURE LOCATION, XCP/L

FIG 23 BODY FLAP EFFECTIVENESS

(A)MACH = .26

APPENDIX
TABULATED SOURCE DATA

Tabulations of plotted data are available on request from
Data Management Services

(RF0001) (09 JUL 74)

GALL19A 061C11F12H51W12E46V19R15120

REFERENCE DATA

XREF = 2690.0100 86.FT. ZMRP = 1070.4000 INCHES
 YREF = 474.8100 INCHES YMRP = .0000 INCHES
 ZREF = 936.8900 INCHES ZMRP = 375.0000 INCHES
 SCALE = .0408 SCALE

PARAMETRIC DATA

BETA = .000 DDFLAP = .000
 ELEVOM = .000 AILFOM = .000
 RUDDER = .000 SPOBRK = 23.000

RUN NO 1 / 0 RN/L = 1.05 GRADIENT INTERVAL = -6.00/ 6.00

MACH	ALPHA	CL	CLM	CM	CAF	CYN	CBL	CT	KCP/L	CAB
.260	-10.670	-.55120	.03310	-.56120	.00140	-.00060	.00040	-.00100	-.67500	.04112
.260	-8.340	-.44330	.03370	-.43120	.00833	-.00060	.00010	.00000	-.67900	.04163
.260	-6.390	-.33490	.03140	-.33840	.01196	-.00040	.00020	.00000	-.64600	.04073
.260	-4.270	-.23080	.03390	-.23260	.01662	-.00030	.00030	.00000	-.69400	.04033
.260	-2.140	-.13320	.02660	-.13410	.02190	-.00050	.00040	.00100	-.72700	.04012
.260	-.090	-.03830	.02830	-.03830	.02341	-.00050	.00030	.00100	-.90400	.03977
.260	2.070	.05830	.02350	.05910	.02140	-.00050	.00030	.00100	-.49100	.03911
.260	4.210	.13880	.02600	.13730	.01455	-.00060	.00040	.00200	-.39300	.03494
.260	6.300	.25350	.03260	.25560	.00456	-.00030	.00030	.00400	-.61700	.03937
.260	8.440	.33740	.04500	.34010	-.00793	-.00070	.00030	.00400	-.62400	.03459
.260	10.580	.45750	.06240	.46120	-.02263	-.00090	.00020	.00500	-.63100	.03947
.260	12.710	.56350	.08790	.56910	-.03830	-.00090	.00000	.00600	-.63400	.04152
.260	14.850	.67760	.12340	.68660	-.05435	-.00090	.00000	.00700	-.63800	.04314
.260	17.010	.81030	.17320	.82560	-.07149	-.00110	.00000	.00900	-.64600	.04592
.260	19.170	.92820	.23150	.95270	-.08621	-.00100	-.00110	.01000	-.64900	.04827
.260	21.340	1.03600	.30100	1.07450	-.09677	.00010	-.00090	.01000	-.64900	.05159
.260	23.480	1.14950	.39320	1.21100	-.09745	.00030	-.00100	.01000	-.65300	.05631
.260	25.600	1.20270	.47030	1.26790	-.09359	.00060	-.00070	.01400	-.65000	.06120
GRADIENT		.04537	-.00090	.04596	-.00022	-.00001	.00001	.00019	-.02110	-.00020

REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR

GA119A 861C11F12M51W12E48V19R1329

(RF0004) (09 JUL 74)

REFERENCE DATA

BRZF = 2690.0100 30.FT. ZMRP = 1076.4000 INCHES
 LBZF = 474.0100 INCHES YMRP = .0000 INCHES
 BRZF = 936.0000 INCHES ZMRP = 373.0000 INCHES
 SCALE = .0403 SCALE

PARAMETRIC DATA

BETA = .000 BOFLAP = .000
 ELEVGM = .000 ALLEGM = .000
 RUDDER = .000 SPOBER = 23.000

RUN NO. 4 / 0 RN/L = 1.85 GRADIENT INTERVAL = -6.00/ 6.00

MACH	ALPHA	CL	CLM	CLN	CAF	CYN	CBL	CT	ACP/L	CAB
.260	-10.640	-.33340	.10310	.03630	-.56330	.00107	-.00050	-.00100	.67300	-.04144
.260	-8.310	-.44480	.07410	.03500	-.45090	.00749	-.00030	-.00100	.69000	.04081
.260	-6.370	-.33480	.04960	.03250	-.33630	.01217	-.00040	.00000	.64700	.04079
.260	-4.230	-.23040	.03370	.02990	-.23230	.01660	-.00030	.00000	.69900	.04086
.260	-2.140	-.13220	.02720	.02790	-.13320	.02230	-.00060	.00000	.72900	.03969
.260	-.030	-.03620	.02340	.02690	-.03620	.02339	-.00060	.00100	.92300	.03946
.260	2.090	.03920	.02350	.02650	.06010	.02136	-.00060	.00100	.44900	.03903
.260	4.220	.15670	.02630	.02610	.15430	.01479	-.00070	.00300	.59100	.03868
.260	6.320	.23480	.03350	.02470	.23700	.00531	-.00080	.00300	.61600	.03776
.260	8.450	.35620	.04530	.02410	.36090	-.00763	-.00090	.00500	.62700	.03451
.260	10.570	.43890	.06230	.02670	.46250	-.02287	-.00100	.00600	.63000	.04003
.260	12.740	.56500	.06870	.02800	.57060	-.03904	-.00110	.00600	.63400	.04131
.260	14.870	.67900	.12410	.02560	.64910	-.05432	-.00110	.00700	.63400	.04329
.260	17.030	.81370	.17480	.01490	.62920	-.07124	-.00100	.00400	.64300	.04341
.260	19.210	.93120	.23360	.01040	.95630	-.08563	-.00110	.01000	.64900	.04403
.260	21.340	1.03600	.30200	.00750	1.07690	-.09645	.00000	.00900	.64900	.03121
.260	23.330	1.13420	.39630	-.00640	1.21720	-.09540	.00030	.01000	.65400	.03620
.260	25.620	1.20710	.47400	.00390	1.29340	-.09463	.00050	.01400	.65000	.06044
GRADIENT	.04561	-.00067	-.00042	-.00042	.04603	-.00022	-.00004	.00033	-.02154	-.00024



(RF0003) (09 JUL 74)

GALL19A 061C11F12M:1W124E7V19R132D

REFERENCE DATA

REF = 2690.0100 SQ.FT. RMRP = 1076.4800 INCHES
 LREF = 474.0100 INCHES TMRP = .0000 INCHES
 BREF = 936.0000 INCHES ZMRP = 375.0000 INCHES
 SCALE = .0405 SCALE

PARAMETRIC DATA

BETA = .000 BDFLAP = .000
 ELEVOM = -40.000 AIRFCM = .000
 FUODER = .000 SPODBR = 23.000

RUN NO. 5/0 RML = 1.05 GRADIENT INTERVAL = -6.00/ 6.00

MACH	ALPHA	CL	CLM	CN	CAF	CYM	CBL	CY	KCP/L	CAB
.260	-11.090	-98810	.29860	-1.02710	.10290	.00160	.00240	-.00600	.73100	.04037
.260	-9.970	-90640	.25010	-.93430	.10356	.00060	-.00230	-.00700	.74200	.03756
.260	-8.630	-81090	.21070	-.83020	.11270	.00010	.00020	-.00300	.75300	.03750
.260	-4.700	-70040	.17340	-.71230	.11542	-.00040	-.00030	-.00400	.76900	.03739
.260	-2.390	-58240	.14390	-.58830	.11744	-.00030	-.00230	-.00400	.78600	.03775
.260	-.430	-46620	.12120	-.46720	.11768	.00040	-.00040	-.00400	.81200	.03794
.260	3.420	-23960	.08390	-.23340	.10104	-.00020	-.00070	-.00100	.83000	.03660
.260	5.920	-16500	.07770	-.15610	.09434	-.00050	-.00110	.00000	1.10400	.03793
.260	9.040	-.07220	.07370	-.06090	.08512	-.00070	-.00130	.00100	1.82100	.03915
.260	10.140	.02160	.07670	-.03540	.07366	-.00080	-.00150	.00200	-1.40900	.03981
.260	12.310	.11700	.06700	.13290	.06010	-.00080	-.00120	.00400	.04400	.04144
.260	14.440	.21030	.10600	.23760	.04819	-.00070	-.00140	.00600	.33200	.04236
.260	16.370	.32480	.13240	.34910	.03422	-.00050	-.00110	.00300	.43200	.04362
.260	18.690	.41260	.16840	.44490	.02732	.00000	-.00110	.00600	.47300	.04724
.260	20.830	.49470	.21330	.53820	.02339	-.00030	-.00320	.01000	.49700	.05067
.260	23.010	.61930	.27610	.67400	.01204	-.00090	-.00990	.01200	.53300	.05357
.260	25.130	.70310	.33360	.79010	.00256	-.00340	-.00490	.00300	.54900	.05363
GRADIENT	.03026	-.00902	-.00323	.05216	-.00223	-.00001	.00000	.00042	.02970	.00007

PARAMETRIC DATA

BETA = .000 SDFLAP = .000
ELEVGM = -40.000 ALLGCM = .000
RUDDER = .000 SPOSRK = 25.000

REFERENCE DATA

REF = 2890.0100 30.FT. AMRP = 1076.4000 INCHES
LREF = 474.8100 INCHES YMRP = .0000 INCHES
BREF = 936.8000 INCHES ZMRP = 375.0000 INCHES
SCALE = .0405 SCALE

RUN NO. 6 / 0 RN/L = 1.05 GRADIENT INTERVAL = -6.00/ 6.00

MACH	ALPHA	CL	CLM	CM	CAF	CYN	CBL	CT	ACP/L	CAP
.260	-11.140	-.99190	.29750	-1.03070	.10036	.00070	.00350	-.00300	.73100	.04034
.260	-9.030	-.91800	.25160	-.94610	.10449	-.00060	-.00240	-.00100	.74300	.03633
.260	-6.990	-.82530	.21260	-.84480	.11209	-.00040	-.00040	-.00100	.75500	.03620
.260	-4.750	-.71420	.23170	-.72620	.11437	-.00010	-.00010	-.00200	.76900	.03556
.260	-2.630	-.59950	.22110	-.60380	.11493	-.00040	-.00120	-.00100	.78400	.03591
.260	-.440	-.48270	.11650	-.48370	.11246	-.00050	-.00090	-.00200	.81200	.03696
.260	1.630	-.37400	.09860	-.37100	.10928	-.00040	-.00030	-.00100	.85200	.03692
.260	3.760	-.26540	.08410	-.25930	.10143	-.00070	-.00010	.00100	.92400	.03769
.260	5.920	-.16990	.07760	-.16090	.09479	-.00040	-.00020	.00000	1.09600	.03642
.260	7.990	-.07630	.07450	-.06720	.08469	-.00040	-.00020	.00100	1.73100	.03430
.260	10.140	.01220	.07790	-.02370	.07434	-.00060	-.00010	.00300	-2.23400	.03971
.260	12.270	.08700	.08700	.12410	.06206	-.00070	-.00000	.00500	.03700	.04031
.260	14.390	.10360	.10360	.22960	.04433	-.00090	-.00160	.00600	.31400	.04300
.260	16.530	.13150	.13150	.34270	.03535	-.00050	-.00040	.00600	.42300	.04500
.260	18.670	.16620	.16620	.44160	.02618	-.00060	-.00100	.00400	.46900	.04696
.260	20.760	.40020	.20700	.52950	.02037	.00000	.00000	.00400	.49100	.05024
.260	22.920	.56410	.25560	.61920	.01592	.00260	.00240	.00500	.50400	.05431
.260	25.030	.63710	.30320	.70560	.00516	.00330	.00240	.00000	.52500	.05640
GRADIENT		.03137	-.00956	.03331	-.00190	-.00004	.00005	.00023	.02414	.00013



(RF8009) (09 JUL 74)

GA119A 861C.1F12H31M124E48V19R15X29

SREF = 2690.0100 SQ.FT. XMRP = 1076.4800 INCHES
 LREF = 474.8100 INCHES YMRP = .0000 INCHES
 BREF = 936.6400 INCHES ZMRP = 375.0000 INCHES
 SCALE = .0400 SCALE

BETA = .000 BDFLAP = .000
 ELEVON = -40.000 AIRCRN = .000
 RUDDER = .000 SPDBEK = 25.000

PARAMETRIC DATA

RUN NO. 9/ 0 RN/L = 1.65 GRADIENT INTERVAL = -6.00/ 6.00

MACH	ALPHA	CL	CDF	CLM	CN	CAF	CYN	CBL	CY	XCP/L	CAB
.260	-11.120	-.99170	.29870	.22280	-1.03070	.10187	.00130	.00400	-.00400	.73100	.04063
.260	-9.010	-.92080	.25410	.23520	-.94930	.10664	.00000	-.00240	-.00300	.74300	.03631
.260	-6.900	-.82460	.21140	.23740	-.84400	.11083	-.00080	-.00090	-.00100	.75500	.03603
.260	-4.740	-.71160	.17300	.23000	-.72330	.11363	-.00050	-.00110	-.00100	.76900	.03602
.260	-2.600	-.59880	.14300	.22120	-.60470	.11565	-.00080	-.00190	-.00100	.74600	.03624
.260	-.450	-.48040	.11630	.20960	-.48140	.11313	-.00060	-.00170	-.00200	.41200	.03664
.260	1.670	-.36770	.09830	.19970	-.36470	.10905	-.00050	-.00120	-.00100	.45300	.03644
.260	3.790	-.25990	.08460	.19230	-.25370	.10166	-.00090	-.00090	.00000	.93100	.03733
.260	5.900	-.16660	.07770	.19310	-.15770	.09445	-.00060	-.00070	.00100	1.10200	.03779
.260	8.010	-.07740	.07610	.19810	-.06610	.08616	-.00060	-.00070	.00100	1.74400	.03743
.260	10.140	.01370	.07680	.20160	.02730	.07522	-.00040	-.00070	.00200	-2.03700	.03940
.260	12.280	.10900	.08730	.20710	.12520	.06228	-.00020	-.00040	.00300	.04300	.04116
.260	14.390	.21060	.10400	.21080	.22960	.04939	-.00100	-.00160	.00600	.31400	.04331
.260	16.510	.31690	.13030	.21190	.34100	.03510	-.00070	-.00170	.00700	.42300	.04596
.260	18.660	.41210	.16800	.21920	.44420	.02730	-.00030	-.00110	.00400	.47100	.04757
.260	20.830	.49340	.20940	.22890	.53750	.01960	.00030	-.00010	.00400	.49500	.05036
.260	22.910	.57220	.25670	.23890	.62700	.01364	.00760	.00220	.00500	.51100	.05427
.260	25.010	.64340	.30600	.24140	.71430	.00440	.00430	.00260	.00000	.52700	.05584
	GRADIENT	.05175	-.00901	-.00378	.05369	-.00190	-.00001	.00007	.00019	.02470	.00017

DATE 22 OCT 74

TABULATED SOURCE DATA - CA119A

PAGE 6

CA119A 861C11F12M51W124E48V19R15X29

(RF6010) (09 JUL 74)

REFERENCE DATA

SREF = 2690.0100 SQ.FT. XMRP = 1076.4800 INCHES
 LREF = 474.8100 INCHES YMRP = .0000 INCHES
 BRP = 938.6800 INCHES ZMRP = 375.0000 INCHES
 SCALE = .0403 SCALE

PARAMETRIC DATA

BETA = .000 BDFLAP = .000
 ELEVOM = -30.000 AILFOM = .000
 RUDDER = .000 SFDBFK = 25.000

RUN NO. 10 / 0 RW/L = 1.63 GRADIENT INTERVAL = -6.00 / 6.00

MACH	ALPHA	CL	COF	CLM	CN	CAF	CYN	CBL	CY	KCP/L	CAP
.280	-11.130	-.99810	.26860	.22830	-1.03120	.07085	-.00140	.00720	.00000	.73300	.03694
.280	-8.990	-.90640	.22040	.23330	-.92970	.07390	-.00060	.00160	.00000	.74300	.03355
.280	-6.840	-.79210	.17810	.23150	-.80770	.06246	-.00120	-.00040	.00000	.75700	.03257
.280	-4.700	-.66220	.14300	.22550	-.69160	.06661	-.00130	-.00110	.00000	.77200	.03366
.280	-2.560	-.55020	.11340	.20920	-.55470	.06864	-.00160	-.00220	.00000	.79200	.03425
.280	-.430	-.44200	.09420	.20190	-.44270	.09090	-.00150	-.00040	.00100	.82000	.03505
.280	1.670	-.34330	.06130	.19910	-.34090	.09142	-.00110	.00190	.00200	.86700	.03534
.280	3.900	-.24230	.07040	.19510	-.23710	.08641	-.00060	.00230	.00000	.95400	.03594
.280	5.930	-.15020	.06480	.19840	-.14270	.09092	-.00060	.00240	.00000	1.15400	.03521
.280	8.040	-.05990	.06220	.19950	-.05060	.07001	-.00070	.00210	.00200	2.10300	.03655
.280	10.160	.03250	.06570	.20420	.04380	.05894	-.00080	.00130	.00300	-1.06900	.03724
.280	12.290	.12650	.07340	.21060	.13920	.04477	-.00070	.00160	.00300	-.09300	.03945
.280	14.400	.21410	.08730	.21990	.22910	.03130	-.00090	.00170	.00400	.29900	.04115
.280	16.510	.30720	.11030	.22700	.32590	.01844	-.00060	.00140	.00400	.39300	.04349
.280	18.650	.40490	.14230	.23210	.42920	.00339	-.00120	.00040	.00700	.45300	.04616
.280	20.790	.46140	.18010	.24580	.51400	-.00249	-.00090	.00110	.00400	.47600	.04414
.280	22.930	.58500	.23240	.24830	.62930	-.01393	.00010	.00000	.00400	.50400	.04971
.280	25.040	.68310	.29270	.24110	.74280	-.02444	.00240	-.00120	.01000	.53200	.05355
.280	GRADIENT	.04953	-.00717	-.00253	.05110	-.00052	.00009	.00046	.00001	.03319	.00014



DATE 22 OCT 74 TABULATED SOURCE DATA - GALL19A

(IRF9011) (09 JUL 74)

GALL19A 861C11F12M51W124E47V19R15X29

REFERENCE DATA

BREF = 2690.0100 SQ.FT. XMRP = 1070.4800 INCHES
 LREF = 474.6100 INCHES YMRP = .0000 INCHES
 SREF = 938.8800 INCHES ZMRP = 375.0000 INCHES
 SCALE = .0405 SCALE

PARAMETRIC DATA

BETA = .000 BOFLAP = .000
 ELEVON = -30.000 ALLRCH = .000
 RUDDER = .000 SPODBK = 25.000

RUN NO. 11/ 0 RN/L = 1.05 GRADIENT INTERVAL = -6.00/ 6.00

MACH	ALPHA	CL	CDF	CLM	CN	CAF	CYN	CBL	CY	XCP/L	CAB
.260	-11.120	-.99330	.26680	.22780	-1.02850	.07217	-.00150	-.00490	.00100	.73300	.03697
.260	-9.990	-.90360	.22150	.23350	-.92750	.07745	-.00050	.00050	.00000	.74500	.03365
.260	-6.840	-.79250	.17910	.23230	-.80820	.06332	-.00120	-.00110	.00100	.75700	.03355
.260	-4.730	-.68590	.14590	.22850	-.69860	.06870	-.00100	-.00070	.00000	.77200	.03345
.260	-2.590	-.56940	.11810	.21930	-.57410	.09223	-.00070	-.00000	.00000	.79200	.03457
.260	-.420	-.44060	.09480	.20210	-.44130	.09155	-.00120	-.00040	.00100	.82000	.03561
.260	1.710	-.33480	.08110	.19630	-.33230	.09115	-.00090	-.00040	.00000	.86900	.03574
.260	3.610	-.23860	.07080	.19330	-.23150	.08650	-.00090	-.00030	.00100	.93900	.03659
.260	5.910	-.14540	.06500	.19470	-.13800	.07966	-.00040	-.00000	.00100	1.17100	.03594
.260	8.060	-.05230	.06420	.19740	-.04270	.07095	-.00070	-.00010	.00000	2.35000	.03543
.260	10.160	.03800	.06640	.20260	.04910	.05866	-.00030	-.00000	.00000	2.46300	.03759
.260	12.300	.12790	.07540	.21100	.14100	.04641	-.00040	.00040	.00000	1.0100	.03926
.260	14.410	.22560	.09090	.21520	.24120	.03191	-.00100	-.00040	.00000	.32300	.04172
.260	16.340	.31920	.11380	.22330	.33840	.01815	-.00070	-.00030	.00000	.40900	.04373
.260	18.670	.41420	.14720	.22860	.43950	.00642	-.00090	-.00140	.00000	.46000	.04510
.260	20.800	.49090	.18540	.24260	.52440	-.00100	-.00070	-.00170	.01000	.48200	.04754
.260	22.940	.59210	.23720	.24370	.63740	-.01235	.00000	-.00150	.01000	.51100	.04967
.260	25.090	.68870	.29790	.23900	.75000	-.02231	.00000	-.00270	.01100	.53400	.05314
GRADIENT	.05115	-.00753	-.00336	-.00336	.05275	-.00094	.00001	-.00004	.00000	.03406	.00021

(RF0012) (09 JUL 74)

GA119A 861C11F12M51W124E40V19R15X29

REFERENCE DATA

SREF = 2490.0100 SQ.FT. XMRP = 1076.4000 INCHES
 LREF = 474.8100 INCHES YMRP = .0000 INCHES
 BREF = 936.8000 INCHES ZMRP = 375.0000 INCHES
 SCALE = .0400 SCALE

PARAMETRIC DATA

BETA = .000 BDFLAP = .000
 ELEVON = -30.000 ALLFON = .000
 RUDDER = .000 SPUBRK = 25.000

RUN NO. 12/ 0 RN/L = 1.85 GRADIENT INTERVAL = -6.00/ 6.00

MACH	ALPHA	CL	CLM	CLN	CAF	CYN	CBL	CT	XCP/L	CAB
.260	-11.120	-.99910	.26760	-1.03200	.06978	-.00010	.00390	-.00100	.73400	-.03644
.260	-9.000	-.91190	.22180	-.93330	.07636	-.00040	-.00040	-.00200	.74500	.03357
.260	-6.850	-.79720	.17880	-.81290	.08244	-.00070	-.00130	-.00100	.75900	-.03232
.260	-4.720	-.69050	.14490	-.70010	.08736	-.00060	-.00130	-.00200	.77200	.03324
.260	-2.580	-.56750	.11850	-.57220	.09100	-.00050	-.00040	-.00100	.79100	-.03377
.260	-.400	-.44730	.09530	-.44900	.09217	-.00060	-.00100	.00000	.82 J	.03454
.260	1.670	-.34420	.08070	-.34170	.09077	-.00010	.00040	.00000	.86000	-.03334
.260	3.610	-.24560	.07060	-.24050	.08685	-.00010	.00050	.00000	.93200	.03531
.260	5.930	-.15520	.06440	-.14770	.08014	-.00020	.00060	.00000	1.14400	-.03526
.260	6.030	-.06610	.06220	-.05660	.07087	-.00030	.00030	.00100	1.93700	.03643
.260	10.180	.02440	.06350	.03560	.06014	-.00050	-.00010	-.00300	-1.48200	-.03694
.260	12.260	.11390	.07270	.12670	.04689	-.00060	.00030	.00400	.02900	.03450
.260	14.390	.20810	.08710	.22320	.03270	-.00070	.00000	.00500	.24400	-.04034
.260	16.520	.30760	.11060	.32630	.01962	-.00070	-.00090	.00600	.39700	.04302
.260	18.640	.39720	.14110	.42150	.00670	-.00080	-.00120	.00700	.48400	-.04500
.260	20.810	.47680	.17920	.51120	-.00261	-.00030	-.00160	.00800	.47500	.04732
.260	22.930	.56000	.22820	.62310	-.01581	.00040	-.00110	.00900	.50600	-.05000
.260	25.090	.67640	.28950	.73720	-.02531	.00270	-.00340	.01100	.53100	.05339
.260	GRADIENT	.03032	-.00746	-.00302	-.00064	.00005	.00014	.00021	.03206	-.00021



0A119A 061C11F12M51M124E48V19819320

(RFB013) (09 JUL 74)

REFERENCE DATA

SREF = 2000.0100 80-FT. XMRP = 1076.4800 INCHES
 LREF = 474.8100 INCHES XMRP = .0000 INCHES
 BREF = 938.8800 INCHES XMRP = 373.0000 INCHES
 SCALE = .0405 SCALE

BETA = .000 8DFLAP = .000
 ELEVON = -20.000 AILPON = .000
 RUDDER = .000 SPDRK = 23.000

RUN NO. 13/ D RM/L = 1.85 GRADIENT INTERVAL = -0.00/ 0.00

PARAMETRIC DATA

MACH	ALPHA	CL	CLM	CN	CAF	CIN	CBL	CI	XCP/L	CAB
.280	-11.040	-.92430	.21730	-.94890	.03023	-.00060	-.00010	-.00100	.72900	.02976
.280	-6.930	-.84930	.17390	-.86800	.03993	-.00060	.00010	.00000	.74200	.03102
.280	-6.790	-.74480	.13470	-.75330	.04376	-.00060	.00000	.00000	.75500	.03209
.280	-4.630	-.61690	.10170	-.62310	.05163	-.00020	.00090	-.00100	.77000	.03299
.280	-2.530	-.51290	.07780	-.51370	.05486	.00020	.00110	-.00100	.79100	.03229
.280	-.390	-.40340	.05810	-.40390	.05337	-.00030	.00020	.00000	.82300	.03303
.280	1.730	-.30290	.04600	-.30140	.05323	-.00030	.00020	.00000	.87600	.03298
.280	3.860	-.19320	.03660	-.17950	.05176	-.00030	.00180	.00000	.99900	.03223
.280	5.990	-.10490	.03430	-.10080	.04515	-.00090	.00040	.00100	1.31600	.03173
.280	8.120	-.00830	.03410	-.00340	.03497	-.00090	.00040	.00200	20.31800	.03271
.280	10.210	.08200	.03900	.09050	.02330	-.00080	.00050	.00300	-.10600	.03359
.280	12.350	.18360	.04630	.18970	.00793	-.00070	.00060	.00400	.27800	.03743
.280	14.490	.29250	.06930	.30060	-.00384	-.00070	.00090	.00300	.41900	.03942
.280	16.610	.40990	.10080	.42160	-.02061	-.00060	.00100	.00300	.48600	.04191
.280	18.790	.53080	.14340	.54870	-.03513	-.00040	.00120	.00700	.52600	.04367
.280	20.940	.63130	.19060	.63770	-.04756	-.00040	.00030	.00900	.54500	.04634
.280	23.100	.74700	.25320	.78720	-.05847	.00040	.00170	.00900	.56500	.04784
.280	25.270	.82180	.31870	.87920	-.06261	.00290	.00300	.00300	.57400	.03184
GRADIENT	.04869	-.00626	-.00167	.04964	-.00036	-.00006	-.00001	.00017	.04596	-.00009

REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR

DATE 22 OCT 74 TABULATED SOURCE DATA - CA119A

(RF0016) (09 JUL 74)

CA119A 061C11F12H51M124E48V13R13X29

PARAMETRIC DATA

BETA = .000 BDFLAP = .000
 ELEVON = -20.000 AILEVN = .000
 RUDDER = .000 SPOBCK = 23.000

REFERENCE DATA

SREF = 2690.0100 SQ.FT. XMRP = 1076.4800 INCHES
 LREF = 474.8100 INCHES YMRP = .0000 INCHES
 BRP = 936.6800 INCHES ZMRP = 375.0000 INCHES
 SCALE = .0405 SCALE

RUN NO. 16/ 0 RN/L = 1.65 GRADIENT INTERVAL = -6.00/ 6.00

MACH	ALPHA	CL	CLM	CN	CAF	CYN	CBL	CT	XCP/L	CAP
.260	-11.040	-.92320	.21790	-.94990	.03656	-.00060	-.00030	-.00100	.72900	-.02953
.260	-8.930	-.85010	.17460	-.86890	.04050	-.00070	-.00000	.00000	.74200	.03073
.260	-6.760	-.74340	.13440	-.75400	.04598	-.00030	-.00010	-.00100	.75600	-.03191
.260	-4.640	-.61600	.10200	-.62230	.05181	-.00020	-.00070	-.00100	.77000	.03322
.260	-2.510	-.50370	.07740	-.50670	.05529	.00030	.00150	-.00200	.79200	-.03255
.260	-.390	-.40000	.05910	-.40040	.05641	-.00030	.00040	.00000	.82400	.03292
.260	1.730	-.30100	.04680	-.29950	.05595	-.00040	.00030	.00000	.87900	.03242
.260	3.850	-.20330	.03730	-.20040	.05089	-.00050	.00010	.00100	.99400	.03246
.260	5.960	-.10740	.03330	-.10330	.04451	-.00070	.00020	.00200	1.30100	.03162
.260	8.100	-.00990	.03400	-.00500	.03511	-.00060	-.00020	.00300	14.05400	.03206
.260	10.210	.08450	.03860	.09000	.02309	-.00070	.00020	.00400	-.11400	-.03342
.260	12.330	.18090	.04860	.18710	.00890	-.00060	.00040	.00500	.27200	.03665
.260	14.480	.28980	.06450	.29770	-.00612	-.00050	.00030	.00600	.41100	-.03954
.260	16.630	.41060	.10060	.42220	-.02109	-.00050	.00070	.00600	.44300	.04173
.260	18.790	.52970	.14280	.54750	-.03546	-.00060	.00100	.00700	.52300	.04404
.260	20.930	.62850	.19030	.65500	-.04675	-.00050	.00000	.00400	.54400	.04624
.260	23.090	.74700	.25520	.78720	-.05822	.00060	.00150	.00400	.56300	.04415
.260	25.240	.84150	.32710	.90060	-.06295	.00240	-.00160	.01100	.57900	.05194
	GRADIENT	.04775	-.00641	.04872	-.00067	-.00007	-.00009	.00032	-.04442	-.00010



PARAMETRIC DATA

BETA = .000 BOFLAP = .000
ELEVGM = -20.000 AIRCRN = .000
RUDDER = .000 SPOBRK = 25.000

REFERENCE DATA

SREF = 2690.0100 SQ.FT. XMRP = 1076.4800 INCHES
LREF = 474.8100 INCHES YMRP = .0000 INCHES
BREF = 936.6600 INCHES ZMRP = 375.0000 INCHES
SCALE = .0403 SCALE

RUN NO. 17/ 0 RN/L = 1.85 GRADIENT INTERVAL = -6.00/ 6.00

MACH	ALPHA	CL	CDF	CLM	CN	CAF	CYN	CBL	CY	KCP/L	CAB
.260	-11.030	-92510	.21760	.19920	-.94970	.03645	-.00070	-.00080	.00000	.72900	.03093
.260	-8.920	-84920	.17420	.21340	-.86390	.04044	-.00080	-.00020	.00000	.74200	.03143
.260	-6.800	-74670	.13660	.21370	-.75760	.04719	-.00060	-.00020	.00000	.75300	.03200
.260	-4.630	-62430	.10300	.20330	-.63060	.05221	-.00040	.00000	.00000	.77000	.03267
.260	-2.510	-51660	.07880	.19820	-.51930	.05614	.00000	.00180	-.00100	.79200	.03307
.260	-.360	-40630	.06060	.19090	-.40670	.05806	-.00070	.00000	.00000	.82400	.03297
.260	1.740	-30600	.04720	.18000	-.30440	.05639	-.00080	.00000	.00000	.89100	.03339
.260	3.860	-20680	.03830	.16580	-.20380	.05244	-.00080	.00000	.00100	.98100	.03265
.260	5.950	-10660	.03410	.16260	-.10230	.04502	-.00060	.00000	.00100	1.30800	.03124
.260	8.100	-01000	.03410	.16460	-.00310	.03523	-.00060	.00047	.00200	13.42100	.03193
.260	10.180	.08260	.03820	.16900	.06910	.02306	-.00070	.00000	.00400	-.13700	.03390
.260	12.320	.17880	.04830	.19420	.18310	.00922	-.00060	.00000	.00400	.26600	.03676
.260	14.450	.28740	.06800	.19620	.29330	-.00391	-.00050	.00040	.00500	.40700	.03989
.260	16.630	.40960	.10110	.19270	.42140	-.02033	-.00040	.00060	.00500	.49300	.04139
.260	18.770	.52720	.14110	.16910	.54460	-.03602	-.00050	.00000	.00700	.52400	.04479
.260	20.930	.62840	.19000	.19230	.63480	-.04709	-.00040	-.00000	.00800	.54300	.04629
.260	23.080	.74240	.25390	.16730	.78260	-.03730	.00000	.00150	.00700	.56400	.04793
.260	25.250	.84100	.32730	.17960	.90000	-.06265	.00290	-.00140	.01100	.57400	.05190
.260	GRADIENT	.04881	-.00647	-.00194	.04976	-.00065	-.00005	-.00010	.00015	.04485	-.00012

REPRODUCTION OF THIS ORIGINAL PAGE IS POOR

CAS119A 861C11F12M51W124E47V19R13X29

(RF9010) (09 JUL 74)

REFERENCE DATA

SREF = 2690.0100 80.FT. XMRP = 1076.4800 INCHES
 LREF = 474.8100 INCHES YMRP = .0000 INCHES
 BRFP = 936.6800 INCHES ZMRP = 375.0000 INCHES
 SCALE = .0405 SCALE

BETA = .000 9DFLAP = .000
 ELEVON = -15.000 ALLCON = .000
 RUDDER = .000 SPODRK = 25.000

PARAMETRIC DATA

RUN NO. 187 0 RN/L = 1.85 GRADIENT INTERVAL = -6.00/ 6.00

MACH	ALPHA	CL	CLM	CN	CAF	CYN	CBL	CY	XCP/L	CAP
.260	-10.970	-.65310	.16870	-.87510	.02072	-.00090	-.00030	.00000	.72300	-.03333
.260	-8.640	-.76230	.14440	-.77540	.02346	-.00090	.00000	.00000	.73500	-.03311
.260	-6.710	-.65910	.10930	-.66740	.03175	-.00090	.00000	.00000	.74900	-.03331
.260	-4.580	-.54800	.08060	-.55070	.03679	-.00030	.00040	.00000	.76400	.03366
.260	-2.430	-.43340	.05840	-.43530	.03965	-.00060	.00070	.00000	.77900	-.03363
.260	-.330	-.32870	.04440	-.32990	.04253	-.00040	.00040	.00000	.82900	.03395
.260	1.790	-.22820	.03430	-.22700	.04146	-.00090	.00030	.00100	.90200	-.03391
.260	3.920	-.13000	.02820	-.12780	.03705	-.00100	.00040	.00200	1.09200	.03399
.260	6.020	-.03250	.02620	-.02960	.02950	-.00090	.00050	.00200	2.54400	-.03337
.260	8.130	.06690	.02980	.07040	.02001	-.00090	.00040	.00300	-.14400	.03303
.260	10.280	.16290	.03590	.16680	.00629	-.00090	.00030	.00400	.30600	.03403
.260	12.410	.26580	.04990	.27030	-.00933	-.00070	.00030	.00500	.43400	.03935
.260	14.570	.38010	.07540	.36690	-.02265	-.00060	.00060	.00600	.50000	.04193
.260	16.720	.50110	.11030	.51170	-.03452	-.00090	.00010	.00700	.56500	.04414
.260	18.900	.62240	.15700	.63970	-.05309	-.00040	.00030	.00900	.57400	.04606
.260	21.030	.72690	.20990	.75560	-.06567	-.00070	.00170	.00900	.59300	.04847
.260	23.190	.84660	.28100	.86910	-.07518	.00200	.00240	.00600	.59600	.05307
.260	25.320	.91450	.34780	.97540	-.07673	.00200	.00024	.00024	.03621	.00004
.260	GRADIENT	.04863	-.00607	-.00166	.00010	-.00026	-.00002			



REFERENCE DATA

SREF = 2690.0100 SQ.FT. XMRP = 1076.4800 INCHES
 LREF = 474.8100 INCHES ZMRP = .0000 INCHES
 PREF = 936.6800 INCHES ZMRP = 375.0000 INCHES
 SCALE = .0405 SCALE

PARAMETRIC DATA

BETA = .000 BOFLAP = .000
 ELEVOM = -15.000 AIRLON = .000
 FUDDER = .000 SPDBRK = 25.000

RUN NO. 19/ 0 RN/L = 1.85 GRADIENT INTERVAL = -6.00/ 6.00

MACH	ALPHA	CL	CDF	CLM	CN	CAF	CYM	CBL	CY	KCP/L	CAB
.260	-10.970	-.85270	.16680	.16840	-.07270	.02113	-.00100	-.00040	.00000	.72300	.03342
.260	-8.830	-.76110	.14450	.17550	-.77430	.02596	-.00100	-.00010	.00000	.73500	.03306
.260	-6.700	-.65370	.10870	.17480	-.66390	.03146	-.00090	.00010	.00000	.74900	.03396
.260	-4.570	-.54580	.08050	.16820	-.55030	.03676	-.00060	.00030	.00000	.76400	.03345
.260	-2.440	-.43530	.05950	.16230	-.43740	.03993	-.00030	.00040	.00000	.78000	.03376
.260	-.310	-.32700	.04400	.15690	-.32720	.04223	-.00100	.00000	.00100	.82800	.03419
.260	1.600	-.22730	.03430	.15410	-.22610	.04153	-.00100	.00010	.00200	.90300	.03421
.260	3.920	-.12840	.02850	.15240	-.12620	.03729	-.00100	.00020	.00200	1.09600	.03396
.260	6.040	-.03130	.02610	.15190	-.02830	.02933	-.00090	.00020	.00300	2.62100	.03365
.260	8.170	.06720	.02930	.15290	.07070	.01953	-.00090	.00020	.00300	-1.14300	.03349
.260	10.280	.16410	.03560	.15680	.16780	.00372	-.00040	.00010	.00400	.30400	.03641
.260	12.410	.26390	.05030	.15990	.27050	-.00402	-.00070	.00000	.00400	.43400	.03749
.260	14.570	.37930	.07560	.15940	.38610	-.02216	-.00260	.00000	.00600	.50000	.03927
.260	16.720	.50350	.11140	.15370	.51430	-.03819	-.00070	.00030	.00700	.58200	.04141
.260	18.890	.62290	.15690	.15040	.64020	-.05319	-.00040	.00010	.00700	.56300	.04403
.260	21.030	.72980	.20990	.13100	.75630	-.06607	-.00030	-.00030	.00900	.57400	.04646
.260	23.220	.85060	.28260	.14150	.89320	-.07564	.00070	.00140	.00400	.59300	.04446
.260	25.310	.91620	.34830	.14320	.97720	-.07691	.00210	.00250	.00600	.59700	.03237
.260	GRADIENT	.04914	-.00604	-.00188	.04995	.00013	-.00006	-.00002	.00024	.03669	.00002

REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR.

(RF0020) (09 JUL 74)

GAT119A B01C11F12M31W124E46V19R15X29

REFERENCE DATA


SREF = 2690.0100 SQ.FT. XMRP = 1076.4800 INCHES
 LREF = 474.8100 INCHES YMRP = .0000 INCHES
 BREF = 936.6800 INCHES ZMRP = 375.0000 INCHES
 SCALE = .0405 SCALE

BETA = .000 BDFLAP = .000
 ELEVCON = -15.000 AIRLCON = .000
 RUDDER = .000 SPDEFK = 25.000

PARAMETRIC DATA

RUN NO. 20/ 0 RN/L = 1.85 GRADIENT INTERVAL = -6.00/ 6.00

MACH	ALPHA	CL	CLM	CN	CAF	CYM	CSL	CY	XCP/L	CAP
.260	-10.970	-.84840	-.16660	-.86820	.02105	-.00110	-.00090	.00000	.72200	.03392
.260	-8.840	-.75740	.17330	-.77060	.02376	-.00110	-.00040	.00000	.73400	.03373
.260	-6.700	-.65280	.10850	-.66100	.03152	-.00090	-.00010	.00000	.74800	.03448
.260	-4.580	-.54350	.08060	-.54820	.03693	-.00070	.00000	.00000	.76400	.03427
.260	-2.460	-.43240	.16110	-.43460	.04043	-.00070	.00060	.00000	.78400	.03393
.260	-.300	-.32550	.15590	-.32570	.04301	-.00110	.00020	.00200	.82400	.03409
.260	1.800	-.22520	.15290	-.22400	.04142	-.00110	.00030	.00200	.90300	.03504
.260	3.910	-.12800	.15170	-.12570	.03753	-.00120	.00040	.00200	1.05600	.03432
.260	6.050	-.03220	.15230	-.02920	.02864	-.00090	.00040	.00300	2.56700	.03339
.260	8.150	.06680	.15250	.07020	.01869	-.00100	.00040	.00400	-.14700	.02440
.260	10.280	.16260	.15620	.16650	.00846	-.00090	.00030	.00500	.30600	.03343
.260	12.420	.26550	.16020	.27010	-.00812	-.00090	.00010	.00500	.43300	.03743
.260	14.540	.37810	.15990	.36460	-.02260	-.00070	.00010	.00600	.49900	.03359
.260	16.710	.50290	.15370	.51320	-.03422	-.00060	.00060	.00700	.54100	.04149
.260	18.860	.62150	.15040	.63960	-.05344	-.00040	.00020	.00400	.56500	.04414
.260	21.060	.73020	.15040	.75690	-.06643	-.00030	-.00020	.00900	.57400	.04653
.260	23.180	.84990	.14180	.89190	-.07646	.00040	.00190	.00900	.59300	.04493
.260	25.300	.91650	.14570	.97740	-.07695	.00210	.00240	.00600	.59700	.05256
	GRADIENT	.74888	-.00192	.04970	.00011	-.00007	.00002	.00024	.03662	.00006



(RF9021) (09 JUL 74)

GAI19A B61C11F12M51M124E48V19R13Z29

REFERENCE DATA

SREF = 2890.0100 SQ.FT. XMRP = 1076.4800 INCHES
 LREF = 474.8100 INCHES YMRP = .0000 INCHES
 BREF = 936.6800 INCHES ZMRP = 375.0000 INCHES
 SCALE = .0403 SCALE

BETA = .000 BDFLAP = .000
 ELEVOM = 10.000 AILFOM = .000
 RUDDER = .000 SFDRBK = 25.000

RUN NO. 21/ 0 RM/L = 1.05 GRADIENT INTERVAL = -6.00/ 6.00

PARAMETRIC DATA

MACH	ALPHA	CL	CLM	CN	CAF	CTM	CBL	CY	KCP/L	CAB
.260	-10.490	-.35710	-.03710	-.36580	.01401	-.00030	.00910	-.00100	-.59400	.04603
.260	-8.350	-.25620	-.05650	-.26200	.02032	-.00020	.00060	.00000	.37200	.04579
.260	-6.230	-.15200	-.03750	-.15560	.02503	-.00040	.00030	.00000	.31600	.04574
.260	-4.080	-.05070	-.05870	-.05300	.02949	-.00060	.00000	.00000	.24400	.04517
.260	-1.990	-.04460	-.06020	.04350	.03394	-.00080	.00040	.00000	1.16100	.04441
.260	.120	.14100	-.06130	.14110	.03424	-.00080	.00090	.00100	.81200	.04413
.260	2.230	.23460	-.06200	.23600	.03099	-.00090	.00090	.00200	.74900	.04359
.260	4.360	.33400	-.06430	.33670	.02312	-.00110	.00050	.00400	.72200	.04324
.260	6.490	.44410	-.06970	.44840	.01259	-.00120	.00030	.00300	.70900	.04300
.260	8.620	.55200	-.07310	.55610	-.00107	-.00120	-.00020	.00600	.70000	.04364
.260	10.760	.66030	-.07460	.66930	-.01601	-.00120	.00070	.00700	.69300	.04601
.260	12.900	.77080	-.07510	.78340	-.03206	-.00090	.00030	.00700	.68400	.04737
.260	15.060	.88930	-.07940	.90690	-.04946	-.00090	-.00030	.00900	.68300	.04939
.260	17.230	1.02150	-.09020	1.04930	-.06511	-.00110	-.00030	.00900	.68000	.05264
.260	19.370	1.12720	-.09020	1.16700	-.07926	-.00130	-.00030	.00900	.67900	.05671
.260	21.540	1.22240	-.09360	1.29370	-.07729	-.00170	-.00170	.00600	.67900	.06264
.260	23.640	1.33150	-.10290	1.42030	-.07674	-.00180	-.00450	.02200	.67900	.06749
.260	25.780	1.36810	-.09270	1.49210	-.07723	-.00000	-.00360	.01500	.67200	.06749
.260	GRADIENT	.04547	-.00062	.04606	-.00075	-.00005	.00004	.00047	.02551	-.00024

CAL19A 861C11F12H51W12E40V19R15X29

(8F0024) (09 JUN 74)

REFERENCE DATA

SREP = 2680.0100 SQ.FT. YMRP = 1076.4800 INCHES
 LREF = 474.8100 INCHES YMRP = .0000 INCHES
 DREF = 936.8800 INCHES ZMRP = 379.0000 INCHES
 SCALE = .0005 SCALE

BETA = .000 SDFLAP = .000
 ELEVON = 10.000 AILEON = .000
 RUDDER = .000 SPOBER = 25.000

PARAMETRIC DATA

RUN NO. 24/ 0 EN/L = 1.85 GRADIENT INTERVAL = -6.00/ 6.00

MACH	ALPHA	CL	CDP	CLM	CN	CAF	CYN	CB-	CY	ACP/L	CAP
.260	-10.470	-1.35440	.07380	-.03410	-.36200	.00814	-.00020	.00030	-.00100	.59700	.04701
.260	-8.350	-.24370	.05190	-.03660	-.25060	.01573	-.00020	.00030	-.00100	.56400	.04677
.260	-6.180	-.13490	.03550	-.08050	-.13900	.02090	-.00030	.00070	.00000	.43000	.04651
.260	-4.110	-.03340	.02820	-.06340	-.03340	.02381	-.00070	.00060	.00000	.00000	.04591
.260	-1.330	.06610	.02750	-.06500	.06310	.02935	-.00030	.00040	.00000	1.01300	.04570
.260	.150	.16120	.03070	-.06620	.16130	.03026	-.00040	.00070	.00200	.40300	.04474
.260	2.250	.29750	.03610	-.06720	.25690	.02607	-.00080	.00070	.00200	.74400	.04470
.260	4.360	.35190	.04370	-.06450	.35440	.01885	-.00090	.00060	.00300	.72300	.04346
.260	6.490	.45330	.05930	-.07010	.45710	.00769	-.00090	.00060	.00400	.70400	.04335
.260	8.610	.55480	.07650	-.07090	.56030	-.00543	-.00100	.00060	.00500	.69400	.04354
.260	10.760	.65960	.10470	-.07050	.66760	-.02029	-.00110	.00070	.00600	.69100	.04433
.260	12.920	.77240	.13960	-.07270	.78410	-.03667	-.00130	.00030	.00700	.69600	.04614
.260	15.030	.88690	.18450	-.07610	.90830	-.05270	-.00150	.00060	.00900	.64300	.04769
.260	17.230	1.02080	.24470	-.06700	1.04740	-.06913	-.00150	.00010	.00900	.64200	.04932
.260	19.370	1.12790	.30930	-.04790	1.16860	-.08244	-.00160	-.00020	.01000	.67900	.05251
.260	21.530	1.22790	.39460	-.09250	1.29700	-.08360	-.00160	.00260	.00300	.67400	.05733
.260	23.690	1.33430	.49870	-.10270	1.42230	-.07931	-.00190	-.00420	.02200	.67400	.06343
.260	25.600	1.37710	.57720	-.06590	1.49110	-.07969	-.00010	-.00360	.01600	.67300	.06419
.260	GRADIENT	.04546	.00207	-.00059	.04599	-.00042	-.00003	-.00000	.00034	.05704	-.00024



DATE 22 OCT 74 TABULATED SOURCE DATA - GA119A

(RFA023) 09 JUL 74

GA119A 061C11F12M51W124E7V19R13X29

PARAMETRIC DATA

BETA = .000 90FLAP = .000
ELEVOM = 10.000 ALLGOM = .000
RUDDER = .000 SPODER = 25.000

REFERENCE DATA

WREF = 2890.0100 SQ.FT. WREF = 1076.4000 INCHES
LWREF = 474.0100 INCHES LWREF = .0000 INCHES
RWREF = 936.0000 INCHES RWREF = 375.0000 INCHES
SCALE = .0405 SCALE

RUN NO. 25/0 RW/L = 1.05 GRADIENT INTERVAL = -6.00/ 6.00

MACH	ALPHA	CL	CLM	CLN	CAF	CTN	CSL	CN	KCP/L	CAP
.260	-10.480	-.35160	-.05460	-.35930	.00901	-.00020	-.05030	-.00200	.59600	.04639
.260	-8.320	-.24290	-.03640	-.24790	-.01631	-.00010	-.05110	-.00100	.56400	.04591
.260	-6.160	-.13510	-.05940	-.13920	.02101	-.00050	-.00070	.00000	.49200	.04624
.260	-4.000	-.03090	-.06290	-.03270	-.02534	-.00060	-.00070	.00000	-.05300	.04613
.260	-1.960	.08400	-.06440	.06300	.02970	-.00070	-.00090	-.00100	1.02400	.04544
.260	1.140	.16130	-.06600	.16140	-.03020	-.00070	.00090	.00100	.40200	.04494
.260	2.240	.23770	-.06740	.25490	.02636	-.00090	-.00090	.00200	.74400	.04424
.260	4.410	.33440	-.04610	.35690	.01978	-.00090	.00070	.00300	.72300	.04396
.260	6.580	.45540	-.07100	.45970	.00794	-.00100	.00060	.00400	.70900	.04347
.260	8.650	.56190	-.07340	.56750	-.00373	-.00110	.00070	.00500	.69900	.04423
.260	10.600	.66890	-.07340	.67710	-.02029	-.00120	.00060	.00600	.69200	.04443
.260	12.910	.77660	-.07490	.78970	-.03616	-.00120	.00050	.00600	.64700	.04593
.260	15.110	.89770	-.07940	.91570	-.05230	-.00140	.00120	.00900	.64400	.04646
.260	17.250	1.02570	-.08910	1.05260	-.06921	-.00160	.00010	.00900	.64300	.05000
.260	19.400	1.13340	-.09970	1.17230	-.08316	-.00140	.00010	.01000	.64000	.05303
.260	21.530	1.22740	-.09290	1.29730	-.04174	.00170	.00290	.00400	.67400	.05619
.260	23.700	1.33570	-.10310	1.42440	-.07457	-.00200	-.00450	.02200	.67400	.06321
.260	25.810	1.37340	-.08320	1.48730	-.07935	-.00010	-.00330	.01600	.67200	.06426
.260	GRADIENT	.04556	-.05070	.04804	-.00079	-.00003	.00000	.00033	.05349	-.00026

0A119A B61C11F12M51W124E47V19R15Z0

(8F8028) (09 JUL 74)

REFERENCE DATA

SREF = 8090.0100 80. FT. IMPR = 1076.4800 INCHES
 LREF = 474.8100 INCHES IMPR = .0000 INCHES
 HREF = 936.8800 INCHES IMPR = 373.0000 INCHES
 SCALE = .0433 SCALE

PARAMETRIC DATA

BETA = .000 BDFLAP = .000
 ELEVON = -10.000 ATRON = .000
 BUDEP = .000 SPDEP = 25.000

RUN NO. 26 V 0 RWL = 1.65 GRADIENT INTERVAL = -6.00/ 6.00

MACH	ALPHA	CL	CLM	CLN	CAF	CFM	CBL	CT	KCP/L	CAB
.200	-10.800	-.78000	.12880	-.77840	.01003	-.00030	.00020	-.00200	.71300	.03543
.200	-8.720	-.65540	.13110	-.66940	.01500	-.00040	.00030	-.00100	.72400	.03527
.200	-6.350	-.53480	.08470	-.56070	.02033	.00000	.00020	-.00200	.73600	.03572
.200	-4.480	-.44400	.09030	-.44730	.02566	.00000	.00000	-.00200	.75400	.03565
.200	-2.320	-.33680	.04330	-.33810	.02965	-.00030	.00020	-.00100	.74300	.03587
.200	-.220	-.23670	.03310	-.23680	.03221	-.00050	.00010	.00000	.43400	.03580
.200	1.990	-.13840	.11320	-.13730	.03073	-.00030	.00030	.00000	.96000	.03372
.200	3.990	-.04240	.11470	-.04070	.02364	-.00030	.00030	.00030	1.64900	.03316
.200	6.130	.03800	.11440	.09910	.01709	-.00030	.00030	.00100	-.07100	.03502
.200	8.280	.15440	.11420	.13640	.00597	-.00060	.00040	.00200	.34400	.03528
.200	10.400	.23830	.04000	.11770	.00697	-.00060	.00020	.00300	.64300	.03620
.200	12.320	.36100	.03620	.11920	-.02139	-.00070	.00020	.00400	.33100	.03773
.200	14.870	.47320	.08610	.48130	-.03710	-.00060	.00030	.00300	.36100	.03994
.200	16.610	.60270	.12600	.61340	-.03365	-.00040	.00030	.00600	.34300	.04253
.200	18.990	.72290	.17640	.74090	-.04843	-.00060	.00000	.00400	.39900	.04502
.200	21.160	.83410	.23490	.86270	-.04217	-.00020	-.00040	.01000	.60700	.04763
.200	23.320	.93290	.31370	.99930	-.04911	.00090	.00200	.00400	.61700	.05044
.200	25.410	1.01110	.34410	1.06080	-.04639	.00120	.00230	.00900	.61400	.05334
GRADIENT	.04744	-.00436	-.00121	.04803	.00007	-.00008	.00073	.00024	.09643	-.00008



GALL19A 861C11F12H31M124E6V19R15X29

PARAMETRIC DATA

SREF = 2690.0100 SQ.FT. XMRP = 1076.4800 INCHES
 LREF = 474.8100 INCHES YMRP = .0000 INCHES
 BREF = 936.6800 INCHES ZMRP = 375.0000 INCHES
 SCALE = .0400 SCALE
 BETA = .000 BDFLAP = .000
 ELEVON = -10.000 ALLROM = .000
 RUDDER = .000 SPDSRK = 23.000

RUN NO. 21/0 RN/L = 1.85 GRADIENT INTERVAL = -6.07/ 6.00

MACH	ALPHA	CL	COF	CLM	CN	CAF	CYN	CBL	CY	XCP/L	CAB
.250	-3.860	-.76100	.15610	.12920	-.77680	.00985	-.00050	.00010	-.00100	.71300	-.03542
.250	-6.740	-.66000	.11590	.13110	-.66990	.01426	-.00030	.00000	-.00100	.72400	.03606
.260	-6.810	-.55500	.08500	.12900	-.56110	.02053	-.00020	.00000	-.00200	.73600	.03568
.260	-4.463	-.44390	.06070	.12480	-.44730	.02604	-.00030	.00000	-.00100	.73400	.03545
.260	-2.360	-.34000	.04390	.12060	-.34150	.02977	-.00040	.00010	.00000	.74200	.03520
.260	-.220	-.23600	.03290	.11700	-.23620	.03203	-.00060	.00020	.00000	.63400	.03534
.260	1.870	-.13750	.02670	.11510	-.13650	.03123	-.00070	.00020	.00000	.96200	.03507
.260	4.010	-.04060	.02280	.11470	-.03890	.02563	-.00070	.00020	.00100	1.73500	.03552
.260	6.120	.05640	.02360	.11490	.03860	.01764	-.00090	.00030	.00200	-.06400	.03414
.260	8.240	.15730	.02020	.11440	.15970	.00540	-.00090	.00040	.00300	.34400	.03561
.260	10.370	.25300	.03930	.11750	.23790	-.00717	-.00090	.00010	.00400	.44400	.03649
.260	12.490	.36060	.05740	.11930	.36450	-.02198	-.00090	.00030	.00500	.53100	.03407
.260	14.670	.47620	.08610	.11840	.48250	-.03729	-.00070	.00060	.00500	.56100	.03944
.260	16.340	.60570	.12640	.11020	.61640	-.05446	-.00090	.00050	.00700	.54600	.04295
.260	19.000	.72700	.17770	.10590	.74530	-.06870	-.00090	-.00010	.00900	.59900	.04437
.260	21.140	.83670	.23540	.10340	.86540	-.08226	-.00040	-.00050	.01000	.60400	.04797
.260	23.310	.95680	.31520	.09170	1.00350	-.09919	.00090	.00230	.00400	.61400	.05051
.260	25.430	1.01820	.38610	.08890	1.09530	-.08434	.00140	.00230	.00400	.61400	.05524
	GRADIENT	.04767	-.00439	-.00121	.04827	.00003	-.00003	.00002	.00019	.10130	.00000

GAI19A 861C11F12M51M124E48V19R13X29 (RF8030) (09 JUL 74)

REFERENCE DATA

SREF = 2690.0100 SQ.FT. XMRP = 1076.4800 INCHES
 LREF = 474.8100 INCHES YMRP = .0000 INCHES
 BRFF = 936.6800 INCHES ZMRP = 375.0000 INCHES
 SCALE = .0405 SCALE

BETA = .000 BDFLAP = .000
 ELEVON = -10.000 AILRCH = .000
 RUDDER = .000 SPO5BK = 25.000

PARAMETRIC DATA

RUN NO. 30/ 0 RN/L = 1.85 GRADIENT INTERVAL = -6.00/ 6.00

MACH	ALPHA	CL	CLM	CN	CAF	CYN	CEL	C*	XCP/L	CAB
.260	-10.670	-.75920	.13590	-.77500	.00981	-.00060	.00050	.00000	.71200	.03563
.260	-8.710	-.65650	.11370	-.66640	.01493	-.00030	-.00010	.00000	.72300	.03337
.260	-6.590	-.55150	.08450	-.55730	.02064	-.00030	.00000	-.00100	.73600	.03373
.260	-4.470	-.44240	.06060	-.44580	.02597	-.00020	.00000	-.00100	.75400	.03566
.260	-2.320	-.33400	.04290	-.33540	.02940	-.00030	.00020	.00000	.78300	.03552
.260	-.240	-.23440	.03270	-.23430	.03176	-.00060	.00000	.00000	.83400	.03560
.260	1.910	-.13540	.02600	-.13440	.03055	-.00060	.00030	.00100	.96400	.03553
.260	4.010	-.03950	.02330	-.03780	.02609	-.00060	.00040	.00100	1.75900	.03474
.260	6.100	-.05630	.02350	-.05850	.01744	-.00060	.00040	.00200	-.06400	.03470
.260	8.240	.15710	.02860	.15360	.00584	-.00070	.00030	.00300	.34900	.03539
.260	10.360	.25700	.03960	.25990	-.00736	-.00070	.00010	.00400	.44600	.03652
.260	12.500	.36220	.05780	.36610	-.02189	-.00030	.00010	.00400	.53200	.03793
.260	14.660	.47750	.08580	.48370	-.03789	-.00050	.00040	.00500	.62000	.04027
.260	16.830	.60760	.12690	.61830	-.05456	-.00090	.00070	.00700	.74600	.04273
.260	18.990	.72840	.17770	.74660	-.06931	-.00070	-.00010	.00400	.90000	.04515
.260	21.150	.83730	.23580	.86600	-.08221	-.00030	-.00060	.00900	.10900	.04744
.260	23.300	.95840	.31560	.99200	-.09330	.00090	.00240	.00700	.61400	.05064
.260	25.410	1.01830	.38650	1.08370	-.08799	.00140	.00240	.00400	.61400	.05512
GRADIENT		.04740	-.00432	.04800	.00007	-.00004	.00004	.00024	.10330	-.00004



GA119A B6TC11F12M51W124E46V19R15X29
 REFERENCE DATA
 SREF = 2690.0100 SQ.FT. XMRP = 1076.4800 INCHES BETA = .000 8DFLAP = .000
 LREF = 474.8100 INCHES YMRP = .0000 INCHES ELEVOM = -5.000 ALLRCH = .000
 BREF = 936.6900 INCHES ZMRP = 375.0000 INCHES RUDDER = .000 SPOBRK = 25.000
 SCALE = .0405 SCALE

PARAMETRIC DATA

RUN NO. 31 / 0 RN/L = 1.85 GRADIENT INTERVAL = -6.00/ 6.00

MACH	ALPHA	CL	CLM	CM	CAF	CYN	CBL	CY	XCP/L	CAB
.260	-10.770	-.63470	.12850	.08160	-.66710	.00387	.00040	-.00100	.69700	.03829
.260	-8.630	-.54950	.09270	.08120	-.53720	.00919	.00000	-.00100	.70500	.03859
.260	-6.500	-.44450	.06330	.07890	-.44900	.01435	.00030	-.00200	.71600	.03809
.260	-4.370	-.33550	.04490	.07620	-.33790	.01921	.00020	-.00100	.73500	.03800
.260	-2.240	-.23150	.03310	.07290	-.23260	.02410	.00050	.00000	.76700	.03755
.260	-1.120	-.13390	.02630	.07030	-.13400	.02609	.00020	.00000	.84500	.03730
.260	1.980	-.03670	.02330	.06970	-.03580	.02460	.00040	.00000	1.36700	.03690
.260	4.110	.05910	.02260	.06930	.08060	.01831	.00060	.00100	.22900	.03689
.260	6.250	.13750	.02860	.06910	.13950	.00959	.00060	.00200	.49200	.03590
.260	8.350	.26020	.03490	.06870	.26250	-.00327	.00070	.00300	.53500	.03696
.260	10.470	.35960	.04940	.07150	.36260	-.01678	.00070	.00400	.57900	.03796
.260	12.620	.46790	.07180	.07230	.47230	-.03212	.00070	.00500	.59500	.03964
.260	14.760	.56170	.10290	.07100	.58870	-.04868	.00060	.00500	.60700	.04201
.260	16.940	.71550	.14950	.06030	.72410	-.06345	.00090	.00700	.62100	.04419
.260	19.090	.83350	.20390	.05590	.83440	-.07997	.00100	.00900	.62400	.04640
.260	21.250	.94340	.26810	.05330	.97650	-.09210	.00010	.00900	.63200	.04901
.260	23.420	1.06090	.33590	.04000	1.11500	-.09327	.00050	.00900	.63400	.05337
.260	25.320	1.12230	.43190	.04980	1.19890	-.09388	.00140	.01100	.63600	.05774
GRADIENT	.04646	-.00237	-.00078	.04692	-.00006	-.00004	.00003	.00019	-.01959	-.00014

REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR.

0A119A 861C11F12M51W12E47V19R15X29

(NF0032) (05 JUL 74)

REFERENCE DATA

SREF = 2690.0100 SQ.FT. XMRP = 1076.4000 INCHES
 LREF = 474.6100 INCHES YMRP = .0000 INCHES
 BREF = 936.6000 INCHES ZMRP = 375.0000 INCHES
 SCALE = .0403 SCALE

PARAMETRIC DATA

BETA = .000 SDFLAP = .000
 ELEVON = -5.000 AILFON = .000
 RUDDER = .000 SPOBRK = 25.000

RUN NO. 32/ 0 RN/L = 1.83 GRADIENT INTERVAL = -6.00/ 6.00

MACH	ALPHA	CL	CDF	CLM	CN	CAF	CYN	CEB	CY	XCP/L	CAB
.260	-10.760	-.5520	.12690	.08270	-.66780	.00408	-.00030	.00070	-.00200	.69700	-.03602
.260	-6.640	-.53070	.09290	.06190	-.55840	.00903	-.00040	-.00020	-.00100	.70600	-.03836
.260	-6.510	-.44440	.06500	.07980	-.44890	.01423	-.00030	.00020	-.00100	.71700	-.03427
.260	-4.340	-.33490	.04450	.07710	-.33740	.01699	-.00030	.00000	-.00100	.73600	-.03771
.260	-2.250	-.23240	.03260	.07370	-.23350	.02330	-.00050	.00010	-.00000	.76200	-.03502
.260	-.130	-.13460	.02610	.07140	-.13470	.02588	-.00050	.00020	-.00000	.84700	-.03734
.260	1.960	-.03720	.02320	.07050	-.03640	.02449	-.00070	.00030	-.00100	1.36400	-.03699
.260	4.060	.03730	.02230	.07020	.05670	.01823	-.00070	.00020	-.00100	.21200	-.03666
.260	6.210	.15640	.02600	.06990	.15630	.00996	-.00070	.00020	-.00200	.49300	-.03666
.260	6.350	.26020	.03310	.06690	.26260	-.00307	-.00090	.00000	-.00300	.55500	-.03673
.260	10.450	.35760	.04900	.07150	.36060	-.01666	-.00090	.00000	-.00300	.57900	-.03799
.260	12.610	.46620	.07110	.07268	.47240	-.03294	-.00070	-.00010	-.00300	.59500	-.04010
.260	14.770	.56240	.10370	.07120	.58960	-.04619	-.00060	-.00020	-.00500	.60700	-.04160
.260	16.920	.71230	.14630	.06160	.72460	-.06349	-.00100	.00000	-.00400	.62000	-.04436
.260	19.100	.83250	.20320	.05690	.63320	-.08049	-.00110	-.00050	-.01000	.62700	-.04677
.260	21.250	.94200	.26710	.05430	.97470	-.09234	-.00030	-.00040	-.01000	.63100	-.04916
.260	23.410	1.05730	.35330	.04290	1.11150	-.09397	.00030	.00210	-.00900	.63600	-.05305
.260	25.540	1.11760	.42960	.05220	1.19370	-.09432	.00020	.00190	-.01200	.63600	-.05797
GRADIENT		.04649	-.00255	-.00081	.04695	-.00002	-.00003	.00003	.00024	-.02136	-.00013

(RF6033) (09 JUL 74)

G4119A 361C11F12M31M124E46V19R15X29

REFERENCE DATA
 SREF = 2690.0100 90.FT. XMRP = 1076.4000 INCHES BETA = .000 BDFLAP = .000
 LREF = 474.8100 INCHES YMRP = .0000 INCHES ELEVON = -3.000 AILRON = .000
 DREF = 936.6000 INCHES ZMRP = 375.0000 INCHES RUDDER = .000 SPDBRK = 25.000
 SCALE = .0405 SCALE

PARAMETRIC DATA
 RUN NO. 33/ 0 RN/L = 1.05 GRADIENT INTERVAL = -6.00/ 6.00

MACH	ALPHA	CL	CDF	CLM	CM	CAF	CYN	CBL	CY	XCP/L	CAB
.260	-10.750	-.65570	.12070	.08280	-.66020	.00406	-.00030	.00030	.00000	.69700	.03795
.260	-8.640	-.55020	.09300	.06150	-.55790	.00924	-.00030	-.00030	.00000	.70500	.03604
.260	-6.500	-.44320	.06470	.07990	-.44760	.01411	-.00030	.00000	.00000	.71700	.03427
.260	-4.370	-.33590	.04470	.07700	-.33630	.01902	-.00030	.00000	.00000	.73300	.03910
.260	-2.240	-.23240	.03310	.07360	-.23360	.02403	-.00760	.00010	.00000	.76600	.03740
.260	-1.130	-.13520	.02610	.07170	-.13530	.02593	-.00060	.00010	.00000	.84700	.03724
.260	1.990	-.03680	.02320	.07060	-.03590	.02450	-.00060	.00020	.00100	1.37400	.03697
.260	4.080	.05770	.02240	.07040	.05920	.01826	-.00060	.00030	.00100	.21400	.03722
.260	6.240	.15820	.02670	.07000	.16010	.00555	-.00040	.00020	.00300	.49100	.03593
.260	8.360	.25950	.03470	.06960	.26190	-.00336	-.00040	.00010	.00300	.55400	.03647
.260	10.480	.35890	.04890	.07240	.36140	-.01722	-.00090	.00000	.00400	.57400	.03797
.260	12.630	.46700	.07160	.07300	.47140	-.03229	-.00070	-.00020	.00400	.59500	.03951
.260	14.770	.58270	.10350	.07150	.58980	-.04856	-.00060	-.00020	.00500	.60700	.04163
.260	16.940	.71390	.14900	.06150	.72630	-.06549	-.00100	.00020	.00400	.62000	.04339
.260	19.080	.83220	.20320	.05700	.83290	-.07996	-.00100	-.00050	.00900	.62700	.04621
.260	21.240	.94290	.26660	.05420	.97550	-.09288	-.00030	-.00050	.00900	.63100	.04934
.260	23.410	1.06050	.35630	.04160	1.11460	-.09445	.00040	.00250	.00900	.63400	.05264
.260	25.530	1.11600	.42960	.05130	1.19400	-.09418	.00030	.00220	.01000	.63600	.05791
GRADIENT	.04651	-.00258	-.00077	-.00037	.04694	-.00005	.00001	.00003	.00014	-.02032	-.00010

CA119A 861C11F1ZM51W124E47V19R13X29

(RF0034) (09 JUL 74)

REFERENCE DATA

SREF = 2690.0100 SQ.FT. XMRP = 1076.4800 INCHES
 LREF = 474.8000 INCHES YMRP = .0000 INCHES
 BREF = 936.6800 INCHES ZMRP = 375.0000 INCHES
 SCALE = .0403 SCALE

PARAMETRIC DATA

BETA = .005 BOFLAP = .000
 ELEVCM = 5.000 AIRLFCM = .000
 RUDDER = .000 SPDBFK = 23.000

RUN NO. 34/ 0 RN/L = 1.85 GRADIENT INTERVAL = -6.00/ 6.00

MACH	ALPHA	CL	CDF	CLM	CN	CAF	CYN	CBL	CY	XCP/L	CAP
.260	-10.570	-.45270	.08600	-.00940	-.46120	.00342	-.00020	.00030	-.00200	.64400	.04399
.260	-8.430	-.34170	.06200	-.01150	-.34710	.01123	.00000	.00070	-.00200	.63900	.04290
.260	-6.280	-.23360	.04030	-.01430	-.23680	.01466	.00000	.00030	-.00200	.62900	.04420
.260	-4.150	-.12920	.02900	-.01690	-.13090	.01955	-.00050	.00030	.00000	.60400	.04323
.260	-2.010	-.03230	.02300	-.01790	-.03310	.02396	-.00050	.00070	.00000	.45300	.04316
.260	.070	.06280	.02540	-.01880	.04290	.02339	-.00040	.00090	.00000	.76200	.04194
.260	2.170	.15960	.02790	-.02000	.16030	.02193	-.00060	.00070	.00100	.69900	.04201
.260	4.250	.25350	.03370	-.02120	.25540	.01486	-.00060	.00060	.00200	.64200	.04144
.260	6.410	.35340	.04470	-.02270	.35920	.00475	-.00070	.00040	.00300	.67000	.04114
.260	8.530	.45760	.05970	-.02330	.46140	-.00879	-.00090	.00040	.00300	.66600	.04206
.260	10.640	.56000	.08120	-.02150	.56330	-.02360	-.00090	.00040	.00600	.66300	.04397
.260	12.820	.66740	.11080	-.02060	.67330	-.04003	-.00100	.00030	.00600	.66300	.04364
.260	14.970	.78340	.15120	-.02340	.79590	-.03627	-.00090	.00000	.00400	.66600	.04764
.260	17.130	.91710	.20690	-.03570	.93740	-.07246	-.00130	.00000	.00400	.66600	.04764
.260	19.280	1.03030	.26620	-.03640	1.06110	-.08711	-.00140	-.00030	.01100	.66300	.05059
.260	21.430	1.13400	.34340	-.04130	1.18110	-.09465	.00000	.00000	.00400	.66500	.05399
.260	23.600	1.24200	.44620	-.03360	1.31670	-.09631	-.00150	-.00170	.01400	.66700	.06076
.260	25.720	1.29140	.52230	-.03810	1.35040	-.09939	.00020	-.00060	.01300	.66200	.06543
	GRADIENT	.04563	.00039	-.00051	.04603	-.00034	-.00001	.00001	.00024	.01904	-.00023



GA119A 881C11F12M51M124E40V19R15129

REFERENCE DATA
 SREF = 2490.0100 SQ.FT. XMRP = 1076.4000 INCHES BETA = .000 BDFLAP = .000
 LREF = 474.0100 INCHES YMRP = .0000 INCHES ELEVON = 3.000 AIRCON = .000
 BREF = 936.6000 INCHES ZMRP = 375.0000 INCHES RUDDER = .000 SPOBRK = 25.000
 SCALE = .0403 SCALE

PARAMETRIC DATA

RUN NO. 35/ 0 RM/L = 1.63 GRADIENT INTERVAL = -6.00/ 6.00

MACH	ALPHA	CL	CLM	CN	CAF	CYN	CBL	CY	XCP/L	CAP
.260	-10.380	-.45100	-.00930	-.45950	.00359	-.00020	.00050	-.00100	.64400	.04371
.260	-6.430	-.34120	-.01190	-.34640	.01004	.00000	.00090	-.00100	.63900	.04393
.260	-6.280	-.23140	-.01450	-.23440	.01493	-.00020	.00060	-.00100	.62900	.04356
.260	-4.170	-.12790	-.01720	-.12970	.01940	-.00050	.00050	.00000	.60300	.04321
.260	-2.080	-.03410	-.01830	-.03500	.02400	-.00060	.00070	.00000	.45900	.04265
.260	.060	.06320	-.01930	.06320	.02516	-.00060	.00040	.00100	.76400	.04194
.260	2.160	.16000	-.02030	.16090	.02129	-.00070	.00090	.00200	.69400	.04226
.260	4.260	.25620	-.02140	.25910	.01480	-.00070	.00060	.00200	.64200	.04114
.260	6.400	.35540	-.02280	.35910	.00425	-.00040	.00050	.00300	.67500	.04074
.260	8.530	.45870	-.02320	.46240	-.00516	-.00090	.00060	.00400	.67000	.04130
.260	10.660	.55900	-.02040	.56330	-.02410	-.00090	.00040	.00500	.66500	.04232
.260	12.800	.66580	-.01990	.67390	-.03934	-.00100	.00030	.00600	.66300	.04355
.260	14.960	.76310	-.02290	.77560	-.05621	-.00110	.00010	.00600	.66200	.04379
.260	17.110	.91560	-.03510	.93580	-.07237	-.00130	.00000	.00900	.66500	.04400
.260	19.280	1.03020	-.03750	1.06110	-.09670	-.00130	-.00060	.01000	.66500	.05044
.260	21.440	1.13550	-.04070	1.18290	-.09420	-.00010	.00060	.00900	.66400	.05369
.260	23.600	1.24430	-.05300	1.31930	-.08925	-.00150	-.00140	.01900	.66600	.06350
.260	25.710	1.29410	-.03930	1.39340	-.08914	.00020	-.00110	.01400	.66200	.06522
	GRADIENT	.04561	-.00059	.04604	-.00056	-.00002	.00001	.00024	.01492	-.00021

REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR

GA119A 861C11F12M31W124E46V19R13X29

(RF0036) (09 JUL 74)

REFERENCE DATA

SREF = 2690.0100 SQ.FT. XMRP = 1076.4800 INCHES
 LREF = 474.0100 INCHES YMRP = .0000 INCHES
 BRFP = 936.6800 INCHES ZMRP = 375.0000 INCHES
 SCALE = .0400 SCALE

BETA = .000 00FLAP = .000
 ELEVON = 3.000 AIRLON = .000
 RUDDER = .000 SPOBPK = 25.000

PARAMETRIC DATA

RUN NO. 36/ 0 RN.L = 1.00 GRADIENT INTERVAL = -6.00/ 6.00

MACH	ALPHA	CL	CLM	CN	CAF	CYN	CEL	CY	XCP/L	CAB
.260	-10.560	-.45160	-.00990	-.46000	.00346	-.00030	.00070	-.00100	.64400	-.04396
.260	-8.410	-.33670	-.01230	-.34370	.01016	-.00030	.00090	.00000	.63600	-.04361
.260	-6.300	-.23260	-.01520	-.23580	.01461	-.00030	.00070	.00000	.62800	-.04343
.260	-4.160	-.12650	-.01770	-.12820	.01946	-.00030	.00070	.00000	.60100	-.04344
.260	-2.060	-.03170	-.01650	-.03260	.02396	-.00040	.00090	.00000	.44200	-.04263
.260	.070	.06560	-.01970	-.06560	.02446	-.00060	.00100	.00000	.76200	-.04265
.260	2.176	.16090	-.02090	.16190	.02154	-.00060	.00090	.00100	.69900	-.04214
.260	4.270	.25800	-.02180	.25990	.01462	-.00070	.00090	.00200	.64300	-.04139
.260	6.410	.35650	-.02350	.35930	.00463	-.00070	.00070	.00200	.67600	-.04061
.260	8.540	.46020	-.02370	.46410	-.00664	-.00090	.00060	.00400	.67100	-.04074
.260	10.670	.56040	-.02130	.56570	-.02384	-.00090	.00060	.00400	.66600	-.04213
.260	12.790	.66700	-.02040	.67500	-.03946	-.00090	.00010	.00500	.66300	-.04340
.260	14.990	.76440	-.02360	.79710	-.03377	-.00070	-.00020	.00600	.66300	-.04329
.260	17.120	.91640	-.03310	.93630	-.07269	-.00130	.00040	.00400	.66500	-.04416
.260	19.260	1.03090	-.03790	1.06180	-.08644	-.00130	-.00030	.01000	.66500	-.05033
.260	21.450	1.13610	-.04120	1.18370	-.09410	.00000	.00090	.00400	.66400	-.05344
.260	23.580	1.24290	-.05260	1.31750	-.08850	-.00190	-.00160	.02000	.66600	-.06042
.260	25.710	1.29310	-.03900	1.39220	-.08929	.00000	-.00050	.01400	.66200	-.06514
	GRADIENT	.04559	-.00050	.04603	-.00057	-.00003	.00001	.00074	.02003	-.00022



GA119A 881C11F12M31W124E49V19R13Z0

(RF0037) (09 JUL 74)

REFERENCE DATA

MREF = 2000.0100 SQ.FT. XMRP = 1076.4800 INCHES
 LREF = 474.8100 INCHES YMRP = .0000 INCHES
 MREF = 936.6800 INCHES ZMRP = 375.0000 INCHES
 SCALE = .0405 SCALE

PARAMETRIC DATA

BETA = .000 8DFLAP = .000
 ELEVOM = 10.000 AIRFOIL = .000
 RUDDER = .000 SPDRK = 25.000

RUN NO. 37/ 0 RN/L = 1.65 GRADIENT INTERVAL = -6.00/ 6.00

MACH	ALPHA	CL	CDF	CLM	CM	CAF	CYN	CBL	CY	KCP/L	CAB
.260	-10.480	-.35440	.07600	-.05330	-.36230	.01024	-.00620	.00040	-.00200	.59900	.04617
.260	-8.360	-.24690	.05320	-.05320	-.25200	.01676	-.00020	.00090	-.00100	.37100	.04610
.260	-6.210	-.13710	.03710	-.05930	-.13930	.02220	-.00060	.00050	.00000	.49500	.04618
.260	-4.070	-.03190	.02980	-.06240	-.03390	.02652	-.00070	.00030	.00000	-.02400	.04609
.260	-1.970	.06380	.02840	-.06430	.06270	.03066	-.00070	.00090	.00000	1.02900	.04329
.260	.170	.16350	.03150	-.06600	.16360	.03103	-.00060	.00090	.00100	.80000	.04490
.260	2.250	.25730	.03740	-.06790	.25660	.02730	-.00090	.00120	.00200	.74800	.04465
.260	4.380	.35550	.04720	-.06960	.35610	.01993	-.00110	.00060	.00300	.72300	.04407
.260	6.500	.45870	.06180	-.07220	.46280	.00943	-.00120	.00060	.00400	.70900	.04339
.260	8.630	.56300	.08150	-.07390	.56680	-.00397	-.00130	.00000	.00500	.70000	.04391
.260	10.770	.66760	.10840	-.07360	.67610	-.01828	-.00130	-.00020	.00600	.69200	.04433
.260	12.930	.78000	.14410	-.07390	.79240	-.03400	-.00130	-.00060	.00800	.69700	.04609
.260	15.080	.90090	.19050	-.08120	.91940	-.05051	-.00130	-.00040	.00700	.69400	.04759
.260	17.220	1.02240	.24790	-.08910	1.04990	-.06590	-.00110	-.00070	.00700	.64300	.05005
.260	19.360	1.12700	.31320	-.08930	1.16710	-.07848	-.00090	-.00050	.00900	.64000	.05235
.260	21.510	1.21450	.39650	-.08970	1.27530	-.07647	-.00090	.00090	.00900	.67400	.05677
.260	23.700	1.33080	.50360	-.10250	1.42100	-.07388	-.00120	-.00060	.02100	.67900	.06393
.260	25.770	1.36590	.57500	-.08070	1.49010	-.07612	.00030	-.00350	.01400	.67200	.06467
	GRADIENT	.04565	.00217	-.00085	.04640	-.00078	-.00005	.00002	.00034	.05735	-.00021

GAI19A 061C11F12M31W124E46N19R13X29

(RF4039) (09 JUL 74)

REFERENCE DATA

SREF = 2690.0100 50. FT. XMRP = 1076.4900 INCHES
 LREF = 474.8100 INCHES YMRP = .0000 INCHES
 BRREF = 936.6970 INCHES ZMRP = 375.0000 INCHES
 SCALE = .0405 SCALE

BETA = .000 9DFLAP = .000
 ELEVSN = 10.000 AIRLUM = .000
 RUDDER = .000 SPOBEX = 25.000

PARAMETRIC DATA

RUN NO. 38/ 0 RN/L = 1.05 GRADIENT INTERVAL = -6.00/ 6.00

MACH	ALPHA	CL	CLM	CM	CAF	CYM	CBL	CT	XCP/L	CAB
.280	-10.450	-.34920	-.05620	-.35680	.00919	-.00000	.00030	-.00200	.59400	.04648
.280	-6.300	-.23930	-.05880	-.24440	.01614	-.00010	.00110	-.00100	.56300	.04633
.280	-6.180	-.13000	-.06290	-.13310	.02169	-.00040	.00080	.00000	.47800	.04634
.280	-4.050	-.02590	-.06350	-.02780	.02637	-.00070	.00030	.00100	-.21300	.04602
.280	-1.910	.07100	-.06700	.07000	.03028	-.00070	.00060	.00100	1.00400	.04559
.280	.190	.16530	-.06850	.16560	.03033	-.00080	.00070	.00200	.40400	.04526
.280	2.310	.26210	-.06970	.26340	.02616	-.00090	.00060	.00300	.74900	.04511
.280	4.410	.35750	-.07090	.36010	.01888	-.00100	.00060	.00400	.72400	.04421
.280	6.530	.45730	-.07200	.46120	.00404	-.00100	.00030	.00400	.70900	.04354
.280	6.660	.55910	-.07260	.56440	-.00453	-.00100	.00040	.00300	.69900	.04346
.280	10.810	.66680	-.07280	.67490	-.02071	-.00110	.00030	.00600	.69100	.04313
.280	12.950	.77700	-.07440	.78900	-.03600	-.00110	.00030	.00700	.68600	.04399
.280	15.100	.89080	-.07700	.90860	-.05217	-.00090	-.00030	.00600	.68300	.04737
.280	17.250	1.02330	-.08820	1.05030	-.06441	-.00110	-.00030	.00400	.68300	.04937
.280	19.410	1.13140	-.09370	1.17060	-.08251	-.00100	-.00030	.00400	.68000	.03223
.280	21.560	1.22900	-.09480	1.29000	-.07974	-.00030	.00140	.00400	.67900	.03636
.280	23.730	1.34500	-.10460	1.43540	-.07716	-.00090	-.00030	.02000	.68000	.06347
.280	25.040	1.37870	-.08650	1.49420	-.07744	.00020	-.00140	.01300	.67300	.06742
.280	GRADIENT	.04531	-.00064	.04545	-.00090	-.00004	.00001	.00034	.07693	-.00019

GALL19A 061C11F12M51W124E7V19R15X29

(RFP041) (09 JUL 74)

REFERENCE DATA

BREF = 2690.0100 SQ.FT. ZMRP = 1076.6000 INCHES
 LREF = 474.8100 INCHES YMRP = .0000 INCHES
 RREF = 936.6000 INCHES ZMRP = 375.0000 INCHES
 SCALE = .0005 SCALE

PARAMETRIC DATA

BETA = .000 BDFLAP = .000
 ELEVOM = .000 ALLKUM = .000
 RUDDER = .000 SPOBPK = 25.000

RUN NO. 41/ 0 RM/L = 1.85 GRADIENT INTERVAL = -6.00/ 6.00

MACH	ALPHA	CL	CLM	CM	CAF	CYN	CBL	CT	RCP/L	CAP
.260	-10.560	-.55180	.10510	-.56170	.00119	.00000	.06790	-.00300	.67500	.04116
.260	-6.530	-.44270	.07380	-.44870	.00730	.00000	.00111	-.00200	.67500	.04076
.260	-6.380	-.33290	.03120	-.33640	.01237	-.00020	.00073	-.00200	.68600	.04071
.260	-4.250	-.22920	.03490	-.23120	.01783	.00000	.00090	-.00200	.69800	.04034
.260	-2.100	-.12890	.02720	-.12980	.02246	-.00030	.00000	.00000	.72900	.03993
.260	-.020	-.03490	.02360	-.03490	.02366	-.00060	.00000	.00000	.92700	.03944
.260	2.070	.06060	.02360	.06140	.02144	-.00030	.00100	.00000	.49900	.03921
.260	4.190	.15750	.02640	.15910	.01499	-.00060	.00000	.00100	.59300	.03996
.260	6.330	.25950	.03350	.26170	.00466	-.00070	.00000	.00200	.61900	.03940
.260	8.450	.36120	.04540	.36400	-.00917	-.00070	.00000	.00200	.62900	.03961
.260	10.600	.46300	.06350	.46680	-.02274	-.00060	.00100	.00300	.63200	.03967
.260	12.700	.56600	.09960	.57160	-.03907	-.00070	.00000	.00400	.63400	.04124
.260	14.870	.67980	.12360	.68850	-.05499	-.00070	.00000	.00500	.63400	.04343
.260	17.020	.81220	.17340	.82740	-.07193	-.00130	.00100	.00400	.64300	.04605
.260	19.200	.93140	.23270	.93610	-.08634	-.00190	-.00020	.00300	.64900	.04854
.260	21.350	1.03650	.30150	1.07700	-.09724	.00000	.00000	.00400	.64900	.05162
.260	23.530	1.13500	.40070	1.21890	-.09369	.00030	.00150	.00900	.65400	.05637
.260	25.600	1.20620	.47400	1.29260	-.09393	.00030	.00110	.01200	.65900	.06042
GRADIENT		.04574	-.00098	.04617	-.00033	-.00006	.00002	.00029	-.02063	-.00017

REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR

GA119A 061C11F12M51W124E49V19R132Z0

IFP0042) (09 JUL 74)

REFERENCE DATA

SREF = 2690.0100 50.FT. ZMRP = 1076.4000 INCHES
 LREF = 476.8100 INCHES YMRP = .0000 INCHES
 ORF = 936.6000 INCHES ZMRP = 375.0000 INCHES
 SCALE = .0405 SCALE

PARAMETRIC DATA

BETA = .000 BDFLAP = .000
 ELEVON = .000 AIRCON = .000
 RUDDER = .000 SPOBRK = 25.000

RUN NO. 42/ 0 RN/L = 1.65 GRADIENT INTERVAL = -6.00/ 6.00

MACH	ALPHA	CL	CLM	CN	CAF	CYM	CB	CC	ACP/L	CAB
.260	-10.650	-.55150	.03640	-.56150	.00200	-.00010	.50080	-.00200	.67600	.04097
.260	-8.510	-.44280	.03430	-.44880	.00761	.00000	.00000	-.00200	.68000	.04079
.260	-6.370	-.33400	.03190	-.33750	.01262	-.00030	.00030	-.00100	.68600	.04109
.260	-4.230	-.23190	.02990	-.23380	.01792	.00020	.00000	-.00000	.69900	.04043
.260	-2.140	-.13160	.02790	-.13250	.02235	-.00050	.00000	.00000	.72900	.03996
.260	-.030	-.03580	.02670	-.03580	.02384	-.00050	.00000	.00000	.92600	.03990
.260	2.070	.05980	.02590	.06060	.02135	-.00030	.00000	.00000	.49400	.03972
.260	4.200	.15830	.02470	.15990	.01514	-.00060	.00000	.00100	.53500	.03893
.260	6.330	.25970	.02270	.26190	.00533	-.00070	.00000	.00200	.62000	.03850
.260	8.450	.36430	.02120	.36720	-.00726	-.00070	.00000	.00300	.63000	.03902
.260	10.590	.46500	.02330	.46900	-.02160	-.00050	.00000	.00300	.63300	.03946
.260	12.740	.57140	.02500	.57750	-.03649	-.00060	.00000	.00400	.63600	.04124
.260	14.880	.68610	.02270	.69560	-.05370	-.00070	.00000	.00600	.64000	.04333
.260	17.050	.81450	.01410	.83010	-.07130	-.00110	.00000	.00700	.64500	.04646
.260	19.190	.93060	.01030	.95580	-.08503	-.00070	.00000	.00800	.64900	.04557
.260	21.360	1.03790	.00400	1.07710	-.09553	.00030	.00000	.00900	.64900	.05163
.260	23.520	1.15100	-.00670	1.21530	-.09200	.00050	.00140	.00300	.65400	.05641
.260	25.610	1.20290	.00750	1.28960	-.09234	.00040	.00120	-.1200	.65000	.06109
	GRADIENT	.04604	-.00059	.04644	-.00032	-.00004	.00000	.00024	-.12000	-.00015



REFERENCE DATA

REF = 2690.0100 SQ.FT. XMRP = 1076.4800 INCHES
 LREF = 474.8100 INCHES YMRP = .0000 INCHES
 BRP = 936.6900 INCHES ZMRP = 373.0000 INCHES
 SCALE = .0400 SCALE

PARAMETRIC DATA

BETA = .000 8DFLAP = .000
 ELEVON = -10.000 ALLCON = .000
 RUDDER = .000 SPODER = 23.000

RUN NO. 43/ 0 RM/L = 1.05 GRADIENT INTERVAL = -6.00/ 6.00

MP M	ALPHA	CL	CLM	CLN	CAF	CYM	CBL	CT	KCP/L	CAB
.260	-10.040	-.75620	.12810	-.77210	.01134	-.00030	.00030	-.00100	.71300	-.03499
.260	-8.710	-.63460	.12970	-.66460	.01333	-.00010	-.00030	-.00200	.72300	-.03396
.260	-6.380	-.54920	.12750	-.55330	.02148	-.00030	-.00020	-.00100	.73600	-.03324
.260	-4.440	-.43980	.12420	-.44320	.02613	-.00020	.00020	-.00100	.73300	-.03316
.260	-2.310	-.33330	.11970	-.33480	.02968	-.00040	.00020	-.00100	.74300	-.03316
.260	-1.160	-.23100	.11640	-.23110	.03293	-.00030	.00010	.00000	.93700	-.03326
.260	1.310	-.13350	.11430	-.13260	.03109	-.00030	.00020	.00000	.96900	-.03341
.260	4.040	-.03690	.11330	-.03510	.02870	-.00060	.00030	.00000	1.43400	-.03476
.260	6.160	.06170	.11300	.06400	.01903	-.00060	.00030	.00100	.00200	-.03453
.260	8.280	.16200	.11240	.16470	.00637	-.00070	.00030	.00300	.40000	-.03543
.260	10.420	.26120	.11340	.26440	-.00624	-.00060	.00020	.00300	.49000	-.03664
.260	12.520	.36440	.11770	.36470	-.02037	-.00060	.00030	.00400	.53400	-.03716
.260	14.700	.46290	.09970	.46960	-.03669	-.00030	.00030	.00300	.56400	-.04046
.260	16.630	.60970	.10940	.61980	-.03391	-.00070	.00040	.00600	.54700	-.04342
.260	19.030	.72790	.10630	.74390	-.06963	-.00030	.00000	.00700	.33900	-.04662
.260	21.200	.83950	.10390	.86930	-.04307	.00010	.00000	.00400	.60400	-.04842
.260	23.310	.95210	.09360	.99930	-.04456	-.00130	.00270	.00600	.61700	-.05143
.260	25.440	1.01810	.09460	1.04580	-.04792	-.00160	.00210	.00400	.61400	-.05623
.260	GRADIENT	.04744	-.00421	.04404	.00012	-.00004	.00001	.00014	.11102	-.05073

GALLINA 061C11F12M31W124E30V19R15K29

(0F8044) (21 OCT 74)

REFERENCE DATA

REF Z 2690.0100 SQ.FT. ZMRP Z 1076.4000 INCHES
 LREF Z 474.8100 INCHES *MRP Z .0000 INCHES
 ORF Z 936.6000 INCHES ZMRP Z 375.0000 INCHES
 SCALE Z .0400 SCALE

RUN NO. 447 0 RM/L = 1.85 GRADIENT INTERVAL Z -6.00/ 6.00

BETA Z .000 SDFLAP Z .000
 ELEVGM Z -40.0000 AIRLGM Z .000
 FUDGEF Z .000 SFBDRK Z 23.000

PARAMETRIC DATA

MACH	ALPHA	CL	COF	CLM	CN	CAF	CYN	COL	C*	ACP/L	CAB
.260	-11.110	-.98060	.29290	.21890	-1.01870	.09843	-.00060	.00120	-.00100	.73100	-.03724
.260	-6.990	-.91170	.24920	.23260	-.93950	.10359	-.00340	-.00610	-.00300	.74300	-.03310
.260	-6.690	-.92320	.20940	.23810	-.84240	.10909	-.00050	-.00240	-.00200	.75600	-.03609
.260	-4.750	-.71710	.17170	.23140	-.72390	.11215	.00000	-.00120	-.00300	.76900	-.03599
.260	-2.600	-.59530	.13960	.22070	-.59230	.11261	-.00020	-.00130	-.00200	.74700	-.03637
.260	-.490	-.48230	.11820	.21130	-.48330	.11210	-.00010	-.00040	-.00200	.81300	-.03673
.260	1.645	-.37860	.09960	.20440	-.37560	.11047	-.00050	-.00140	-.00200	.85200	-.03696
.260	3.760	-.27300	.08360	.19850	-.26890	.10336	-.00100	-.00240	.00000	.92600	-.03766
.260	5.910	-.17860	.07880	.19900	-.16950	.09642	-.00110	-.00240	.00000	1.04400	-.03699
.260	8.020	-.08750	.07470	.20140	-.07820	.08622	-.00110	-.00240	.00100	1.62400	-.03901
.260	10.120	.00380	.07790	.20690	.01740	.07605	-.00040	-.00170	.00300	-3.70000	-.03934
.260	12.240	.09330	.08720	.21410	.11170	.06499	-.00040	-.00040	.00300	-.05300	-.04094
.260	14.380	.19300	.10210	.21850	.21230	.05104	.00000	-.00040	.00400	.27300	-.04413
.260	16.550	.30770	.12940	.21830	.33160	.03642	-.00040	-.00130	.00600	.40900	-.04310
.260	18.660	.40700	.16430	.22190	.43420	.02329	-.00060	-.00140	.00400	.00000	-.04776
.260	20.760	.48290	.20330	.23410	.52360	.01475	.00000	-.00120	.01000	.44700	-.05014
.260	22.910	.56460	.25190	.24230	.61420	.01215	.00060	-.00140	.00900	.30700	-.03267
.260	25.030	.64510	.30300	.24240	.71270	.00149	.00330	-.00050	.00100	-.02600	-.03543
.260	GRADIENT	.05010	-.00663	-.00316	.03203	-.00142	-.00011	-.00014	.00021	.02727	.00012

TABULATED SOURCE DATA - OA119A

OA119A 861C11F12M31M124E11V19R13X29

REFERENCE DATA

SREF = 2690.0100 SQ.FT. XMRP = 1076.4800 INCHES
 LREF = 474.8100 INCHES YMRP = .7000 INCHES
 BREF = 936.6800 INCHES ZMRP = 375.0000 INCHES
 SCALE = .0485 SCALE

BETA = .000 BDFLAP = .000
 ELEVON = -40.000 ALLCON = .000
 RUDDER = .000 SPOBRK = 25.000

PARAMETRIC DATA

RUN NO. 45/ 0 RM/L = 1.85 GRADIENT INTERVAL = -6.00/ 6.00

MACH	ALPHA	CL	CDF	CLM	CN	CAF	CYN	CBL	CY	XCF/L	CAB
.260	-11.130	-.98080	.29470	.21940	-1.01930	.09974	-.00170	.00230	.00100	.73100	.03592
.260	-9.000	-.90350	.24820	.23060	-.93320	.10349	-.00099	-.00610	-.00400	.74300	.03353
.260	-6.990	-.82340	.21060	.23860	-.84280	.11027	-.00070	-.00230	-.00100	.75600	.03319
.260	-4.770	-.71250	.17280	.23160	-.72450	.11295	-.00020	-.00110	-.00100	.76900	.03349
.260	-2.630	-.59750	.14060	.22240	-.60340	.11309	-.00060	-.00120	.00000	.78700	.03614
.260	-.470	-.48650	.11790	.21400	-.48740	.11399	-.00040	-.00050	-.00100	.81300	.03833
.260	1.640	-.37810	.09960	.20500	-.37510	.11046	-.00050	.00000	.00000	.83300	.03660
.260	3.750	-.27310	.08690	.19900	-.26680	.10463	-.00040	.00020	.00000	.92600	.03624
.260	5.880	-.18270	.08050	.20110	-.17350	.09882	-.00030	.00070	.00100	1.07400	.03601
.260	8.010	-.08950	.07670	.20340	-.07700	.08838	-.00030	.00070	.00300	1.62400	.03763
.260	10.100	.00110	.08110	.20820	.01530	.07973	-.00030	.00090	.00300	-4.33100	.03731
.260	12.240	.09250	.08870	.21590	.10923	.06706	-.00020	.00130	.00300	-.07500	.04026
.260	14.370	.19270	.10320	.21970	.21230	.03216	.00030	.00120	.00400	.27100	.04349
.260	16.510	.30560	.13050	.21890	.33010	.03924	-.00020	.00050	.00600	.40400	.04443
.260	18.660	.40370	.16430	.22370	.4. 10	.02646	-.00020	.00050	.00300	.46200	.04724
.260	20.780	.48600	.20370	.23430	.52670	.01805	-.00000	.00000	.00900	.44900	.05064
.260	22.920	.57450	.25340	.23940	.62780	.00971	.00070	-.00090	.00900	.51100	.05326
.260	25.040	.64810	.30530	.24230	.71. 0	.00223	.00330	-.00040	.00100	.52700	.05629
	GRADIENT	.05008	-.00861	-.00313	.05205	-.00133	-.00000	.00014	.00015	.02643	.00004

REFERENCE DATA

SREF = 2690.0100 SQ.FT. XMRP = 1076.4000 INCHES BETA = .000 BDFLAP = .000
 LREF = 474.9100 INCHES YMRP = .0000 INCHES ELEVON = -30.000 AIRCRN = .000
 SREF = 936.6800 INCHES ZMRP = 375.0000 INCHES PUDDER = .000 SPDRK = 25.000
 SCALE = .0400 SCALE

PARAMETRIC DATA

RUN NO. 46/ 0 RN/L = 1.85 GRADIENT INTERVAL = -6.00/ 6.00

MACH	ALPHA	CL	CDF	CLM	CM	CAF	CYN	CBL	CY	XCP/L	CAB
.260	-11.140	-.99630	.27070	.23030	-1.02960	.07314	-.00120	-.00340	.00000	.73400	.03663
.260	-9.000	-.91600	.22500	.24110	-.93990	.07890	.00020	-.00100	-.00400	.74600	.03267
.260	-6.860	-.80430	.17670	.23720	-.81990	.06140	.00000	.00300	-.00200	.75900	.03350
.260	-4.690	-.67610	.14130	.22420	-.68340	.06533	.00010	.00280	-.00100	.77200	.03403
.260	-2.560	-.55230	.11300	.21060	-.55700	.06823	.00030	.00510	-.00100	.79100	.03406
.260	-.430	-.43920	.09360	.20190	-.43990	.09034	-.00030	.00130	.00000	.82100	.03443
.260	1.690	-.33960	.07900	.19920	-.33730	.08906	-.00020	.00150	.00000	.86900	.03619
.260	3.820	-.23660	.06840	.19480	-.23350	.08424	-.00040	.00140	.00000	.85900	.03349
.260	5.920	-.14680	.06180	.19520	-.13970	.07666	-.00060	.00030	.00100	1.16600	.03652
.260	8.030	-.05340	.06070	.19790	-.04440	.06761	-.00090	.00010	.00200	2.24900	.03705
.260	10.160	.04220	.06320	.20220	.03270	.05491	-.00080	.00020	.00300	-.75700	.03916
.260	12.310	.13670	.07320	.20760	.14910	.04244	-.00090	.00040	.00500	.13900	.03963
.260	14.430	.23460	.09130	.21290	.25000	.02995	-.00090	.00010	.00500	.33800	.04061
.260	16.560	.32760	.11410	.22060	.34680	.01592	-.00110	-.00210	.00400	.41700	.04341
.260	18.700	.43140	.14840	.22390	.45620	.00231	-.00100	-.00190	.00400	.47100	.04332
.260	20.820	.50700	.18560	.23770	.53990	-.00569	-.00070	-.0010	.00900	.49000	.04797
.260	22.940	.58450	.22990	.24890	.62790	-.01617	.00120	-.00130	.00600	.50600	.05070
.260	25.100	.68120	.29270	.24240	.74100	-.02391	.00390	-.00100	.00700	.53100	.05322
GRADIENT		.04963	-.00735	-.00263	.03116	-.00077	-.00007	-.00036	.00017	.03391	.00027



(0F0047) (21 OCT 74)

CA119A 061C11F12M51M124E51V19R13129

PARAMETRIC DATA

BETA = .000 9DFLAP = .000
 ELEVON = -20.000 A1LRGM = .000
 RUDDER = .000 SPOBRK = 25.000

REFERENCE DATA

SREF = 2690.0100 SQ.FT. XMRP = 1076.4000 INCHES
 LREF = 474.8100 INCHES YMRP = .0000 INCHES
 BRREF = 936.6800 INCHES ZMRP = 375.0000 INCHES
 SCALE = .0405 SCALE

RUN NO. 47/ 0 RN/L = 1.65 GRADIENT INTERVAL = -6.00/ 6.00

MACH	ALPHA	CL	CDF	CLM	CM	CAF	CYN	CBL	CY	XCP/L	CAP
.260	-11.030	-.93220	.21650	.20320	-.95680	.03597	-.00040	.00130	-.00100	.75000	.03022
.260	-8.920	-.84820	.17350	.21200	-.86490	.03987	.00000	-.00090	-.00200	.74200	.03151
.260	-6.810	-.74280	.13440	.21070	-.75350	.04333	.00020	.00150	-.00200	.75500	.03219
.260	-4.660	-.62380	.10170	.20210	-.63000	.05067	.00010	.00100	-.00200	.77000	.03294
.260	-2.490	-.51370	.07760	.19690	-.51660	.05523	.00010	.00130	-.00200	.79200	.03224
.260	-.390	-.40780	.05900	.19010	-.40820	.05822	-.00040	.00050	-.00100	.92300	.03246
.260	1.740	-.30440	.04550	.18690	-.30280	.05474	-.00050	.00050	.00000	.97900	.03334
.260	3.810	-.21030	.03720	.18470	-.20740	.05111	-.00050	.00050	.00000	.97900	.03249
.260	5.950	-.11040	.03390	.18360	-.10620	.04526	-.00050	.00110	.00000	1.24700	.03046
.260	8.090	.01130	.03300	.18320	-.00650	.03434	-.00040	.00130	.00000	11.02400	.03291
.260	10.210	.06240	.03710	.18960	.08770	.02191	-.00030	.00130	.00100	-.14200	.03513
.260	12.340	.16040	.04770	.19470	.18650	.00909	-.00010	.00160	.00100	.26700	.03761
.260	14.490	.26960	.06900	.19580	.29770	-.00369	.00000	.00130	.00200	.41000	.03974
.260	16.640	.40950	.10070	.19290	.42120	-.02069	.00000	.00190	.00300	.44300	.04142
.260	18.800	.52420	.14080	.19180	.54160	-.03369	-.00010	.00110	.00300	.52100	.04434
.260	20.940	.62490	.18740	.19550	.65060	-.04833	.00070	.00120	.00300	.54100	.04644
.260	23.080	.73710	.25100	.19000	.77650	-.05800	.00160	.00190	.00300	.56200	.04945
.260	25.240	.83810	.32480	.18170	.89660	-.06366	.00300	-.00070	.00300	.57700	.05244
	GRADIENT	.04834	-.00640	-.00179	.04930	-.00055	-.00007	-.00003	.00023	.04319	-.00011

REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR

GA119A 861C11F12M51W124E31V19R15X29

REFERENCE DATA
 SREF = 2690.0100 SQ.FT. XMRP = 1076.4000 INCHES BETA = .000 BDFLAP = .000
 LREF = 474.6100 INCHES YMRP = .0000 INCHES ELEVOM = 15.000 AIRLON = .000
 BREF = 936.6000 INCHES ZMRP = 375.0000 INCHES RUDDER = .000 SPDBFK = 25.000
 SCALE = .0403 SCALE

RUN NO. 48/ 0 RN/L = 1.85 GRADIENT INTERVAL = -6.00/ 6.00

PARAMETRIC DATA

MACH	ALPHA	CL	CDF	CLM	CM	CAF	CYN	CBL	CY	XCP/L	CAB
.260	-10.390	-.25640	.06760	-.09760	-.26440	.02027	.00000	.00110	-.00200	.31600	.04969
.260	-6.270	-.14930	.04910	-.10030	-.15460	.02714	-.00020	.00190	-.00100	.41300	.04844
.260	-6.100	-.03500	.03680	-.10640	-.03670	.03290	-.00050	.00090	.00000	-.35700	.04937
.260	-3.990	.06560	.03370	-.11000	.06310	.03821	-.00060	.00110	.00000	1.29300	.04826
.260	-1.890	.16270	.03590	-.11240	.16150	.04132	-.00070	.00100	.00100	.90900	.04812
.260	.220	.25960	.04210	-.11510	.25970	.04114	-.00076	.00110	.00100	.41500	.04900
.260	2.360	.35780	.05190	-.11690	.35960	.03712	-.00070	.00110	.00200	.77100	.04727
.260	4.460	.45490	.06310	-.11960	.45860	.02939	-.00090	.00090	.00300	.74700	.04626
.260	6.580	.55610	.06330	-.12190	.56200	.01900	-.00090	.00090	.00400	.73200	.04596
.260	8.720	.66150	.10710	-.12340	.67010	.00533	-.00090	.00060	.00400	.71900	.04611
.260	10.860	.76930	.13820	-.12450	.78160	-.00915	-.00120	.00060	.00600	.71000	.04672
.260	13.010	.88330	.17860	-.12920	.90080	-.02481	-.00110	.00030	.00600	.70400	.04820
.260	15.160	1.00100	.22900	-.13360	1.02610	-.04076	-.00110	.00000	.00700	.70000	.05050
.260	17.320	1.11640	.28890	-.13680	1.15190	-.05691	-.00100	-.00090	.00900	.69500	.05235
.260	19.460	1.21340	.35620	-.13510	1.26290	-.06440	-.00090	-.00090	.00900	.69100	.05462
.260	21.600	1.29510	.43140	-.13810	1.37030	-.05706	-.00020	.00020	.00900	.64900	.06135
.260	23.760	1.40640	.52500	-.14490	1.50990	-.06120	-.00240	-.00740	.02600	.64700	.06766
.260	25.840	1.43360	.62400	-.11950	1.56220	-.06334	-.00090	-.00300	.01700	.64000	.07273
.260	GRADIENT	.04606	.00373	-.00104	.04679	-.00102	-.00003	-.00002	.00033	-.05410	-.00023



GA119A 80C11F12M31W124E47V19R13Z29

REFERENCE DATA

SREF = 2890.0100 SO.FT. XMRP = 1076.4800 INCHES
 LREF = 474.9100 INCHES YMRP = .0000 INCHES
 BREF = 936.6800 INCHES ZMRP = 375.0000 INCHES
 SCALE = .0405 SCALE

PARAMETRIC DATA

BETA = .000 80FLAP = .000
 ELEVON = 15.000 AIRCRN = .000
 RUDDER = .000 SPOBER = 25.000

RUN NO. 49/ 0 RN/L = 1.85 GRADIENT INTERVAL = -6.00/ 6.00

MACH	ALPHA	CL	CLM	CLN	CAF	CYN	CBL	CY	KCP/L	CAB
.260	-10.390	-.23590	-.09830	-.26380	.01970	-.00020	.00090	-.00100	.51500	.04334
.260	-8.230	-.14720	-.10060	-.19250	.02604	-.00040	.00170	.00000	.45900	.04969
.260	-6.100	-.03630	-.10370	-.03990	.03191	-.00070	.00100	.00000	-.32000	.04938
.260	-4.010	.06070	-.10800	.05830	.03696	-.00070	.00120	.00000	1.33300	.04941
.260	-1.870	.15670	-.10960	.15550	.04006	-.00070	.00150	.00100	.91100	.04919
.260	.210	.23090	.04100	.23100	.04006	-.00080	.00150	.00200	.81400	.04765
.260	2.340	.34790	-.11230	.34970	.03613	-.00080	.00130	.00200	.77000	.04649
.260	4.440	.44320	-.11390	.44670	.02765	-.00090	.00100	.00300	.74500	.04640
.260	6.590	.53000	-.11910	.55580	.01797	-.00040	.00070	.00400	.73100	.04571
.260	8.700	.63920	-.12290	.66760	.00461	-.00070	.00040	.00400	.71900	.04594
.260	10.850	.77150	-.12670	.78350	-.01055	-.00040	.00020	.00500	.71100	.04715
.260	13.000	.88310	-.12740	.90010	-.02688	-.00090	.00000	.00600	.70400	.04714
.260	15.150	.99830	-.13180	1.02260	-.04326	-.00100	-.00010	.00700	.69900	.04964
.260	17.340	1.12170	-.13800	1.15640	-.06019	-.00090	-.00050	.00800	.69600	.05205
.260	19.460	1.21900	-.13660	1.26760	-.07137	.00020	.00010	.00700	.69100	.05424
.260	21.610	1.30390	-.14070	1.37900	-.05947	-.00010	.00010	.01000	.68900	.06041
.260	23.770	1.41980	-.15090	1.52330	-.06349	-.00250	-.00710	.02600	.68900	.06736
.260	25.870	1.49020	-.12530	1.57980	-.06581	-.00020	-.00040	.01400	.68100	.07206
GRADIENT	.04530	.00353	-.00069	.04600	-.00105	-.00002	-.00003	.00033	-.06246	-.00027

REPRODUCIBILITY OF THE ORIGINAL PAGE IS POOR

GA119A 861C11F12M51W124E40V19R1329

(RF0030) (09 JUL 74)

REFERENCE DATA

SREF = 2690.0100 SQ.FT. XMRP = 1076.4800 INCHES
 LREF = 474.8100 INCHES YMRP = .0000 INCHES
 BREF = 936.6400 INCHES ZMRP = 373.0000 INCHES
 SCALE = .0400 SCALE

BETA = .000 BDFLAP = .000
 ELEVON = 15.000 ALLRON = .000
 RUDDER = .000 SPOBRK = 25.000

RUN NO. 50/0 RM/L = 1.85 GRADIENT INTERVAL = -6.00/ 6.00

MACH	ALPHA	CL	CD	CLM	CN	CAF	CYN	CBL	CT	XCP/L	CAB
.260	-10.380	-.24860	.06630	-.10070	-.23650	.02039	-.00030	-.00090	-.00100	-.50700	.04817
.260	-8.230	-.14000	.04780	-.10360	-.14540	.02732	-.00030	.00170	.00000	.36900	.04906
.260	-6.100	-.03010	.03490	-.10850	-.03360	.03135	-.00060	.00140	.00000	-.33400	.04941
.260	-3.990	.07040	.03220	-.11200	.06800	.03704	-.00080	.00110	.00100	1.25800	.04954
.260	-1.860	.16740	.03470	-.11390	.16610	.04017	-.00080	.00130	.00200	-.90400	.04959
.260	.260	.26380	.04100	-.11540	.26400	.03992	-.00080	.00120	.00200	.41300	.04745
.260	2.360	.35760	.05000	-.11640	.35940	.03325	-.00100	.00120	.00300	.77100	.04728
.260	4.460	.45150	.06320	-.11720	.45500	.02792	-.00090	.00130	.00300	.74600	.04817
.260	6.590	.55220	.09080	-.11390	.53790	.01686	-.00100	.00110	.00400	.73100	.04625
.260	8.720	.65750	.10460	-.12110	.66370	.00370	-.00110	.00090	.00600	.71900	.04599
.260	10.880	.76370	.13630	-.12450	.78160	-.01135	-.00100	.00070	.00500	.71000	.04640
.260	13.040	.88210	.17610	-.12650	.89910	-.02749	-.00090	.00070	.00700	.70300	.04799
.260	15.160	.99750	.22470	-.12980	1.02150	-.04402	-.00090	-.00040	.00900	.69400	.04971
.260	17.340	1.11670	.28490	-.13590	1.15040	-.06090	-.00090	-.00060	.00900	.69500	.05204
.260	19.480	1.21790	.35210	-.13430	1.26560	-.07428	.00030	.00020	.00700	.69100	.05464
.260	21.640	1.31230	.43590	-.14330	1.38770	-.06003	.00040	.00030	.00400	.69000	.06131
.260	23.790	1.42170	.53570	-.15040	1.52500	-.06301	-.00260	-.00690	.02600	.68400	.06770
.260	25.880	1.45550	.63350	-.12700	1.58600	-.06557	-.00100	-.00270	.01700	.68100	.07223
.260	GRADIENT	.04310	.00366	-.00081	.04540	-.00110	-.00002	.00001	.00024	-.35444	-.00029



CA119A 061C11F12M31W124E47V19R15X29

(RF9031) (09 JUL 74)

REFERENCE DATA

SRF = 2090.0100 SO.FT. XMRP = 1076.4800 INCHES
 LREF = 474.8100 INCHES YMRP = .0000 INCHES
 PRF = 936.8800 INCHES ZMRP = 375.0000 INCHES
 SCALE = .0403 SCALE

BETA = .000 BDFLAP = .000
 ELEVOM = 20.000 AIRCRH = .000
 RUDDER = .000 SPOBRK = 29.000

RUN NO. 51/ D RM/L = 1.85 GRADIENT INTERVAL = -6.00/ 6.00

PARAMETRIC DATA

MACH	ALPHA	CL	CLM	CLN	CAF	CYN	CBL	CY	KCP/L	CAB
.260	-10.320	-.18060	-.13420	-.18970	.03347	-.00940	.00140	.00000	.39100	.03042
.260	-8.200	-.07820	-.13550	-.08470	.04004	-.00090	.00160	.00000	.06400	.03044
.260	-6.050	.02920	-.14030	.02440	.04641	-.00090	.00210	.00100	2.76300	.03019
.260	-3.940	.13380	-.14570	.13060	.03133	-.00130	.00150	.00200	1.06200	.03066
.260	-1.810	.23360	-.14950	.23190	.03560	-.00130	.00190	.00200	.98900	.03011
.260	.290	.31160	-.15310	.33190	.03569	-.00140	.00220	.00300	.92100	.04920
.260	2.410	.43060	-.15610	.43340	.03145	-.00140	.00270	.00300	.79400	.04967
.260	4.530	.52970	-.15950	.53490	.04357	-.00140	.00240	.00400	.76100	.04817
.260	6.690	.64630	-.16650	.65470	.03303	-.00130	.00240	.00400	.74600	.04409
.260	8.820	.75980	-.17490	.77210	.02049	-.00130	.00270	.00500	.73500	.04791
.260	10.980	.87040	-.17740	.86770	.00320	-.00120	.00140	.00600	.72500	.04472
.260	13.100	.98140	-.17960	1.00510	-.01076	-.00190	.00170	.00900	.71700	.04964
.260	15.270	1.09710	-.18360	1.12960	-.02819	-.00190	.00050	.01000	.71100	.03243
.260	17.420	1.20670	-.18440	1.25070	-.04493	-.00120	.00010	.01000	.70600	.03432
.260	19.540	1.29480	-.18010	1.35530	-.03274	-.00120	-.00020	.01000	.70100	.03719
.260	21.640	1.37690	-.18520	1.46710	-.03710	-.00130	-.00150	.01000	.69400	.06416
.260	23.830	1.48240	-.18960	1.60200	-.04244	-.00280	-.00930	.02400	.69300	.07033
.260	25.930	1.49410	-.15390	1.63770	-.04970	-.00010	-.00590	.00600	.64600	.07526
GRADIENT	.04674	.00510	-.00162	.04774	-.00095	-.00091	.00012	.00024	-.03342	-.00030

0A119A 861C11F12M51W124E48V19R15X29

(RF0052) (09 JUL 74)

REFERENCE DATA

SREF = 2890.0100 80.FT. YMRP = 1076.4000 INCHES
 LREF = 474.8100 INCHES YMRP = .0000 INCHES
 BREF = 936.6000 INCHES ZMRP = 375.0000 INCHES
 SCALE = .0403 SCALE

BETA = .000 9DFLAP = .000
 ELENGH = 20.000 ALLRGM = .000
 RUDDER = .000 SPDRK = 29.000

RUN NO. 92/ 0 RN/L = 1.85 GRADIENT INTERVAL = -0.00/ 6.00

PARAMETRIC DATA

MACH	ALPHA	CL	CLM	CM	CAF	CYN	CBL	CY	XCP/L	CAS
.260	-10.270	-1.6000	.06310	-1.4230	-.16870	-.00010	.00190	-.00200	.34100	.05941
.260	-8.130	-.03340	.04750	-.14530	-.03932	-.00050	.00260	-.00100	-.24500	.05123
.260	-5.990	.05330	.04060	-.19010	.03080	-.00010	.00260	-.00100	1.73900	.05064
.260	-3.850	.13610	.04090	-.15410	.05136	-.00070	.00210	.00000	1.02200	.05063
.260	-1.770	.25080	.04700	-.15570	.24930	-.00070	.00220	.00000	.98100	.05002
.260	.340	.34330	.05350	-.15630	.34360	-.00070	.00220	.00000	.81900	.04937
.260	2.450	.43480	.06770	-.15610	.43730	-.00090	.00250	.00100	.74300	.04876
.260	4.370	.52880	.08430	-.15760	.53390	-.00100	.00270	.00200	.76000	.04844
.260	6.700	.63000	.10370	-.16080	.63890	-.00090	.00300	.00200	.74400	.04735
.260	8.830	.74540	.13370	-.16900	.73710	-.00090	.00290	.00300	.73300	.04669
.260	10.960	.86360	.17070	-.17430	.88030	-.00100	.00280	.00400	.72500	.04497
.260	13.140	.97500	.21410	-.17540	.99620	-.00100	.00220	.00500	.71600	.04499
.260	15.290	1.08660	.26600	-.17840	1.11630	-.00130	.00220	.00700	.71000	.05232
.260	17.430	1.19930	.32870	-.18080	1.24210	-.00170	.00090	.00600	.70500	.05495
.260	19.570	1.29780	.39880	-.17590	1.34700	-.00050	.00020	.00700	.70000	.05736
.260	21.740	1.38670	.50790	-.18630	1.47610	-.00140	-.00020	.01200	.69400	.06420
.260	23.990	1.49380	.61120	-.19210	1.61340	-.00340	-.01010	.02900	.69300	.07010
.260	26.000	1.53850	.69270	-.17980	1.68670	-.05117	.01350	-.01000	.64900	.07469
	GRADIENT	.04466	.00416	-.00060	.04556	-.00041	.00007	.00024	-.07694	-.00023



GALLI9A 861C11F12M51M124E31V19R13Z29

REFERENCE DATA
 SREF = 2690.0100 SQ.FT. XMRP = 1076.4800 INCHES BETA = .000 80FLAP = .300
 LREF = 474.0100 INCHES YMRP = .0000 INCHES ELEVOM = 20.000 AILRCM = .000
 SREF = 936.6800 INCHES ZMRP = 375.0000 INCHES RUDDER = .000 SPOBCK = 25.000
 SCALE = .0003 SCALE

PARAMETRIC DATA

RUM NO. 94/ 0 RM/L = 1.05 GRADIENT INTERVAL = -6.00/ 6.00

MACH	ALPHA	CL	CDF	CLM	CM	CAF	CTM	CBL	CY	XCP/L	CAB
.260	-10.280	-.17720	.06680	-.13530	-.18630	.03416	-.00010	.00140	-.00200	.39400	.05012
.260	-8.150	-.06740	.05080	-.13930	-.07390	.04075	-.00030	.00200	.00000	-.04100	.03071
.260	-5.990	.04420	.04300	-.14610	.03950	.04743	-.00010	.00210	.00000	2.01200	.03026
.260	-3.890	.14280	.04340	-.14990	.13960	.05305	-.00070	.00150	.00000	1.04700	.03027
.260	-1.760	.24020	.04910	-.15280	.23660	.05655	-.00090	.00140	.00100	.98700	.04967
.260	.340	.33310	.05780	-.15420	.33350	.05588	-.00080	.00190	.00100	.82200	.04945
.260	2.440	.42820	.06930	-.15540	.43070	.05125	-.00090	.00210	.00100	.78400	.04899
.260	4.570	.52560	.08370	-.13790	.53080	.04353	-.00100	.00190	.00200	.76100	.04943
.260	6.680	.63180	.10660	-.16230	.63990	.03228	-.00130	.00030	.00500	.74500	.04791
.260	8.820	.74330	.13520	-.16860	.75520	.01965	-.00130	.00090	.00500	.73400	.04930
.260	10.960	.85240	.17070	-.17150	.86930	.00339	-.00140	.00120	.00600	.72400	.04952
.260	13.130	.97070	.21600	-.17670	.99440	-.01032	-.00140	.00140	.00600	.71700	.05040
.260	15.280	1.08640	.27050	-.18140	1.11920	-.02553	-.00150	.00100	.00700	.71100	.05272
.260	17.420	1.19390	.33260	-.18320	1.23870	-.04015	-.00170	.00000	.01000	.70600	.05496
.260	19.550	1.28050	.40140	-.17730	1.34100	-.05029	-.00090	-.00040	.00900	.70000	.05732
.260	21.680	1.36060	.50130	-.18030	1.44960	-.03694	-.00020	-.00110	.01000	.69700	.06473
.260	23.860	1.43960	.60120	-.18260	1.57610	-.04942	-.00250	-.00030	.02900	.69400	.07032
.260	25.900	1.44520	.65190	-.13720	1.58480	-.04507	-.00070	.00070	.01300	.69400	.07597
.260	GRADIENT	.04542	.00437	-.00104	.04635	-.00035	-.00007	.00002	.00019	-.09614	-.00019

REPRODUCTION OF THE ORIGINAL PAGE IS POOR



(RF0033) (05 JUL 74)

CA119A 061C11F12M31M124E40V19R1320

PARAMETRIC DATA

BREF = 2090.0100 50.FT. XMRP = 1076.4000 INCHES BETA = .000 90FLAP = -12.000
 LREF = 474.0100 INCHES YMRP = .0000 INCHES ELEVGM = .000 AILFGM = .000
 BREF = 936.0000 INCHES XMRP = 375.0000 INCHES RUDDER = .000 SPOBRK = 23.000
 SCALE = .0405 SCALE

REFERENCE DATA

70. INJ. 55/ 0 RM/L = 1.05 GRADIENT INTERVAL = -6.00/ 6.00

HACH	ALPHA	CLM	CLM	CM	CAF	CYN	CBL	CY	XCP/L	CAC
.260	-10.600	.05160	.05160	-.36480	.00407	-.00020	.00070	-.00200	.66400	.04449
.260	-8.540	.04910	.04910	-.47130	.00992	-.00010	.00070	-.00100	.69000	.04475
.260	-6.390	.04630	.04630	-.36050	.01320	-.00010	.00060	-.00100	.69900	.04405
.260	-4.290	.03920	.03920	-.23650	.02522	-.00020	.00090	-.00200	.71300	.04395
.260	-2.160	.03070	.03070	-.13540	.02485	-.00060	.00050	-.00000	.73200	.04299
.260	-.070	.02620	.02620	-.06040	.02614	-.00060	.00050	.00000	.90300	.04297
.260	2.060	.03720	.03720	.04090	.02394	-.00060	.00050	.00100	.23700	.04290
.260	4.170	.03350	.03350	.13510	.01789	-.00060	.00060	.00100	.34200	.04229
.260	6.310	.03340	.03340	.23570	.00796	-.00090	.00050	.00300	.59000	.04173
.260	8.430	.03710	.03710	.34010	-.00492	-.00070	.00050	.00300	.61000	.04194
.260	10.550	.04630	.04630	.44020	-.01940	-.00090	.00050	.00400	.61700	.04230
.260	17.760	.04600	.04600	.55180	-.03327	-.00090	.00030	.00500	.62300	.04329
.260	14.050	.05770	.05770	.66670	-.05192	-.00090	.00030	.00600	.62900	.04319
.260	16.990	.06350	.06350	.80040	-.06883	-.00130	.00060	.00400	.63700	.04674
.260	19.150	.05060	.05060	.92960	-.08437	-.00090	-.00030	.01000	.64100	.04932
.260	21.320	1.01310	.02390	1.05030	-.09328	.00010	-.00010	.00900	.64300	.05204
.260	23.400	1.13320	.00730	1.19520	-.09260	.00090	.00040	.01000	.64900	.05764
.260	25.590	1.15430	.02190	1.26930	-.09162	.00020	.00160	.01200	.64300	.06174
GRADIENT	.04375	-.00036	-.00042	.04620	-.00023	-.00099	-.00003	.00033	-.03946	-.00016



(RF0036) (09 JUL 74)

GALL19A 081C11F12M51W12E40V19R1329

BETA = .000 BDFLAP = -12.000
 ELEVOM = 15.001 AIRFCM = .000
 RUDDER = .000 SPOBRK = 25.000

REF = 2690.0100 SQ.FT. ZMRP = 1076.4000 INCHES
 LREF = 474.0100 INCHES YMRP = .0000 INCHES
 BREF = 936.6000 INCHES ZMRP = 373.0000 INCHES
 SCALE = .0400 SCALE

REFERENCE DATA

RUM NO. S6/ O RN/L = 1.85 GRADIENT INTERVAL = -6.00/ 6.00

PARAMETRIC DATA

MACH	ALPHA	CL	CLM	CLN	CAF	CYN	COL	CY	KCP/L	CAB
.260	-10.390	-.26930	-.06730	-.27610	.02231	-.00030	.00000	-.00100	.33600	.03245
.260	-8.230	-.15980	-.09070	-.16480	.02996	-.00060	.00130	.00000	.44900	.03298
.260	-6.080	-.04810	-.03920	-.03200	.03393	-.00070	.00120	.00000	-.02400	.03315
.260	-3.980	.05170	-.09690	.04910	.03944	-.00090	.00050	.00100	1.39399	.03309
.260	-1.860	.14580	-.10030	.14430	.04231	-.00110	.00100	.00100	.93700	.03264
.260	.230	.24110	.04240	.24130	.04136	-.00110	.03090	.00200	.93600	.03279
.260	2.350	.33330	-.10090	.33310	.03926	-.00130	.00070	.00300	.76300	.03039
.260	4.480	.42940	-.10110	.42900	.02987	-.00150	.00050	.00400	.73900	.03024
.260	6.610	.53120	-.10320	.53700	.01906	-.00130	.00090	.00500	.72400	.04974
.260	8.720	.63690	-.10730	.64330	.00599	-.00120	.00090	.00300	.71300	.04934
.260	10.890	.74860	-.11060	.76090	-.00941	-.00120	.00060	.00600	.70300	.03042
.260	13.030	.86030	-.11330	.87740	-.02462	-.00130	.00060	.00700	.69900	.03107
.260	15.180	.97920	-.11640	1.00330	-.04179	-.00110	.00090	.00600	.69300	.03314
.260	17.330	1.09750	-.12320	1.13130	-.05896	-.00120	-.00030	.00400	.69200	.03330
.260	19.470	1.19770	-.12220	1.24320	-.07126	.00090	.00090	.00400	.69400	.03742
.260	21.610	1.29070	-.13040	1.36310	-.05861	.00070	.00070	.00300	.69700	.06331
.260	23.810	1.40320	-.13790	1.50360	-.06339	-.00220	-.00090	.00200	.69300	.07003
.260	25.980	1.42260	-.10850	1.59020	-.06426	-.00020	-.00090	.01400	.67700	.07419
.260	GRADIENT	.04433	.00327	.04506	-.00110	-.00007	-.00004	.00039	-.06990	-.00034

REPRODUCIBILITY OF THIS PAGE IS POOR

CA119A 061C11F12N51W12E40V10R13R20

(197033) (09 JUL 74)

REFERENCE DATA

SREF = 2000.0100 56.FT. LMRP = 1076.4000 INCHES
 LREF = 474.0100 INCHES TMRP = .0000 INCHES
 SREF = 936.0000 INCHES ZMRP = 375.0000 INCHES
 SCALE = .0403 SCALE

PARAMETRIC DATA

BETA = .000 00FLAP = .000
 ELEPCA = 20.000 01LECA = .000
 RUDDER = .000 5PDRSK = 25.000

RUN NO. 59/0 RM/L = 1.95 GRADIENT INTERVAL = -0.00/ 0.00

MACH	ALPHA	CL	CDP	CLM	CM	CAP	CYM	CBL	CY	XCP/L	CAP
.260	-10.290	-1.6000	.04300	-1.14170	-1.59350	.03327	-0.00050	.00050	.00000	.34400	.04961
.260	-6.150	-0.5100	.04770	-1.14550	-0.38010	.03992	-0.00080	.05130	.00000	-0.26900	.05016
.260	-6.000	-0.5750	.04030	-1.15160	.05290	.04610	-0.00060	.03140	.00000	1.70500	.04996
.260	-3.900	-1.5900	.04030	-1.15560	.13590	.05104	-0.00110	.00060	.00200	1.01900	.05037
.260	-1.790	-2.5340	.04640	-1.15770	.25100	.05434	-0.00120	.00070	.00200	.92000	.04970
.260	-.330	-3.4700	.05540	-1.15910	.34610	.05349	-0.00130	.00080	.00300	.82000	.04915
.260	2.440	-4.3920	.06750	-1.15990	.44170	.04874	-0.00130	.00070	.00300	.74400	.04926
.260	4.530	-5.3650	.08340	-1.16200	.54150	.04077	-0.00140	.00080	.00400	.76200	.04922
.260	6.670	-6.4170	.10500	-1.16630	.64960	.02975	-0.00130	.00040	.00500	.74600	.04777
.260	8.830	-7.5900	.13450	-1.17440	.77150	.01623	-0.00130	.00030	.00600	.73500	.04412
.260	10.970	-8.9900	.17060	-1.17740	.90630	.00196	-0.00140	.00040	.00700	.72500	.04440
.260	13.100	-9.7960	.21460	-1.19000	1.00270	-.01306	-0.00120	.00060	.00700	.71400	.04931
.260	15.270	-1.09600	.26630	-1.19330	1.12000	-.02094	-0.00120	.00070	.00400	.71100	.05167
.260	17.430	1.20460	.33010	-1.18460	1.24920	-.04594	-0.00110	.00110	.01000	.70600	.05424
.260	19.570	1.29370	.40300	-1.18020	1.35400	-.05364	-0.00070	.00060	.00900	.70100	.05712
.260	21.720	1.39510	.51240	-1.19290	1.44560	-.04046	-0.00040	.00110	.00800	.69900	.06425
.260	23.990	1.50400	.61600	-1.19910	1.62330	-.04625	-0.00220	.00430	.02700	.69700	.06949
.260	25.930	1.50190	.67633	-1.19920	1.64640	-.04967	-.00000	.00220	.01100	.69700	.07317
GRADIENT		.04513	.00415	-.00046	.04605	-.00047	-.00006	-.00005	.00033	-.01424	-.00021



(RF0061) (09 JUL 74)

GA119A 061C11F12M51M124E48V19R15Z29

PARAMETRIC DATA

BETA = .000 SDFLAP = .000
 ELEVGM = 15.000 AILRCM = .000
 RUDDER = .000 SPOBRK = 45.000

REFERENCE DATA

MACH = 2890.0100 SQ.FT. YMRP = 1076.4898 INCHES
 LREF = 474.8100 INCHES YMRP = .0000 INCHES
 BREF = 936.8800 INCHES ZMRP = 375.0000 INCHES
 SCALE = .0405 SCALE

RUN NO. 61/ 0 RM/L = 1.05 GRADIENT INTERVAL = -6.00/ 6.00

MACH	ALPHA	CL	CDP	CLM	CN	CAF	CYM	CBL	CT	KCP/L	CAS
.200	-10.400	-.25610	.06750	-.09910	-.26400	.02015	-.00070	.00040	.00000	.51400	.04764
.200	-8.270	-.14720	.04680	-.10220	-.19270	.02717	-.00090	.00120	.00000	.40300	.04751
.200	-6.140	-.03760	.03630	-.10700	-.04130	.03206	-.00120	.00110	.00100	-.30900	.04434
.200	-4.000	.06330	.03320	-.11050	.06080	.03761	-.00160	.00030	.00300	1.32000	.04769
.200	-1.870	.15990	.03580	-.11250	.15060	.04104	-.00190	.00030	.00400	.91300	.04771
.200	.220	.23360	.04160	-.11374	.29390	.04062	-.00190	.00030	.00500	.91600	.04717
.200	2.320	.34930	.04980	-.11490	.35100	.03562	-.00170	.00010	.00500	.77200	.04709
.200	4.470	.44800	.06260	-.11590	.44930	.02772	-.00170	.00010	.00500	.74700	.04626
.200	6.590	.55170	.08130	-.11990	.55730	.01735	-.00160	.00030	.00600	.73100	.04517
.200	8.720	.65880	.10450	-.12340	.66700	.00352	-.00130	.00030	.00600	.72000	.04577
.200	10.850	.76790	.13370	-.12550	.77970	-.01137	-.00160	.00030	.00700	.71100	.04641
.200	12.990	.87830	.17460	-.12770	.89510	-.02743	-.00160	.00020	.00700	.70400	.04743
.200	15.170	.99960	.22530	-.13300	1.02380	-.04001	-.00130	.00020	.00700	.69900	.04369
.200	17.320	1.11630	.28510	-.13740	1.15060	-.06024	-.00110	-.00010	.00900	.69600	.03168
.200	19.460	1.21590	.35280	-.13620	1.26400	-.07251	-.00020	.00020	.00700	.69100	.03410
.200	21.670	1.31350	.43730	-.14510	1.36930	-.06016	.00070	.00070	.00600	.69000	.06141
.200	23.800	1.42080	.56080	-.15540	1.53360	-.06346	-.00210	-.00390	.02400	.64900	.06690
.200	25.900	1.45360	.63330	-.12700	1.58440	-.06507	-.00010	.00230	.01100	.68100	.07192
.200	GRADIENT	.04519	.00345	-.00062	.04590	-.00119	-.00001	-.00006	.00024	-.06090	-.00017